

Welding nipples/adapters

Welding nipples similar to EN 10241/DIN 2982
















	,	 /-		702		٠,		
Type 20 bar wox	Type 50 bar, ST 37			Type 20 bar	INOX	Type 50 bar, ST 37		
AISI 316Ti	black steel	Thread	L	AISI 316Ti	3	black steel	Thread	L
Diameter 10.2 mm	(1/8")			Diameter 42.	4 mm (1	1/4")		
RONI 18/30 AS ES		R 1/8"	30*	RONI 114/50		· ,	R 1 1/4"	50*
RONI 18/40 AS ES		R 1/8"	40	RONI 114/60		RONI 114/60 AS ST		
RONI 18/60 AS ES		R 1/8"	60	RONI 114/80		RONI 114/80 AS ST		
RONI 18/80 AS ES		R 1/8"	80	RONI 114/10		RONI 114/100 AS S		
RONI 18/100 AS ES		R 1/8"	100	RONI 114/12		RONI 114/120 AS S		
Diameter 13.5 mm	(1/4")	IC -70	100	RONI 114/13		RONI 114/130 AS S		
RONI 14/30 AS ES	RONI 14/30 AS ST	R 1/4"	30*	Diameter 48.			10 1 7 4	100
RONI 14/40 AS ES	RONI 14/40 AS ST	R 1/4"	40	RONI 112/50		RONI 112/50 AS ST	R 1 1/2"	50*
RONI 14/60 AS ES	RONI 14/60 AS ST	R 1/4"	60	RONI 112/60		RONI 112/60 AS ST		
RONI 14/80 AS ES	RONI 14/80 AS ST	R 1/4"	80	RONI 112/80		RONI 112/80 AS ST		
RONI 14/100 AS ES	RONI 14/100 AS ST	R 1/4"		RONI 112/10		RONI 112/100 AS ST		
			100					
RONI 14/120 AS ES	RONI 14/120 AS ST	R 1/4"	120	RONI 112/12		RONI 112/120 AS S		
RONI 14/160 AS ES	RONI 14/160 AS ST	R 1/4"	160	RONI 112/15			R 1 1/2"	
RONI 14/200 AS ES	RONI 14/200 AS ST	R 1/4"	200	RONI 112/30			R 1 1/2"	300
Diameter 17.2 mm				Diameter 60.		<u> </u>		
RONI 38/30 AS ES	RONI 38/30 AS ST	R 3/8"	30*	RONI 20/50		RONI 20/50 AS ST	R 2"	50*
RONI 38/40 AS ES	RONI 38/40 AS ST	R 3/8"	40	RONI 20/60		RONI 20/60 AS ST	R 2"	60
RONI 38/60 AS ES	RONI 38/60 AS ST	R 3/8"	60	RONI 20/80		RONI 20/80 AS ST	R 2"	80
RONI 38/80 AS ES	RONI 38/80 AS ST	R 3/8"	80	RONI 20/100		RONI 20/100 AS ST	R 2"	100
RONI 38/100 AS ES		R 3/8"	100	RONI 20/120		RONI 20/120 AS ST	R 2"	120
RONI 38/120 AS ES	RONI 38/120 AS ST	R 3/8"	120	RONI 20/200	AS ES	RONI 20/200 AS ST	R 2"	200
RONI 38/350 AS ES	RONI 38/350 AS ST	R 3/8"	350	RONI 20/400	AS ES		R 2"	200
Diameter 21.3 mm	(1/2")			Diameter 76.	1 mm (2	!1/2")		
RONI 12/35 AS ES	RONI 12/35 AS ST	R 1/2"	35*	RONI 212/50	AS ES	RONI 212/50 AS ST	R 2 1/2"	50
RONI 12/40 AS ES	RONI 12/40 AS ST	R 1/2"	40	RONI 212/60	AS ES	RONI 212/60 AS ST	R 2 1/2"	60*
RONI 12/60 AS ES	RONI 12/60 AS ST	R 1/2"	60	RONI 212/80	AS ES	RONI 212/80 AS ST	R 2 1/2"	80
RONI 12/80 AS ES	RONI 12/80 AS ST	R 1/2"	80	RONI 212/10	O AS ES	RONI 212/100 AS S	R 2 1/2"	100
RONI 12/100 AS ES	RONI 12/100 AS ST	R 1/2"	100	RONI 212/12	O AS ES	RONI 212/120 AS S	TR 2 1/2"	120
RONI 12/120 AS ES	RONI 12/120 AS ST	R 1/2"	120	RONI 212/17	O AS ES	RONI 212/170 AS S	TR 2 1/2"	170
Diameter 26.9 mm	·			Diameter 88.		•		
RONI 34/30 AS ES	RONI 34/30 AS ST	R 3/4"	30	RONI 30/50		RONI 30/50 AS ST	R 3"	50
RONI 34/40 AS ES	RONI 34/40 AS ST	R 3/4"	40*	RONI 30/60		RONI 30/60 AS ST	R 3"	60
RONI 34/60 AS ES	RONI 34/60 AS ST	R 3/4"	60	RONI 30/70		RONI 30/70 AS ST	R 3"	70*
RONI 34/80 AS ES	RONI 34/80 AS ST	R 3/4"	80	RONI 30/80		RONI 30/80 AS ST	R 3"	80
RONI 34/100 AS ES	RONI 34/100 AS ST	R 3/4"	100	RONI 30/100		RONI 30/100 AS ST	R 3"	100
RONI 34/120 AS ES	RONI 34/120 AS ST	R 3/4"	120	RONI 30/120		RONI 30/120 AS ST		120
				-			K 3	120
RONI 34/200 AS ES		R 3/4"	200	Diameter 114			D 4#	
Diameter 33.7 mm	· ,	D 1#	40*	RONI 40/50		RONI 40/50 AS ST	R 4"	50
RONI 10/40 AS ES	RONI 10/40 AS ST	R 1"	40*	RONI 40/60		RONI 40/60 AS ST	R 4"	60*
RONI 10/60 AS ES	RONI 10/60 AS ST	R 1"	60	RONI 40/80		RONI 40/80 AS ST	R 4"	80
RONI 10/80 AS ES	RONI 10/80 AS ST	R 1"	80	RONI 40/100		RONI 40/100 AS ST	R 4"	100
RONI 10/100 AS ES	RONI 10/100 AS ST	R 1"	100	RONI 40/120	AS ES	RONI 40/120 AS ST	R 4"	120
RONI 10/120 AS ES	RONI 10/120 AS ST	R 1"	120					
* DIN installation length								

up to 50 bar

Hose nozzles with weld ends			PN 20
Type Mox		Hose Ø	Install.
AISI 316Ti	D	internal	length
ST 1413 AS ES	13.5 (1/4")	13	70
ST 3816 AS ES	17.2 (3/8")	16	70
ST 1219 AS ES	21.3 (1/2")	19	70
ST 3425 AS ES	26.9 (3/4")	25	70
ST 1032 AS ES	33.7 (1")	32	70
ST 11440 AS ES	42.4 (11/4")	40	70
ST 11250 AS ES	48.3 (11/2")	48 (50*)	100
ST 2060 AS ES	60.3 (2")	60	100
ST 21275 AS ES	76.1 (21/2")	75	120
ST 3090 AS ES	88.9 (3")	88 (90*)	120

* with flexible hoses when using suitable hose clips

Double nipples with JIC threads			up to 310 bar		
Type zinc-plated steel	Type AISI 316Ti	Thread	Thread	PN*	
DN 7/16-7/16	DN 7/16-7/16 ES	UNF 7/16"-20	UNF 7/16"-20	310 bar	
DN 1/2-1/2	DN 1/2-1/2 ES	UNF 1/2"-20	UNF 1/2"-20	275 bar	
DN 9/16-7/16	DN 9/16-7/16 ES	UNF 9/16"-18	UNF 7/16"-20	275 bar	
DN 9/16-1/2		UNF 9/16"-18	UNF 1/2"-20	275 bar	
DN 9/16-9/16	DN 9/16-9/16 ES	UNF 9/16"-18	UNF 9/16"-18	275 bar	
DN 3/4-9/16	DN 3/4-9/16 ES	UNF 3/4"-16	UNF 9/16"-18	275 bar	
DN 3/4-3/4	DN 3/4-3/4 ES	UNF 3/4"-16	UNF 3/4"-16	275 bar	
DN 7/8-1/2		UNF 7/8"-14	UNF 1/2"-20	210 bar	
DN 7/8-3/4	DN 7/8-3/4 ES	UNF 7/8"-14	UNF 3/4"-16	210 bar	
DN 7/8-7/8	DN 7/8-7/8 ES	UNF 7/8"-14	UNF 7/8"-14	210 bar	
DN 11/16-3/4	DN 11/16-3/4 ES	UN 1 1/16"-12	UNF 3/4"-16	210 bar	

 $^{^{}st}$ the safety factor reached in tests with hydraulic oil was four-times, please ask in individual cases

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.