

Double nipples with right-hand threads/left-hand threads

PN 16

Type	Thread	Thread	SW	Type	Thread	Thread	SW
brass				brass			
DN 1414 MS RHLH	G 1/4"	G 1/4" LH	17	DN 1010 MS RHLH	G 1"	G 1" LH	36
DN 3838 MS RHLH	G 3/8"	G 3/8" LH	19	DN 114114 MS RHLH	G 1 1/4"	G 1 1/4" LH	46
DN 1212 MS RHLH	G 1/2"	G 1/2" LH	22	DN 112112 MS RHLH	G 1 1/2"	G 1 1/2" LH	50
DN 3434 MS RHLH	G 3/4"	G 3/4" LH	27				

Double nipples with left-hand threads

PN 16

Type	Thread	Thread	SW
brass			
DN 1414 MS LH	G 1/4" LH	G 1/4" LH	17
DN 3838 MS LH	G 3/8" LH	G 3/8" LH	19

Double nipples with metric threads/G threads and metric threads

PN 16

Type	Thread	Thread	SW
brass			
Imperial/metric threads			
DN 14-M14 MS	G 1/4"	M 14 x 1.5	17
DN 14-M16 MS	G 1/4"	M 16 x 1.5	19
DN 38-M14 MS	G 3/8"	M 14 x 1.5	19
DN 38-M16 MS	G 3/8"	M 16 x 1.5	19
DN 12-M24 MS	G 1/2"	M 24 x 1.5	27
Metric/metric threads			
DN M14-M14 MS	M 14 x 1.5	M 14 x 1.5	17
DN M16-M14 MS	M 16 x 1.5	M 14 x 1.5	17
DN M16-M16 MS	M 16 x 1.5	M 16 x 1.5	19
DN M24-M24 MS	M 24 x 1.5	M 24 x 1.5	27

Double nipples with R threads/NPT threads

PN 60

Type	Thread	Thread	SW	Length	Type	Thread	Thread	SW	Length
brass nickel-plated					brass nickel-plated				
DN 18R18NPT MSV	R 1/8"	NPT 1/8"	11	27	DN 12R12NPT MSV	R 1/2"	NPT 1/2"	22	46
DN 14R14NPT MSV	R 1/4"	NPT 1/4"	14	35	DN 34R34NPT MSV	R 3/4"	NPT 3/4"	27	47
DN 38R38NPT MSV	R 3/8"	NPT 3/8"	17	37					

Double nipples with G threads/NPT threads

PN 40

Type	Thread	Thread	SW	Length	Type	Thread	Thread	SW	Length
AISI 316Ti					AISI 316Ti				
DN 18G18NPT ES	G 1/8"	NPT 1/8"	14	26	DN 10G10NPT ES	G 1"	NPT 1"	41	55
DN 14G14NPT ES	G 1/4"	NPT 1/4"	19	33.5	DN 114G114NPT ES	G 1 1/4"	NPT 1 1/4"	50	66
DN 38G38NPT ES	G 3/8"	NPT 3/8"	22	38	DN 112G112NPT ES	G 1 1/2"	NPT 1 1/2"	55	64
DN 12G12NPT ES	G 1/2"	NPT 1/2"	27	43	DN 20G20NPT ES	G 2"	NPT 2"	70	66
DN 34G34NPT ES	G 3/4"	NPT 3/4"	32	47					

High pressure double nipples G threads/NPT threads

up to 800 bar

Type	Thread	Thread	PN
zinc-plated steel	with internal cone		
HDA 14	G 1/4"	NPT 1/4"	800 bar*
HDA 38	G 3/8"	NPT 3/8"	700 bar*

* with 2-fold safety

Double nipples with NPT threads

up to 345 bar

Type	Type	Thread	Thread	SW	Length**	PN*
zinc-plated steel	AISI 316Ti					
DN 1818 NPT	DN 1818 NPT ES	NPT 1/8"	NPT 1/8"	12	27.0	345 bar
DN 1418 NPT	DN 1418 NPT ES	NPT 1/4"	NPT 1/8"	14	30.5	275 bar
DN 1414 NPT	DN 1414 NPT ES	NPT 1/4"	NPT 1/4"	14	36.5	275 bar
DN 3818 NPT	DN 3818 NPT ES	NPT 3/8"	NPT 1/8"	17	30.5	210 bar
DN 3814 NPT	DN 3814 NPT ES	NPT 3/8"	NPT 1/4"	19	36.5	210 bar
DN 3838 NPT	DN 3838 NPT ES	NPT 3/8"	NPT 3/8"	19	36.5	210 bar
DN 1214 NPT	DN 1214 NPT ES	NPT 1/2"	NPT 1/4"	22	40.5	210 bar
DN 1238 NPT	DN 1238 NPT ES	NPT 1/2"	NPT 3/8"	22	43.7	210 bar
DN 1212 NPT	DN 1212 NPT ES	NPT 1/2"	NPT 1/2"	22	48.4	210 bar
DN 3412 NPT	DN 3412 NPT ES	NPT 3/4"	NPT 1/2"	27	50.0	170 bar
DN 3434 NPT	DN 3434 NPT ES	NPT 3/4"	NPT 3/4"	27	50.0	170 bar
DN 1034 NPT	DN 1034 NPT ES	NPT 1"	NPT 3/4"	36	54.0	140 bar
DN 1010 NPT	DN 1010 NPT ES	NPT 1"	NPT 1"	36	59.0	140 bar
DN 114114 NPT	DN 114114 NPT ES	NPT 1 1/4"	NPT 1 1/4"	46	63.0	80 bar

* the safety factor reached in tests with hydraulic oil was four-times, please ask in individual cases,

** Details apply for stainless steel type. For all other types, please ask.

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.

