

## **Reducing nipples**

## Reducing nipples with conical male and cylindrical female threads up to 25 bar Type 16 bar Twox Type 16 bar Mox Type 25 bar mall Thread Type 25 bar mall. Thread Thread Thread cast iron galv. **AISI 316** male female cast iron galv. **AISI 316** male female RN 1418 K ST RN 1418 K ES R 1/4' RN 114112 K ST Rp 1 1/2 Rp 1/8 R 1 1/4" RN 1438 K ST R 1/4" Rp 3/8" RN 11420 K ST Rp 2" Rp 1/2" RN 1412 K ST R 1/4" Rp 1/2" RN 11212 K ST RN 11212 K ES R 1 1/2" R 1 1/2" RN 3818 K ES R 3/8" Rp 1/8" RN 11234 K ST RN 11234 K ES Rp 3/4" R 1 1/2" Rp 1" R 3/8" Rp 1/4" RN 11210 K ES RN 3814 K ST RN 3814 K ES RN 11210 K ST RN 3812 K ST R 3/8" Rp 1/2" RN 112114 K ST R 1 1/2" Rp 1 1/4" Rp 2" RN 1218 K ES R 1/2" Rp 1/8" RN 11220 K ST R 11/2" Rp 1/2" RN 1214 K ST RN 1214 K ES R 1/2" Rp 1/4" RN 2012 K ST R 2" RN 1238 K ST R 1/2" Rp 3/8" R 2" Rp 3/4" RN 1238 K ES RN 2034 K ST Rp 1" R 1/2" R 2" Rp 3/4" RN 2010 K ES RN 1234 K ST RN 2010 K ST Rp 1 1/4" RN 1210 K ST R 1/2" Rp 1" RN 20114 K ST RN 20114 K ES R 2" Rp 1/4" R 2" Rp 1 1/2" RN 3414 K ST RN 3414 K ES R 3/4" RN 20112 K ST RN 20112 K ES RN 3438 K ST RN 3438 K ES R 3/4" Rp 3/8" RN 20212 K ST R 2" Rp 2 1/2 R 3/4" Rp 1/2" RN 2030 K ST R 2" RN 3412 K ST Rp 3" RN 3412 K ES R 3/4" Rp 1" RN 3410 K ST RN 212114 K ST R 2 1/2" Rp 1 1/4" Rp 1 1/4" RN 34114 K ST R 3/4" RN 212112 K ST RN 212112 K ES R 21/2" Rp 1 1/2" Rp 2" RN 1038 K ST Rp 3/8" RN 21220 K ST RN 21220 K ES R 21/2" R 1" Rp 1/2" Rp 3" RN 1012 K ES RN 21230 K ST R 2 1/2 RN 1012 K ST Rp 1" R 1" RN 1034 K ES Rp 3/4" RN 1034 K ST RN 3010 K ST R 34 R 1" Rp 1 1/4" RN 10114 K ST Rp 1 1/4" RN 30114 K ST R 3" RN 10112 K ST R 1" Rp 1 1/2' RN 30112 K ST RN 30112 K ES R 3" Rp 1 1/2" R 1" Rp 2" RN 3020 K ES R 3" Rp 2" RN 1020 K ST RN 3020 K ST Rp 1/2" Rp 2 1/2 R 11/4" R 3" RN 11412 K ST RN 30212 K ST RN 30212 K ES Rp 2" RN 11434 K ST RN 11434 K ES R 1 1/4" Rp 3/4" R 4" RN 4020 K ST Rp 1" R 4" Rp 3" R 1 1/4" RN 11410 K ST RN 11410 K ES RN 4030 K ST RN 4030 K ES



## Thread enlargements with conical male and cyl. female threads

Type <b>brass</b>	Thread	Thread
nickel-plated	male	female
RN 1818 K MSV	R 1/8"	Rp 1/8"
RN 1814 K MSV	R 1/8"	Rp 1/4"
RN 1838 K MSV	R 1/8"	Rp 3/8"
RN 1812 K MSV	R 1/8"	Rp 1/2"
RN 1414 K MSV	R 1/4"	Rp 1/4"
RN 1438 K MSV	R 1/4"	Rp 3/8"
RN 1412 K MSV	R 1/4"	Rp 1/2"

Type <b>brass</b>	Thread	Thread
nickel-plated	male	female
RN 1434 K MSV	R 1/4"	Rp 3/4"
RN 3838 K MSV	R 3/8"	Rp 3/8"
RN 3812 K MSV	R 3/8"	Rp 1/2"
RN 3834 K MSV	R 3/8"	Rp 3/4"
RN 1212 K MSV	R 1/2"	Rp 1/2"
RN 1234 K MSV	R 1/2"	Rp 3/4"
RN 3434 K MSV	R 3/4"	Rp 3/4"





High pressure swivel joints from page 140



Service units from page 330



Kamlock couplings from page 186

PN 16



Brass nickel-plated reducing, connecting and and closing nozzle: rom M5 up to 1" on page 596



Coupling sockets NW7 from page 150







Pressure gauge from page 366



Liquid seals, gaskets & tapes from page 549



PU, PA, PTFE and PE hoses from page 192



Work gloves on page 589



Threaded nozzles & hose nozzles from page 64



2/2, 3/2 directional valves of brass or stainless steel from page 404

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C