Angle fittings



Angles 90° with female threads (forged)			up to 150 bar	
Type 16 bar brass nickel-pl.	Type 16 bar	Type 150 bar AISI 316L	Thread	
W 50 MSV			M5	
W 18 MSV	W 18 MS*	W 18 MD ES	G 1/8"	
W 14 MSV	W 14 MS	W 14 MD ES	G 1/4"	
W 38 MSV	W 38 MS	W 38 MD ES	G 3/8"	
W 12 MSV	W 12 MS	W 12 MD ES	G 1/2"	
W 34 MSV	W 34 MS		G 3/4"	
W 10 MSV	W 10 MS		G 1"	
	W 114 MS		G 11/4"	
	W 112 MS		G 11/2"	

design as for MSV



Angles 90° with female threads (cast)				up to 25 bar		
Type 10 bar AISI 316	Type 16 bar Nox	Type 25 bar mall. cast iron galv.	Thread	Type 16 bar Nox	Thread	
Standard						
W 18 ES E	W 18 ES		Rp 1/8"	W 18 ES NPT	NPT 1/8"	
W 14 ES E	W 14 ES	W 14 ST	Rp 1/4"	W 14 ES NPT	NPT 1/4"	
W 38 ES E	W 38 ES	W 38 ST	Rp 3/8"	W 38 ES NPT	NPT 3/8"	
W 12 ES E	W 12 ES	W 12 ST	Rp 1/2"	W 12 ES-NPT	NPT 1/2"	
W 34 ES E	W 34 ES	W 34 ST	Rp 3/4"	W 34 ES-NPT	NPT 3/4"	
W 10 ES E	W 10 ES	W 10 ST	Rp 1"	W 10 ES-NPT	NPT 1"	
W 114 ES E	W 114 ES	W 114 ST	Rp 1 1/4"	W 114 ES-NPT	NPT 1 1/4"	
W 112 ES E	W 112 ES	W 112 ST	Rp 1 1/2"	W 112 ES-NPT	NPT 1 1/2"	
W 20 ES E	W 20 ES	W 20 ST	Rp 2"	W 20 ES-NPT	NPT 2"	
	W 212 ES	W 212 ST	Rp 2 1/2"			
	W 30 ES	W 30 ST	Rp 3"			
	W 40 ES	W 40 ST	Rp 4"			
Reduced						
		W 1238 ST	Rp 1/2" / Rp 3/8"			
		W 3412 ST	Rp 3/4" / Rp 1/2"			
		W 1012 ST	Rp 1" / Rp 1/2"			
		W 1034 ST	Rp 1" / Rp 3/4"			
		W 11410 ST	Rp 1 1/4" / Rp 1"			
		W 112114 ST	Rp 1 1/2" / Rp 1 1/4"			
		W 20112 ST	Rp 2" / Rp 1 1/2"			




Elbows 90° with female threads

PN 25

Materials: Malleable cast iron galvanised

lype		lype		
long (2)	L	short (2a)	L	Thread
BO 14 i ST	40			Rp 1/4"
BO 38 i ST	48			Rp 3/8"
BO 12 i ST	55	BO 12 iK ST	45	Rp 1/2"
BO 34 i ST	69	BO 34 iK ST	50	Rp 3/4"
BO 10 i ST	85	BO 10 iK ST	63	Rp 1"
BO 114 i ST	105	BO 114 iK ST	76	Rp 1 1/4"

Туре		Туре		
long (2)	L	short (2a)	L	Thread
BO 112 i ST	116	BO 112 iK ST	85	Rp 11/2"
BO 20 i ST	140	BO 20 iK ST	102	Rp 2"
BO 212 i ST	176			Rp 21/2"
BO 30 i ST	205			Rp 3"
BO 40 i ST	260			Rp 4"





Threaded angles PVC-	• U (for plastic threads only
----------------------	--------------------------------------

PN 10

Note: • Do not use PVC-U damaging thread seals!

Warning: Not suitable for compressed air or other gases under pressure!

		External Ø	Installation length
Туре	Thread	D	L
W 38 PVC	Rp ³ /8"	23.5	23
W 12 PVC	Rp 1/2"	28.0	25
W 34 PVC	Rp ³ /4"	34.0	30
W 10 PVC	Rp 1"	43.0	36
W 114 PVC	Rp 1 1/4"	54.0	41
W 112 PVC	Rp 1 1/2"	63.0	46
W 20 PVC	Rp 2"	78.0	57
W 212 PVC	Rp 21/2"	89.0	84
W 30 PVC	Rp 3"	106.0	99
W 40 PVC	Rp 4"	129.0	119

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at $\pm 20^{\circ}$ C.