

Distributors/pipeline sockets

2



type 180/C1

Cross pieces			up to 25 bar		
Type 16 bar brass nickel-pl.	Type 16 bar brass	Thread	Type 16 bar AISI 316	Type 25 bar mall. cast iron galv.	Thread
K 18 MSV	K 18 MS*	G 1/8"	K 18 ES	---	Rp 1/8"
K 14 MSV	K 14 MS*	G 1/4"	K 14 ES	K 14 ST	Rp 1/4"
K 38 MSV	K 38 MS*	G 3/8"	K 38 ES	K 38 ST	Rp 3/8"
K 12 MSV	K 12 MS*	G 1/2"	K 12 ES	K 12 ST	Rp 1/2"
---	K 34 MS	G 3/4"	K 34 ES	K 34 ST	Rp 3/4"
---	K 10 MS	G 1"	K 10 ES	K 10 ST	Rp 1"
---	K 114 MS	G 1 1/4"	K 114 ES	K 114 ST	Rp 1 1/4"
---	K 112 MS	G 1 1/2"	K 112 ES	K 112 ST	Rp 1 1/2"
---	K 20 MS	G 2"	K 20 ES	K 20 ST	Rp 2"
---	---	---	K 212 ES	K 212 ST	Rp 2 1/2"
---	---	---	K 30 ES	K 30 ST	Rp 3"
---	---	---	K 40 ES	K 40 ST	Rp 4"

* design as for MSV




type 220

Air junctions, 2-way			up to 25 bar		
Type 16 bar brass nickel-pl.	Thread	Type 16 bar brass	Type 16 bar AISI 316	Type 25 bar mall. cast iron galv.	Thread
Y 18 MSV	G 1/8"	---	---	---	---
Y 14 MSV	G 1/4"	---	Y 14 ES	---	Rp 1/4"
Y 38 MSV	G 3/8"	LW 238 MS	Y 38 ES	Y 38 ST	Rp 3/8"
Y 12 MSV	G 1/2"	LW 212 MS	Y 12 ES	Y 12 ST	Rp 1/2"
---	---	---	Y 34 ES	Y 34 ST	Rp 3/4"
---	---	---	Y 10 ES	Y 10 ST	Rp 1"
---	---	---	Y 114 ES	---	Rp 1 1/4"
---	---	---	Y 112 ES	---	Rp 1 1/2"
---	---	---	Y 20 ES	---	Rp 2"
---	---	---	Y 212 ES	---	Rp 2 1/2"
---	---	---	Y 30 ES	---	Rp 3"

Air junctions, 3-way		PN 16
Type brass	Thread	
LW 338 MS	G 3/8"	
LW 312 MS	G 1/2"	



Y-pieces (female/female/male)			PN 16
Type brass nickel-plated	Thread male	Thread female	
YE 18 MSV	R 1/8"	G 1/8"	
YE 14 MSV	R 1/4"	G 1/4"	
YE 38 MSV	R 3/8"	G 3/8"	
YE 12 MSV	R 1/2"	G 1/2"	



Pipeline sockets with push-in fittings			PN 16
Type brass	Thread	Push in tube Ø external	Outlets
WD 1215 MS	G 1/2"	15	1 x upwards, 1 x at the front
WD 3422 MS	G 3/4"	22	1 x upwards, 1 x at the front



Pipeline sockets			PN 16
Type brass	Type AISI 316	Thread	Outlets
WD 38 MS	WD 38 ES	G 3/8"	1 x upwards, 1 x at the front
WD 12 MS	WD 12 ES	G 1/2"	1 x upwards, 1 x at the front
WD 34 MS	WD 34 ES	G 3/4"	1 x upwards, 1 x at the front



Threaded nozzles & hose nozzles from page 64



LOCTITE
Liquid seals,
gaskets & tapes
from page 549



Parker
Push in hoses
on page 228



Ball valves
from page 280

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.