

Pipeline sockets/air junctions, 5-way

PN 16

Type	Thread	Outlets
brass		
WD 12 LW3 MS	G 1/2"	1 x upwards, 1 x downwards, 3 x at the front



Pipeline sockets/distributors, 5-way

PN 16

Type	Thread	Outlets
brass		
WD 12 VT MS	G 1/2"	1 x upwards, 1 x downwards, 2 x on the side, 1 x at the front



Pipeline sockets/air junctions made of plastic

PN 15

Temperature range: -10°C to max. +50°C

Type with 2 outlets	Type with 3 outlets	Upper input thread	Front output thread	Lower through-hole thread
End junction box without through-hole thread				
WD 12 LW 2 K	WD 12 LW 3 K	G 1/2"	G 1/2"	---
WD 12 LW 2 K-34	WD 12 LW 3 K-34	G 3/4"	G 1/2"	---
Through-way junction box				
WD 12 LW 2 KD	WD 12 LW 3 KD	G 1/2"	G 1/2"	G 1/2"
WD 12 LW 2 KD-34	WD 12 LW 3 KD-34	G 3/4"	G 1/2"	G 3/4"



Air junctions with female threads and coupling sockets NW 7.2

Materials: Housing: Brass, seals: NBR

Temperature range: -20°C to max. +100°C

Operating pressure: 0 - 35 bar as well as large vacuum

Type	Input E	Output
2-way		
LWKDG 238 NW7	G 3/8" (FT)	2 x coupling sockets NW 7.2
LWKDG 212 NW7	G 1/2" (FT)	2 x coupling sockets NW 7.2
3-way		
LWKDG 338 NW7	G 3/8" (FT)	3 x coupling sockets NW 7.2
LWKDG 312 NW7	G 1/2" (FT)	3 x coupling sockets NW 7.2



Air junctions with male threads and coupling sockets NW 7.2

Materials: Housing: Brass, seals: NBR

Temperature range: -20°C to max. +100°C

Operating pressure: 0 - 35 bar as well as large vacuum

Type	Input E	Output
2-way		
LWKDGDN 238 NW7	G 3/8" (MT)	2 x coupling sockets NW 7.2
LWKDGDN 212 NW7	G 1/2" (MT)	2 x coupling sockets NW 7.2
3-way		
LWKDGDN 338 NW7	G 3/8" (MT)	3 x coupling sockets NW 7.2
LWKDGDN 312 NW7	G 1/2" (MT)	3 x coupling sockets NW 7.2




Pipeline sockets with coupling sockets NW 7.2

Materials: Housing: Brass, seals: NBR

Temperature range: -20°C to max. +100°C

Operating pressure: 0 - 35 bar as well as large vacuum

Type	Input E	Output
brass		
WDKDG 38 MS NW7	G 3/8" (FT)	1 x coupling socket NW 7.2
WDKDG 12 MS NW7	G 1/2" (FT)	1 x coupling socket NW 7.2
WDKDG 34 MS NW7	G 3/4" (FT)	1 x coupling socket NW 7.2



Big push-in fittings
up to Ø 32 mm
from page 24



Coupling sockets
NW7 from page 150



Bolts, nuts
and washers
from page 615



PVC fabric hoses
on page 208

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.