

Closing plugs






Blind fittings with inch threads (60° conical hose nipples)

up to 575 bar

Suitable: ROV blind fittings with a 60° cone close the hoses and pipe screw connectors that are provided with a 60° conical hose nipple in a union nut with female thread.

Type zinc-	Type V4A		
plated steel	(stainless steel)	Thread	PN*
ROV 1/8	ROV 1/8 ES	G 1/8"	575 bar
ROV 1/4	ROV 1/4 ES	G 1/4"	575 bar
ROV 3/8	ROV 3/8 ES	G 3/8"	425 bar
ROV 1/2	ROV 1/2 ES	G 1/2"	300 bar
ROV 3/4	ROV 3/4 ES	G 3/4"	175 bar
ROV 1	ROV 1 ES	G 1"	150 bar
ROV 11/4	ROV 11/4 ES	G 11/4"	150 bar
	ROV 11/2 ES	G 1 1/2"	125 bar
	ROV 2 ES	G 2"	75 bar

 $^{^{}st}$ the safety factor reached in tests with hydraulic oil was four-times, please ask in individual cases



Locking screws with JIC threads		ads up	up to 310 bar		
Type zinc- plated steel	Type V4A (stainless steel)	Thread	PN*		
VSTi 7/16 JIC	VSTi 7/16 JIC ES	UNF 7/16"-20	310 bar		
VSTi 1/2 JIC	VSTi 1/2 JIC ES	UNF 1/2"-20	275 bar		
VSTi 9/16 JIC	VSTi 9/16 JIC ES	UNF 9/16"-18	275 bar		
VSTi 3/4 JIC	VSTi 3/4 JIC ES	UNF 3/4"-16	275 bar		
VSTi 7/8 JIC	VSTi 7/8 JIC ES	UNF 7/8"-14	210 bar		
VSTi 11/16 JIC	VSTi 11/16 JIC ES	UN 11/16"-12	210 bar		
VSTi 13/16 JIC		UN 13/16"-12	170 bar		
VSTi 15/16 JIC	VSTi 15/16 JIC ES	UN 15/16"-12	170 bar		
VSTi 15/8 JIC	VSTi 15/8 JIC ES	UN 15/8"-12	140 bar		
VSTi 17/8 JIC	VSTi 17/8 JIC ES	UN 17/8"-12	100 bar		

^{*} the safety factor reached in tests with hydraulic oil was four-times, please ask in individual cases





ISO 8434-1 (DIN 2353) Closing plugs for cutting ring screw connections*

Type zinc-	Type	Un	nion nut*		For pipe screw
plated steel	AISI 316Ti	he	avy	Light	connectors
BUZ 6	BUZ 6 ES	M	6 S	M 6 L	6L/6S
BUZ 8	BUZ 8 ES	M	8 S	M 8 L	8 L / 8 S
BUZ 10	BUZ 10 ES	М	10 S	M 10 L	10 L / 10 S
BUZ 12	BUZ 12 ES	M	12 S	M 12 L	12 L / 12 S
BUZ 14	BUZ 14 ES	M	14 S		14 S
BUZ 15	BUZ 15 ES			M 15 L	15 L
BUZ 16	BUZ 16 ES	M	16 S		16 S
BUZ 18	BUZ 18 ES			M 18 L	18 L
BUZ 20	BUZ 20 ES	M	20 S		20 S
BUZ 22	BUZ 22 ES			M 22 L	22 L
BUZ 25	BUZ 25 ES	М	25 S		25 S
BUZ 28	BUZ 28 ES			M 28 L	28 L
BUZ 30	BUZ 30 ES	М	30 S		30 S
BUZ 35	BUZ 35 ES			M 35 L	35 L
BUZ 38	BUZ 38 ES	М	38 S		38 S
BUZ 42	BUZ 42 ES			M 42 L	42 L

Please order union nuts separately if required. Nuts can be found on page 99



Application example

Blind fittings for cutting ring screw connections*

ISO 8434-1 (DIN 2353)

Suitable: Blind fitting for EVGE, DKO-L or DKO-S. To seal the hoses or pipe ends, on which nuts and cutting rings have

been diddhed.					
Type zinc-	Type	Tube Ø Union nut	Type zinc-	Type	Tube Ø Union nut
plated steel	AISI 316Ti	male thread	plated steel	AISI 316Ti	male thread
Light model series			Heavy model series		
ROV 6 L	ROV 6 L ES	6 L M 12 x 1.5	ROV 6 S	ROV 6 S ES	6 S M 14 x 1.5
ROV 8 L	ROV 8 L ES	8 L M 14 x 1.5	ROV 8 S	ROV 8 S ES	8 S M 16 x 1.5
ROV 10 L	ROV 10 L ES	10 L M 16 x 1.5	ROV 10 S	ROV 10 S ES	10 S M 18 x 1.5
ROV 12 L	ROV 12 L ES	12 L M 18 x 1.5	ROV 12 S	ROV 12 S ES	12 S M 20 x 1.5
ROV 15 L	ROV 15 L ES	15 L M 22 x 1.5	ROV 14 S	ROV 14 S ES	14 S M 22 x 1.5
ROV 18 L	ROV 18 L ES	18 L M 26 x 1.5	ROV 16 S	ROV 16 S ES	16 S M 24 x 1.5
ROV 22 L	ROV 22 L ES	22 L M 30 x 2	ROV 20 S	ROV 20 S ES	20 S M 30 x 2
ROV 28 L	ROV 28 L ES	28 L M 36 x 2	ROV 25 S	ROV 25 S ES	25 S M 36 x 2
ROV 35 L	ROV 35 L ES	35 L M 45 x 2	ROV 30 S	ROV 30 S ES	30 S M 42 x 2
ROV 42 L	ROV 42 L ES	42 L M 52 x 2	ROV 38 S	ROV 38 S ES	38 S M 52 x 2
+ DI .				0.0	

Please order union nuts and cutting rings separately if required. Nuts and cutting rings are found from page 98.

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.