

Couplings NW 2.7



Coupling plugs with male threads

NW 2.7

PT Optional: Body made of AISI 316L -ES4A, with valve for both-sided shut-off -BA, NPT thread -NPT

Туре	Туре	Type	Thread
brass	brass nickel-plated	stainless steel	male
KSG M5 NW2,7	KSG M5 NW2,7 MSV	KSG M5 NW2,7 ES	M 5
KSG 18 NW2,7	KSG 18 NW2,7 MSV	KSG 18 NW2,7 ES	G 1/8"



Coupling plugs with female threads

NW 2.7

POptional: Body made of AISI 316L -ES4A, with valve for both-sided shut-off -BA, NPT thread -NPT

Type brass	Type brass nickel-plated	Type stainless steel	Thread female
KSGi M5 NW2,7	KSGi M5 NW2,7 MSV	KSGi M5 NW2,7 ES	M 5
KSGi 18 NW2,7	KSGi 18 NW2,7 MSV	KSGi 18 NW2,7 ES	G 1/8"



Coupling plugs with hose nozzles

NW 2.7

Poptional: Body made of AISI 316L -ES4A, with valve for both-sided shut-off -BA

Type brass	Туре	Type	Hose ∅
brass	brass nickel-plated	stainless steel	internal
KSS 3 NW2,7	KSS 3 NW2,7 MSV	KSS 3 NW2,7 ES	3
KSS 4 NW2,7	KSS 4 NW2,7 MSV	KSS 4 NW2,7 ES	4
	KSS 5 NW2,7 MSV	KSS 5 NW2,7 ES	5



Coupling plugs with hose nozzles & bulkhead threads

NW 2.7

Poptional: With valve for both-sided shut-off -BA

— - F						
Туре	Туре			Hose Ø		
brass	brass nickel-plated	A	Emax	internal		
KSSS 3 NW2,7	KSSS 3 NW2,7 MSV	M 7 x 0.5	14	3		
KSSS 4 NW2,7	KSSS 4 NW2,7 MSV	M 7 x 0.5	14	4		



Coupling plugs with union nuts

NW 2.7

Poptional: Body made of AISI 316L -ES4A, with valve for both-sided shut-off -BA

Opinional. Body made of vitor of the 20-17, with valve for both stated short of Brit						
Туре	Туре	Type	Hose Ø			
brass	brass nickel-plated	stainless steel	ext. x internal			
KSK 3 NW2,7	KSK 3 NW2,7 MSV	KSK 3 NW2,7 ES	4.3 x 3			
KSK 4 NW2.7	KSK 4 NW2.7 MSV	KSK 4 NW2.7 ES	6 x 4			



Coupling plugs with union nuts & bulkhead threads

NW 2.7

Optional: With valve for both-sided shut-off -BA

Туре	Туре			Hose Ø
brass	brass nickel-plated	A	Emax	ext. x internal
KSKS 3 NW2,7	KSKS 3 NW2,7 MSV	M 7 x 0.5	11	4.3 x 3
KSKS 4 NW2,7	KSKS 4 NW2,7 MSV	M 8 x 0.5	8.5	6 x 4
,				



Order example: KSG M5 NW2.7 **

Standard type

Designation for the options:

Body made of stainless steel AISI 316L . .-ES4A
With valve for both-sided shut-off .-BA
NPT thread . .-NPT

Special version BA: Socket and plug shut-off





All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.