

Coupling sockets with angle hose nozzles

NW 7.2

Type	Actual nominal width	Hose Ø internal
brass		
KDSW 6 NW7	7.2	6
KDSW 9 NW7	7.2	9
KDSW 13 NW7	7.2	13



Coupling sockets with union nuts

NW 7.2

Optional: Can be used for plug shut-off on both sides -BA

Type	Type	Type	Actual nominal width	Hose Ø ext. x internal
brass	brass nickel-plated	stainless steel		
KDK 4 NW7	---	---	7.2	6 x 4
KDK 6 NW7	KDK 6 NW7 MSV	KDK 6 NW7 ES	7.2	8 x 6
KDK 8 NW7	KDK 8 NW7 MSV	KDK 8 NW7 ES	7.2	10 x 8
KDK 129 NW7	KDK 129 NW7 MSV	---	7.2	12 x 9



Order example: KDK 4 NW7 **

Standard type

Designation for the options:
Can be used for plug shut-off on both sides . . . -BA

Coupling sockets with union nuts & bend protection

NW 7.2

Optional: Can be used for plug shut-off on both sides -BA

Type	Type	Actual nominal width	Hose Ø ext. x internal
brass	brass nickel-plated		
Rigid			
KDK KS 6 NW7	KDK KS 6 NW7 MSV	7.2	8 x 6
KDK KS 8 NW7	KDK KS 8 NW7 MSV	7.2	10 x 8
KDK KS 129 NW7	---	7.2	12 x 9
Rotatable			
KDK KD 4 NW7	KDK KD 4 NW7 MSV	7.2	6 x 4
KDK KD 6 NW7	KDK KD 6 NW7 MSV	7.2	8 x 6
KDK KD 8 NW7	KDK KD 8 NW7 MSV	7.2	10 x 8



Order example: KDK KS 6 NW7 **

Standard type

Designation for the options:
Can be used for plug shut-off on both sides . . . -BA

Coupling sockets with lock against accidental uncoupling

NW 7.2

Application: By turning the sliding sleeve by 180° and accidental loosening of the coupling is prevented. Only when the recess of the sleeve is in front of the locking pin can the coupling be unlocked.

Type	Actual nominal width	Connection
brass		
KDGiV 14 NW7	7.2	G 1/4" (FT)
KDSV 13 NW7	7.2	Hose nozzle 13mm



Coupling sockets with male threads, ball locks

NW 7.2

Optional: Body made of AISI 316L -ES4AKV, can be used for plug shut-off on both sides -BA

Type	Thread	Stainless steel*	Thread	Actual nominal width
steel hard., nickel-pl./brass nickel-plate	male	steel*	male	
KDG 14 NW7 ST	R 1/4"	KDG 14 NW7 ES KV	G 1/4"	7.8
KDG 38 NW7 ST	R 3/8"	KDG 38 NW7 ES KV	G 3/8"	7.8
KDG 12 NW7 ST	R 1/2"	KDG 12 NW7 ES KV	G 1/2"	7.8

* coupling can be used with plug without shut-off and with shut-off -BA.



Order example: KDG 14 NW7 ST **

Standard type

Designation for the options:
Body made of AISI 316L-ES4AKV
Can be used for plug shut-off on both sides . . . -BA

Special version BA:
Socket and plug shut-off

