## Coupling sockets with female threads, ball locks — NW 7.2

👉 **Optional:** Body made of AISI 316L **-ES4AKV**, can be used for plug shut-off on both sides **-BA**

| Type steel hard., nickel-pl./brass nickel-plate | Type stainless steel* INOX | Actual nominal width | Thread female |
|---|---|---|---|
| KDGi 14 NW7 ST | KDGi 14 NW7 ES KV | 7.8 | G 1/4" |
| KDGi 38 NW7 ST | KDGi 38 NW7 ES KV | 7.8 | G 3/8" |
| KDGi 12 NW7 ST | KDGi 12 NW7 ES KV | 7.8 | G 1/2" |

\* coupling can be used with plug without shut-off and with shut-off **-BA**.

👉 Order example: KDGi 14 NW7 ST **

Standard type

**Designation for the options:**
Body made of AISI 316L . . . . . . . . . . . . . . . . .**-ES4AKV**
Can be used for plug shut-off on both sides . . . .**-BA**

## Coupling sockets with hose nozzles, ball locks — NW 7.2

👉 **Optional:** Body made of AISI 316L **-ES4AKV**, can be used for plug shut-off on both sides **-BA**

| Type steel hard., nickel-pl./brass nickel-plate | Type stainless steel* INOX | Actual nominal width | Hose Ø internal |
|---|---|---|---|
| KDS 6 NW7 ST | KDS 6 NW7 ES KV | 7.8 | 6 |
| --- | KDS 8 NW7 ES KV | 7.8 | 8 |
| KDS 9 NW7 ST | KDS 9 NW7 ES KV | 7.8 | 9 |
| --- | KDS 10 NW7 ES KV | 7.8 | 10 |
| KDS 13 NW7 ST | KDS 13 NW7 ES KV | 7.8 | 13 |

\* coupling can be used with plug without shut-off and with shut-off **-BA**.

👉 Order example: KDS 6 NW7 ST **

Standard type

**Designation for the options:**
Body made of AISI 316L . . . . . . . . . . . . . . . . .**-ES4AKV**
Can be used for plug shut-off on both sides . . . .**-BA**

## Coupling sockets with male threads, ball locks & plastic sleeves — NW 7.2

| Type steel/brass/plastic | | Actual nominal width | Thread male |
|---|---|---|---|
| KDG 14 NW7 STK | | 7.8 | R 1/4" |
| KDG 38 NW7 STK | | 7.8 | R 3/8" |
| KDG 12 NW7 STK | | 7.8 | R 1/2" |

## Coupling sockets with female threads, ball locks & plastic sleeves — NW 7.2

| Type steel/brass/plastic | | Actual nominal width | Thread female |
|---|---|---|---|
| KDGi 14 NW7 STK | | 7.8 | G 1/4" |
| KDGi 38 NW7 STK | | 7.8 | G 3/8" |
| KDGi 12 NW7 STK | | 7.8 | G 1/2" |

## Coupling sockets with hose nozzles, ball locks & plastic sleeves — NW 7.2

| Type steel/brass/plastic | | Actual nominal width | Hose Ø internal |
|---|---|---|---|
| KDS 6 NW7 STK | | 7.8 | 6 |
| KDS 8 NW7 STK | | 7.8 | 8 |
| KDS 9 NW7 STK | | 7.8 | 9 |
| KDS 10 NW7 STK | | 7.8 | 10 |
| KDS 13 NW7 STK | | 7.8 | 13 |

PVC fabric hoses on page 208

Blow guns from page 524

Compressed air tools from page 533

Service units FUTURA series from page 330

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.