

Compressor couplings



Compressor couplings

42 mm clamp width

Temperature range: -40°C to max. +95°C
Operating pressure: 10 or 16 bar

Compressor couplings with male threads (similar to DIN 3489)

42 mm

Type 10 bar malleable iron galv. NBR seal	DN	Type 10 bar malleable iron galv. brass seal	DN	Type 16 bar AISI 316 FKM seal	DN	Thread
KAG 38	8.5	---	---	KAG 38 ES	10	G 3/8"
KAG 12	12	KAG 12 MS	11	KAG 12 ES	14	G 1/2"
KAG 34	17	KAG 34 MS	17	KAG 34 ES	19	G 3/4"
KAG 10	20	KAG 10 MS	17	KAG 10 ES	20	G 1"
Replacement seals						
SKG GU		SKG MS		SKG GU ES		



Compressor couplings with female threads (similar to DIN 3489)

42 mm

Type 10 bar malleable iron galv. NBR seal	DN	Type 10 bar malleable iron galv. brass seal	DN	Type 16 bar AISI 316 FKM seal	DN	Thread
KiG 38	15	---	---	KiG 38 ES	15	Rp 3/8"
KiG 12	19	KiG 12 MS	17	KiG 12 ES	19	Rp 1/2"
KiG 34	20	KiG 34 MS	17	KiG 34 ES	20	Rp 3/4"
KiG 10	20	KiG 10 MS	17	KiG 10 ES	20	Rp 1"
Replacement seals						
SKG GU		SKG MS		SKG GU ES		



Compressor couplings with hose nozzles (similar to DIN 3489)

42 mm

Type 10 bar malleable iron galv. NBR seal	DN	Type 10 bar malleable iron galv. brass seal	DN	Type 16 bar AISI 316 FKM seal	DN	Hose Ø internal
SKG 13	8.5	SKG 13 MS	8.5	SKG 13 ES	9	13 (1/2")
SKG 19	14	SKG 19 MS	15	SKG 19 ES	15	19 (3/4")
SKG 25	19	SKG 25 MS	19	SKG 25 ES	20	25 (1")
SKG 32	20	---	---	---	---	32 (1 1/4")
Replacement seals						
SKG GU		SKG MS		SKG GU ES		



Compressor couplings with hose nozzles & safety collars (similar to DIN 3489) 42 mm

✓ Advantages: • Additional mechanical connection between coupling and clamp (only in connection with hose clamp SL ... SB on page 239)



Type 10 bar malleable iron galvanised	DN	Safety collar Ø	Hose Ø internal
SKG 10 SB	5.5	21	10
SKG 13 SB	8.5	24	13 (1/2")
SKG 19 SB	14	28	19 (3/4")
SKG 25 SB	18.5	36	25 (1")
Replacement seals (NBR)			
SKG GU			

Compressor couplings with hose nozzles, rotatable (similar to DIN 3489)

42 mm

Type 16 bar malleable iron galvanised	DN	Hose Ø internal
SKGD 13	10	13 (1/2")
SKGD 19	15	19 (3/4")
SKGD 25	19	25 (1")
Replacement seals (NBR)		
SKG GU		

