

Sandblast couplings

58 mm clamp width

Suitable: Couplings to connect sandblast hoses without cross section constriction.

Materials: Body: Malleable iron galvanised, yellow chromated or nylon, seal: NBR

Operating pressure: Up to max. 12 bar

Supply volume: Type malleable cast iron: With retaining screws, type nylon: With retaining screws and automatic lock function



Recommended accessories for couplings made from malleable cast iron: Safety clip or automatic lock function

Warning: Please note that the malleable cast iron coupling SSKG 32135, SSKIG 11462, SSKIG 11262, SSKIG G 5062 and the nylon coupling have a new sealing system so that the hose or the thread is positioned right on the seal. The advantage is that the blasting abrasives cannot be compressed behind the seal. In the case of all other couplings, the hose is separated from the seal by a ridge.

Sandblast couplings with hose connections

58 mm

Type malleable iron	L	Type nylon	L	Hose Ø internal	Hose Ø external	Repl.seal for type mall. iron	Repl.seal for type nylon
---		SSKG 19 N	110	19	33	---	SSKGN GU 19
SSKG 2593	93	SSKG 25 N	110	25	39	SSKG GU	SSKGN GU 25
SSKG 3292	92	SSKG 32 N	136	32	48	SSKG GU	SSKGN GU
SSKG 32135	135	---		32	48	SSKG GU LG	---
SSKG 38129	129	SSKG 38 N	136	38	56	SSKG GU	SSKGN GU
SSKG 40150	150	SSKG 42 N	137	42	60	SSKG GU	SSKGN GU



Sandblast couplings with female threads

58 mm

Type malleable iron	L	Type nylon	L	Thread female	Repl.seal for type mall. iron	Repl.seal for type nylon
SSKiG 11455	55	---		G 1 1/4"	SSKG GU	---
SSKiG 11462	62	SSKiG 114 N	63	G 1 1/4"	SSKG GU LG	SSKGN GU
SSKiG 11255	55	---		G 1 1/2"	SSKG GU	---
SSKiG 11262	62	---		G 1 1/2"	SSKG GU LG	---
SSKiG 2079	79	---		G 2"	SSKG GU	---
SSKiG G5055	55	---		50 mm coarse thread	SSKG GU	---
SSKiG G5062	62	SSKiG G50 N	63	50 mm coarse thread	SSKG GU LG	SSKGN GU



Replacement seals for sandblast couplings

58 mm

Type NBR	Ø internal	Ø external	L
For malleable iron			
SSKG GU	31.0	48.5	10.5
SSKG GU LG	31.0	44.0	27.0
For nylon			
SSKGN GU 19	19.0	44.0	27.0
SSKGN GU 25	25.0	44.0	27.0
SSKGN GU	31.5	44.0	27.0



Spare parts/accessories for sandblast couplings

58 mm

Type		VPE
Retaining screws for the malleable iron and nylon types		
SSKG HA	Cross recess screw 4.8 x 13 mm for hose attachment	10
Safety clips/automatic lock functions for the malleable iron types		
SSKG SI	Safety clip according to DIN 11024, 3 mm wire	10
SSKG SIA	Automatic lock function for attaching to the coupling, 2 mm wire	10

