



Garden hose quick couplings

End caps for garden hose quick couplings

40 mm

Type	Type brass with KTW approval	Type stainless steel
brass	KTW approval	INOX
GKVS	GKVS KTW	GKVS ES
Replacement seals		
GKOR		NBR seal for type brass
GKOR KTW		NBR seal for type brass with KTW approval
GKOR ES		FKM seal for type stainless steel
Chain made of stainless steel		
GKVS KETTE ES		Stainless steel chain used for GK end caps with borehole



Garden hose quick couplings with hose nozzles, rotatable

40 mm

Type coupled can be rotated	Type coupled can not be rotated*	Hose Ø internal	Seal NBR standard	Seal NBR KTW approval
GSKD 13 MS	GSKD 13 MS E	13 (1/2")	GKORX	GKOR KTW
GSKD 19 MS	GSKD 19 MS E	19 (3/4")	GKORX	GKOR KTW
GSKD 25 MS	GSKD 25 MS E	25 (1")	GKORX	GKOR KTW
GSKD 32 MS	---	32 (1 1/4")	GKORX	GKOR KTW

* suitable replacement seal: GKOR



Angle garden hose quick couplings with hose nozzles, rotatable

40 mm

Type coupled can be rotated	Hose Ø internal	Seal NBR standard	Seal NBR KTW approval
GSKDW 13 MS	13 (1/2")	GKORX	GKOR KTW
GSKDW 19 MS	19 (3/4")	GKORX	GKOR KTW
GSKDW 25 MS	25 (1")	GKORX	GKOR KTW
GSKDW 32 MS	32 (1 1/4")	GKORX	GKOR KTW



Safety garden hose quick couplings with hose nozzles

40 mm

Type	Hose Ø internal	Seal NBR
GSSK 13 MS	13 (1/2")	GKORS
GSSK 19 MS	19 (3/4")	GKORS
GSSK 25 MS	25 (1")	GKORS
GSSK 32 MS	32 (1 1/4")	GKORS



Garden hose quick couplings with screw connections for garden hoses

40 mm

Temperature range: 0°C to max. +60°C

Operating pressure: 0 - 8 bar

Media: Water

- ✓ **Advantages:**
- Multiple assembly possible
 - No formation of dirt accumulations
 - No risk of injury due to sharp edges and corners

Type	Hose Ø internal	Seal NBR
GSKWS 13 MS	13 (1/2")	GKORS
GSKWS 19 MS	19 (3/4")	GKORS
Replacement seals		
GKOR		NBR seal for type brass
GKOR KTW		NBR seal for type brass with KTW approval



Garden hose quick couplings with screw connections for industrial hoses

40 mm

- ✓ **Advantages:**
- Multiple assembly possible
 - No formation of dirt accumulations
 - No risk of injury due to sharp edges and edges
 - Suitable for almost all high-quality industrial and pressure hoses
 - With KTW approval

Type	Hose Ø internal	Hose Ø external	Wall thickness of hose	Seal NBR KTW approval
GSKX 13 KTW	13 (1/2")	19.0 - 20.6	3.0 - 3.8	GKOR KTW
GSKX 19 KTW	19 (3/4")	26.6 - 27.4	3.8 - 4.2	GKOR KTW
GSKX 25 KTW	25 (1")	33.8 - 35.0	4.4 - 5.0	GKOR KTW



All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.