

### Garden hose hose couplings

up to 10 bar

Type brass:

Materials: Body: Brass, seal: NBR, compression ring: Nylon

Temperature range: 0°C to max. +60°C

Operating pressure: 0 - 8 bar

Media: Water

Type GARDENA:

Materials: Body: PP and ABS, seal: EPDM

Temperature range: 0°C to max. +40°C

Operating pressure: 0 - 10 bar

Media: Water

### Coupling plugs with female threads (valve pieces)

Type brass	Type GARDENA	Thread female
WSKS 12 i	WSKS 12 iK	G 1/2"
WSKS 34 i	WSKS 34 iK	G 3/4"
WSKS 10 i	WSKS 10 iK	G 1"

### Coupling plugs with male threads (device adapters)

Type brass	Type GARDENA	Thread male
---	WSKS 14 K	G 1/4"
WSKS 12	---	G 1/2"
WSKS 34	WSKS 34 K	G 3/4"

### Coupling sockets with hose connections

Type brass	Type GARDENA	Hose Ø internal
<b>Standard</b>		
WSKDS 13	WSKDS 13 K	13 (1/2")
WSKDS 19	WSKDS 19 K	19 (3/4")
<b>With water stop</b>		
WSKDS 13 A	WSKDS 13 AK	13 (1/2")
WSKDS 19 A	WSKDS 19 AK	19 (3/4")

### Coupling sockets with male threads (for device connections)

Type GARDENA	Thread male
WSKDG 34 K	G 3/4"

### Hose connectors (repairs)

Type brass	Type GARDENA	Hose Ø internal
WSS 13	WSS 13 K	13 (1/2")
WSS 19	WSS 19 K	19 (3/4")

### GARDENA water volumeters

PN 12

**Application:** The water volumeter is ideal for controlling water consumption. The device measures the amount of water that has flowed through it. Four functions, easy to select via buttons: Water consumption per day, per season, per watering operation, and current flow rate (l/min.).

**Temperature range:** Medium: +5°C to max. +40°C, environment: +5°C to max. +60°C

**Measuring tolerance:** ± 5%

**Connection:** GARDENA coupling system (any flow direction)

**Auxiliary energy:** 3V coin cells (included in scope of delivery)

Type	Measuring range
DMG 30 K	2 - 30 l/min.

### GARDENA spray guns/GARDENA washing brushes

Type GARDENA	Version
WS SPR K	Water sprayer, with hard jet or spray mist setting. Continuous flow adjustment, trigger handle with continuous locking
WS SPR MULTI K	Multi-function spray head with three spray patterns (hard jet, rain jet, shower), variable flow adjustment for dosed watering, trigger handle with continuous locking
WS SPR CLASSIC	Classical water jet. Continuous adjustment from hard jet to fine spray mist
WS SPR WASCH	Classic compact washing brush with regulating and shut-off valve. Bristles of horse-hair mixture
WS SPR WASCH EL	Compact washing brush, brush body elastic with regulating and shut-off valve
WS SPR WASCH SR	Hand scrubber with regulating and shut-off valve, bristles made of synthetic fibre



type WS SPR CLASSIC



type WS SPR WASCH




type WS SPR WASCH EL



type WS SPR WASCH SR

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.



type WS SPR K



type WS SPR MULTI K