

Polyurethane coil tubes



Especially good value!



Duo




Trio



Quattro



360° rotatable



360° rotatable



360° rotatable

360° rotatable

Polyurethane coil tubes

Properties: Polyurethane coil tubes have high wear, pressure and abrasion resistance. They prevent scratching of painted surfaces (bodywork construction), have a lasting return force and at the same time have very good buckling resistance and elasticity.

Polyurethane coil tubes

Material: Polyester polyurethane
Temperature range: -20°C to max. +60°C
Operating pressure: 10 bar

Usable with:	push-in fittings	CK quick screw fittings	PK push-in nipple
	page no. 24	53	60

Working length	Working length	Working length	Working length	Hose Ø	Winding Ø
2 m	3 m	6 m	8 m	external x internal	internal
SP PUN 42/2	SP PUN 42/3	---	---	4 x 2	17
---	SP PUN 64/3	SP PUN 64/6	SP PUN 64/8	6 x 4	30
---	SP PUN 85/3	SP PUN 85/6	SP PUN 85/8	8 x 5	34
---	SP PUN 106/3	SP PUN 106/6	SP PUN 106/8	10 x 6.5	42
---	SP PUN 128/3	SP PUN 128/6	SP PUN 128/8	12 x 8	60

Polyurethane multiple coil tubes

Material: Polyester polyurethane
Temperature range: -20°C to max. +60°C
Operating pressure: 10 bar


Usable with:	push-in fittings	CK quick screw fittings	PK push-in nipple
	page no. 24	53	60

Working length	Working length	Working length	Hose Ø	Winding Ø
2.5 m	5 m	10 m	external x internal	internal
Duo hoses (2-way), axial outlet				
Standard colours: blue-black				
SP PU DUO 4/2,5	SP PU DUO 4/5	SP PU DUO 4/10	4 x 2	30
SP PU DUO 4,3/2,5	SP PU DUO 4,3/5	SP PU DUO 4,3/10	4,3 x 3	30
SP PU DUO 6/2,5	SP PU DUO 6/5	SP PU DUO 6/10	6 x 4	60
SP PU DUO 8/2,5	SP PU DUO 8/5	SP PU DUO 8/10	8 x 6	80
SP PU DUO 10/2,5*	SP PU DUO 10/5*	SP PU DUO 10/10*	10 x 8	90
Trio hoses (3-way), radial outlet				
Standard colours: blue-black-natural				
SP PU TRIO 6/2,5	SP PU TRIO 6/5		6 x 4	60
SP PU TRIO 8/2,5	SP PU TRIO 8/5		8 x 6	80
Quattro hoses (4-way), radial outlet				
Standard colours: blue-black-green-natural				
SP PU QUAT 6/2,5	SP PU QUAT 6/5		6 x 4	60
SP PU QUAT 8/2,5	SP PU QUAT 8/5		8 x 6	80

* radial outlet

Polyurethane coil tubes with bend protection spirals, 360° rotatable

Material: Polyester polyurethane
Temperature range: -20°C to max. +60°C
Operating pressure: 10 bar




✓ **Advantages:** • With rotary connections for slow rotary movement to avoid twisting the hoses.

Working length	Working length	Working length	Hose Ø	Thread	Winding Ø
3 m	6 m	8 m	external x internal		internal
SPK PUN 146/3	SPK PUN 146/6	SPK PUN 146/8	6 x 4	G 1/4"	30
SPK PUN 148/3	SPK PUN 148/6	SPK PUN 148/8	8 x 5	G 1/4"	34
SPK PUN 1410/3	SPK PUN 1410/6	SPK PUN 1410/8	10 x 6.5	G 1/4"	42
SPK PUN 3812/3	SPK PUN 3812/6	SPK PUN 3812/8	12 x 8	G 3/8"	60

Polyurethane coil tubes with fabric and bend protection spirals, 360° rotatable

Material: Polyether polyurethane
Temperature range: -20°C to max. +75°C
Operating pressure: Type SPK TX 149/...: 14.5 bar, type SPK TX 3812/...: 12.5 bar



✓ **Advantages:** • With rotary connections for slow rotary movement to avoid twisting the hoses
 • High operating pressure

Working length	Working length	Working length	Hose Ø	Thread	Winding Ø	Type
3 m	6 m	7.5 m	external x int.		Ø int.	replace. fitting
SPK TX 149/3	SPK TX 149/6	SPK TX 149/7,5	9.5 x 6.3	G 1/4"	23	SPK 14/96 PU
SPK TX 3812/3	SPK TX 3812/6	SPK TX 3812/7,5	12 x 8	G 3/8"	31	SPK 38/128 PU

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.