


Polyurethane coil tubes w/ bend protection spirals 360° rot. w/ couplings NW 7.2

Material: Polyester polyurethane
Temperature range: -20°C to max. +60°C
Operating pressure: 10 bar



- ✓ **Advantages:**
- With rotary connections for slow rotary movement to avoid twisting the hoses.
 - With coupling socket and plug, can be used immediately in the work place.

Working length 3 m	Working length 6 m	Working length 8 m	Hose Ø external x internal	Winding Ø internal
SPK PUN 64/3 KDG	SPK PUN 64/6 KDG	SPK PUN 64/8 KDG	6 x 4	30
SPK PUN 85/3 KDG	SPK PUN 85/6 KDG	SPK PUN 85/8 KDG	8 x 5	34
SPK PUN 106/3 KDG	SPK PUN 106/6 KDG	SPK PUN 106/8 KDG	10 x 6.5	42
SPK PUN 128/3 KDG	SPK PUN 128/6 KDG	SPK PUN 128/8 KDG	12 x 8	60



Polyurethane coil tubes w/ bend protection spirals 360° rot. w/ couplings NW 7.2

Material: Polyether polyurethane
Temperature range: -20°C to max. +75°C
Operating pressure: 8 bar
Optional: With push-button safety coupling -S



- ✓ **Advantages:**
- With rotary connections for slow rotary movement to avoid twisting the hoses
 - With coupling socket and plug, can be used immediately in the work place

Working length 3 m	Working length 6 m	Working length 7.5 m	Working length 10 m	Hose Ø external x int.	Winding Ø int.
SPK PU 148/3 KDG	SPK PU 148/6 KGD	SPK PU 148/7,5 KGD	---	8 x 5	24
SPK PU 149/3 KDG	SPK PU 149/6 KGD	SPK PU 149/7,5 KGD	SPK PU 149/10 KDG	9.5 x 6.3	41
SPK PU 3812/3 KDG	SPK PU 3812/6 KGD	SPK PU 3812/7,5 KGD	SPK PU 3812/10 KDG	12 x 8	56

Order example: SPK PU 148/3 KDG **

Standard type


Designation for the options:
With push-button valve safety coupling -S



Polyurethane coil tubes (Stream-Line) with couplings NW 7.2/NW 10



Material: Polyester polyurethane
Temperature range: -20°C to max. +60°C
Operating pressure: 10 bar



- ✓ **Advantages:**
- With steel coupling socket and plug, can be used immediately in the work place
 - Very high quality CEJN safety coupling
 - Steel plug, well-suited for applications with high mechanical wear

Working length 4 m	Working length 6 m	Working length 8 m	Hose Ø external x int.	Winding Ø internal
With safety coupling eSafe NW 7				
SP PUC 106/4 KDG-S	SP PUC 106/6 KDG-S	SP PUC 106/8 KDG-S	10 x 6.5	32
SP PUC 128/4 KDG-S	SP PUC 128/6 KDG-S	SP PUC 128/8 KDG-S	12 x 8	41
SP PUC 1611/4 KDG-S	SP PUC 1611/6 KDG-S	SP PUC 1611/8 KDG-S	16 x 11	63
With safety coupling eSafe NW 10				
SP PUC 1611/4 KDG-10	SP PUC 1611/6 KDG-10	SP PUC 1611/8 KDG-10	16 x 11	63



Coupling sockets
NW7 from page 150



Safety couplings
from page 156



Distinctive
couplings
from page 162



Blow guns
from page 524

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.