

## Polyamide coil tubes with bend protection spirals, 360° rotatable DIN 73378 (Eco)

Material: PA 12 W  
Temperature range: -40°C to max. +90°C  
Standard colour: Blue



*Especially good value!*

- ✓ **Advantages:** • With rotary connections for slow rotary movements to avoid twisting the hoses.

Working length 3 m	Working length 5 m	Working length 7 m	Hose Ø external x internal	Operating pressure	Thread
SPKD 186/3 E	SPKD 186/5 E	SPKD 186/7 E	6 x 4	27 bar	R 1/8"
SPKD 148/3 E	SPKD 148/5 E	SPKD 148/7 E	8 x 6	19 bar	R 1/4"
SPKD 1410/3 E	SPKD 1410/5 E	SPKD 1410/7 E	10 x 8	15 bar	R 1/4"
SPKD 3812/3 E	SPKD 3812/5 E	SPKD 3812/7 E	12 x 9	19 bar	R 3/8"



## Polyamide coil tubes with bend protection spirals, 360° rot. DIN 73378/74324\*\*

Material: PA 12 W  
Temperature range: -40°C to max. +90°C  
Standard colour: Blue  
 Optional: Colours black, natural, red, yellow



- ✓ **Advantages:** • With rotary connections for slow rotary movement to avoid twisting the hoses  
• Axial outlets for more workspace

Working length 2.5 m	Working length 5 m	Working length 7.5 m	Hose Ø external x internal	Operating pressure	Thread
SPKD 186/2,5	SPKD 186/5	SPKD 186/7,5	6 x 4	27 bar	G 1/8"
SPKD 148/2,5	SPKD 148/5	SPKD 148/7,5	8 x 6	19 bar	G 1/4"
SPKD 1410/2,5	SPKD 1410/5	SPKD 1410/7,5	10 x 8	15 bar	G 1/4"
SPKD 3812/2,5	SPKD 3812/5	SPKD 3812/7,5	12 x 9	19 bar	G 3/8"
SPK 1215/2,5*	SPK 1215/5*	SPK 1215/7,5*	15 x 12	15 bar	G 1/2"

\* star connection, \*\* only available in black: DIN 74324

Order example: SPKD 186/2,5 \*\*

Standard type

### Designation for the options:

● colour black ..... SCHWARZ  
○ natur colour ..... NATUR  
● colour red ..... ROT  
● yellow colour ..... GELB




## Polyamide coil tubes with bend protection spirals, 360° rot. with couplings NW 7

Material: PA 12 W  
Temperature range: -20°C to max. +90°C  
Standard colour: Blue



- ✓ **Advantages:** • With rotary connections for slow rotary movement to avoid twisting the hoses  
• With coupling socket and plug, can be used immediately in the work place  
• Axial outlets for more workspace

Working length 2.5 m	Working length 5 m	Working length 7.5 m	Hose Ø external x internal	Operating pressure
SPKD 148/2,5 KDG	SPKD 148/5 KDG	SPKD 148/7,5 KDG	8 x 6	19 bar
SPKD 1410/2,5 KDG	SPKD 1410/5 KDG	SPKD 1410/7,5 KDG	10 x 8	15 bar
SPKD 3812/2,5 KDG	SPKD 3812/5 KDG	SPKD 3812/7,5 KDG	12 x 9	19 bar



All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.