

Steam hoses

Epecially good value!



2-part clamps
for steam hoses
on page 239

Low pressure steam hoses

up to +164°C

Materials: Cover: EPDM, black, patterned and perforated material, inner tube: EPDM, black, smooth
Properties: Good resistance to acids and alkalis. After use, drain water or steam!
Temperature range: -40°C to max. +164°C
Operating pressure: Max. 7 bar constant at +164°C, water to max. 20 bar
Operating range: Hot water and saturated steam
Roll length: 40 m

Type	Hose Ø internal	Hose Ø external	Min. bend radius
WSH 10 ND	10 (3/8")	21	60
WSH 13 ND	13 (1/2")	24	80
WSH 19 ND	19 (3/4")	33	115
WSH 25 ND	25 (1")	39	150
WSH 32 ND	32 (1 1/4")	47	195
WSH 38 ND	38 (1 1/2")	56	230
WSH 50 ND	51 (2")	69	300

4



Steam fittings
from page 69

Steam hoses DAMPF-TRIX® 6000, DIN EN ISO 6134-2A

up to +210°C

Materials: Cover: EPDM external layer, insensitive to ozone, weathering and UV radiations, abrasion resistant
pressure carrier: 2 steel wire mesh inner tube: Smooth, non-porous EPDM
Temperature range/operating pressure: 18 bar constant at +210°C, temporary 23 bar at +220°C
Electrical resistance: R < 10⁶ Ohm/m
Operating range: Saturated steam
Roll length: 40 m

Type	Hose Ø internal	Hose Ø external	Min. bend radius
WSH 13	13 (1/2")	25	130
WSH 19	19 (3/4")	33	190
WSH 25	25 (1")	40	250
WSH 32	32 (1 1/4")	48	320
WSH 38	38 (1 1/2")	54	380
WSH 50	50 (2")	68	500

Oil resistant (external) steam hoses DAMPF-TRIX® 6000, DIN EN ISO 6134-2B

to +210°C

Materials: Cover: Special oil resistant external layer, insensitive to ozone, weathering and UV radiations, abrasion resistant, pressure carrier: 2 steel wire mesh inner tube: Smooth, non-porous EPDM
Temperature range/operating pressure: 18 bar constant at +210°C, temporary 23 bar at +220°C
Electrical resistance: R < 10⁶ Ohm/m
Operating range: Saturated steam
Roll length: 40 m

Type	Hose Ø internal	Hose Ø external	Min. bend radius
WSH 13 OL	13 (1/2")	25	130
WSH 19 OL	19 (3/4")	33	190
WSH 25 OL	25 (1")	40	250
WSH 32 OL	32 (1 1/4")	48	320
WSH 38 OL	38 (1 1/2")	54	380
WSH 50 OL	50 (2")	68	500

We cut our hoses to your required length!


You can also select already pre-cut parts in our Online Shop to special conditions.




Tube cutters
on page 595



Oil binding agents &
oil binding cloths
from page 581



tesa
tesa -adhesive
technology
from page 585



Thermometer
from page 396

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.