

Suction hoses and pressure hoses

Vacuum plastic coil tubes made of PVC-Superflex

Materials: Soft PVC light grey, support coil made of hard PVC white (smooth on the inside, corrugated on the outside)

Temperaturbereich: -15°C to max. +50°C

Application: As connection between ventilators and work stations, vacuum cleaner industry, aerating and venting, mechanical engineering, air conditioning. For suction of small wood or plastic shavings.. Can also ideally be used as cable protection hose.



Type	Hose Ø internal	Min. bend radius	Operating pressure	Roll length m
VU 13 FLEX	13	13	-0,5 bis 0 bar	30
VU 19 FLEX	19	19	-0,5 bis 0 bar	50
VU 25 FLEX	25	25	-0,5 bis 0 bar	50
VU 30 FLEX	30	30	-0,5 bis 0 bar	50
VU 32 FLEX	32	32	-0,5 bis 0 bar	50
VU 35 FLEX	35	35	-0,5 bis 0 bar	50
VU 38 FLEX	38	38	-0,5 bis 0 bar	50
VU 40 FLEX	40	40	-0,5 bis 0 bar	50
VU 45 FLEX	45	45	-0,5 bis 0 bar	50
VU 50 FLEX	50	50	-0,5 bis 0 bar	50
VU 60 FLEX	60	60	-0,5 bis 0 bar	50
VU 70 FLEX	70	70	-0,5 bis 0 bar	50
VU 76 FLEX	76	76	-0,5 bis 0 bar	50
VU 80 FLEX	80	80	-0,5 bis 0 bar	50
VU 90 FLEX	90	90	-0,5 bis 0 bar	50
VU 100 FLEX	100	100	-0,5 bis 0 bar	30
VU 110 FLEX	110	110	-0,2 bis 0 bar	30
VU 120 FLEX	120	120	-0,2 bis 0 bar	30
VU 125 FLEX	125	125	-0,2 bis 0 bar	30
VU 150 FLEX	150	150	-0,2 bis 0 bar	30
VU 180 FLEX	180	180	-0,1 bis 0 bar	20
VU 203 FLEX	203	203	-0,1 bis 0 bar	20

AC and vent hoses made of PVC coated polyester meshes

Materials: PVC coated polyester mesh with a bronzed steel wire coil embedded in the wall

Temperature range: -30°C to max. +80°C (temporary +100°C)

Wall thickness: Approx. 0.4 mm

Application: HVAC, welding gas extraction, solar systems, household equipment, good flexibility, self-extinguishing, low-temperature flexibility, good expansion ratio.




Type	Hose Ø internal	Operating pressure	Roller length m
LUFLEX 40	40	-0.20 to 0.90 bar	30
LUFLEX 50	50	-0.20 to 0.80 bar	15
LUFLEX 60	60	-0.16 to 0.80 bar	15
LUFLEX 70	70	-0.14 to 0.70 bar	15
LUFLEX 75	75	-0.10 to 0.60 bar	15
LUFLEX 80	80	-0.10 to 0.60 bar	15
LUFLEX 90	90	-0.09 to 0.50 bar	15
LUFLEX 100	100	-0.09 to 0.50 bar	15
LUFLEX 120	120	-0.08 to 0.50 bar	15
LUFLEX 125	125	-0.08 to 0.50 bar	15
LUFLEX 140	140	-0.06 to 0.35 bar	15
LUFLEX 150	150	-0.06 to 0.20 bar	15
LUFLEX 160	160	-0.05 to 0.20 bar	10
LUFLEX 175	175	-0.05 to 0.20 bar	10
LUFLEX 200	200	-0.05 to 0.20 bar	10
LUFLEX 250	250	-0.04 to 0.10 bar	10



Wire hose clamps
from page 238



Threaded nozzles &
hose nozzles
from page 64



Respirator
page 590



Dustpans and
hand sweepers
on page 584

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.