

## Push-in fittings with union nuts, imperial threads cylindrical

60° cone

Type zinc-plated steel straight	Type zinc-plated steel 90°	Type zinc-plated steel 45°	Thread	Hose Ø internal	PN
STP 146	STPW90 146	STPW45 146	G 1/4"	6.4	25 bar
STP 3810	STPW90 3810	STPW45 3810	G 3/8"	9.5	20 bar
STP 1212	STPW90 1212	STPW45 1212	G 1/2"	12.7	16 bar
STP 3420	STPW90 3420	STPW45 3420	G 3/4"	19.1	12 bar
STP 1025	STPW90 1025	STPW45 1025	G 1"	25.4	12 bar



## Push-in fittings with male threads, imperial threads cylindrical

60° cone

Type zinc-plated steel	Thread	Hose Ø internal	PN
GTP 186	G 1/8"	6.4	25 bar
GTP 146	G 1/4"	6.4	25 bar
GTP 1410	G 1/4"	9.5	20 bar
GTP 3810	G 3/8"	9.5	20 bar
GTP 1212	G 1/2"	12.7	16 bar
GTP 1216	G 1/2"	15.9	16 bar
GTP 3420	G 3/4"	19.1	12 bar
GTP 1025	G 1"	25.4	12 bar



## Push-in fittings threaded nozzles

PN 15

Type brass	Thread	Hose Ø internal	Spanner width
GTP 186 MS	G 1/8"	6.4	14
GTP 1810 MS	G 1/8"	9.5	14
GTP 146 MS	G 1/4"	6.4	17
GTP 1410 MS	G 1/4"	9.5	17
GTP 1412 MS	G 1/4"	12.7	17
GTP 3810 MS	G 3/8"	9.5	17
GTP 3812 MS	G 3/8"	12.7	17
GTP 1210 MS	G 1/2"	9.5	22
GTP 1212 MS	G 1/2"	12.7	22
GTP 1216 MS	G 1/2"	15.9	22
GTP 3416 MS	G 3/4"	15.9	27
GTP 3419 MS	G 3/4"	19.1	27



## Push-in fittings hose connectors

PN 15

Type brass	Hose Ø internal
SVRP 12 MS	12.7
SVRP 16 MS	15.9



**LOCTITE**  
Liquid seals, gaskets & tapes from page 549

**SKF**  
Roller bearing from p. 603

Oil binding agents & oil binding cloths from page 581

High pressure ball valves from page 292

Knives on page 595

Tube cutters on page 595

Hydraulic valves from page 452

Manual tools can be found in the Online Shop

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.