

Hinge bolt clamps



Suitable: For use in demanding applications, such as the mounting of suction and pressure hoses with high Shore hardness or with plastic or steel inserts. Ideal for commercial vehicle construction, industry, construction machinery, farming, mining, ...

Material: Tape and housing: AISI 430 (W2), screw: Zinc-plated steel

Optional: Material complete AISI 304 (W4) -2A


Advantages: • Hollow bolt reduces load on screw and tape. Increased service life

Type	Ø Clamping range	Tape width	Type	Ø Clamping range	Tape width
SSB 19 ES	17 - 19	18	SSB 79 ES	73 - 79	25
SSB 21 ES	19 - 21	18	SSB 85 ES	79 - 85	25
SSB 23 ES	21 - 23	18	SSB 91 ES	85 - 91	25
SSB 25 ES	23 - 25	18	SSB 97 ES	91 - 97	25
SSB 27 ES	25 - 27	18	SSB 104 ES	97 - 104	25
SSB 29 ES	27 - 29	18	SSB 112 ES	104 - 112	25
SSB 31 ES	29 - 31	18	SSB 121 ES	112 - 121	25
SSB 34 ES	31 - 34	18	SSB 130 ES	121 - 130	25
SSB 37 ES	34 - 37	18	SSB 140 ES	130 - 140	30
SSB 40 ES	37 - 40	18	SSB 150 ES	140 - 150	30
SSB 43 ES	40 - 43	18	SSB 162 ES	150 - 162	30
SSB 47 ES	43 - 47	20	SSB 174 ES	162 - 174	30
SSB 51 ES	47 - 51	20	SSB 187 ES	174 - 187	30
SSB 55 ES	51 - 55	20	SSB 200 ES	187 - 200	30
SSB 59 ES	55 - 59	20	SSB 213 ES	200 - 213	30
SSB 63 ES	59 - 63	20	SSB 226 ES	213 - 226	30
SSB 68 ES	63 - 68	20	SSB 239 ES	226 - 239	30
SSB 73 ES	68 - 73	25	SSB 252 ES	239 - 252	30

Order example: SSB 19 ES **

Standard type

Designation for the options:
Material AISI 304 (W4) -2A



Hinge bolt clamps, 2-part



Suitable: For use in demanding applications, such as the mounting of suction and pressure hoses with high Shore hardness or with plastic or steel inserts. Ideal for commercial vehicle construction, industry, construction machinery, farming, mining, ...

Material: Tape and housing: AISI 430 (W2), screw: Zinc-plated steel

Optional: Material complete AISI 304 (W4) -2A


Advantages: • Hollow bolt reduces load on screw and tape. Increased service life
• Improved clamping strength thanks to 2-part design
• Greater clamping range

Type	Ø Clamping range	Tape width	Type	Ø Clamping range	Tape width
SSBP 67 ES	59 - 67	18	SSBP 196 ES	176 - 196	25
SSBP 75 ES	67 - 75	18	SSBP 216 ES	196 - 216	25
SSBP 83 ES	75 - 83	20	SSBP 236 ES	216 - 236	25
SSBP 91 ES	83 - 91	20	SSBP 256 ES	236 - 256	25
SSBP 101 ES	87 - 101	20	SSBP 276 ES	256 - 276	25
SSBP 115 ES	101 - 115	20	SSBP 296 ES	276 - 296	25
SSBP 129 ES	115 - 129	20	SSBP 316 ES	296 - 316	25
SSBP 143 ES	129 - 143	20	SSBP 336 ES	316 - 336	25
SSBP 157 ES	143 - 157	20	SSBP 356 ES	336 - 356	25
SSBP 171 ES	157 - 171	20	SSBP 376 ES	356 - 376	25
SSBP 185 ES	171 - 185	20			

Order example: SSBP 67 ES **

Standard type

Designation for the options:
Material AISI 304 (W4) -2A



Consoles for hose clamps



Suitable: This console and a hose clamp add stability to the foot for round containers and a stable mounting of tubes. **Clamps that can be used:** SS ... (page 235), SSB ... (see above on this page), SSSI ... (page 238) - please observe the width!

Type zinc-plated steel	For tube Ø	Max. clamp width	Length x width	Mounting - long hole width x length
SSBK 62	40 - 62	20	120 x 40	9 x 8
SSBK 80	63 - 80	20	120 x 40	9 x 8
SSBK 100	81 - 100	20	120 x 40	9 x 8
SSBK 118	101 - 118	25	156 x 50	9 x 18
SSBK 136	119 - 136	25	156 x 50	9 x 18
SSBK 163	137 - 163	25	156 x 50	9 x 18
SSBK 180	163 - 180	25	236 x 60	9 x 32
SSBK 207	181 - 207	25	236 x 60	9 x 32
SSBK 234	208 - 234	25	236 x 60	9 x 32
SSBK 259	235 - 259	30	300 x 60	11 x 32



1 piece hose clamp

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.