

Rubber-coated pipe clamps

DIN 3016-1 (Form D1)

Suitable: For easy mounting of hoses, cables and pipes.

Materials: Clamp: Zinc-plated steel, insert: NBR/CR

Temperature range: -35°C to max. +100°C



Type zinc-plated steel (W1)	For pipe Ø	Tape width	Mounting hole
RGSS 6	6	9	4.3
RGSS 8	8	12	5.3
RGSS 10	10	12	5.3
RGSS 12	12	12	5.3
RGSS 14	14	12	5.3
RGSS 15	15	12	5.3
RGSS 18	18	12	5.3
RGSS 20	20	12	5.3
RGSS 22	22	12	5.3
RGSS 25	25	12	5.3

Type zinc-plated steel (W1)	For pipe Ø	Tape width	Mounting hole
RGSS 28*	28	12	5.3
RGSS 30*	30	12	5.3
RGSS 32	32	20	8.4
RGSS 34	34	20	8.4
RGSS 35	35	20	8.4
RGSS 38	38	20	8.4
RGSS 40	40	20	8.4
RGSS 42	42	25	10.5
RGSS 45	45	25	10.5
RGSS 48	48	25	10.5

* similar to DIN 3016-1


fischer

Pipe clamps made of galvanised steel

Materials: Clamp: Steel zinc plated, insert: EPDM

Temperature range: -40°C to max. +100°C

- ✓ **Advantages:**
- Sound insulation for DIN 4109
 - patented quick fastener guarantees a simple and quick assembly
 - large opening angle for easy inserting of tubes (pipe clamp is opened by folding down)
 - with reliable engaging, the tube can be pre-assembled and adjusted before tightening the clamp



Typ	Ø Spann- bereich	Gewinde G*	Breite B	Zulässige Belastung
RSF 15	12 - 15	M 8 & M 10	20	800 N
RSF 19	15 - 19	M 8 & M 10	20	800 N
RSF 24	20 - 24	M 8 & M 10	20	800 N
RSF 30	25 - 30	M 8 & M 10	20	800 N
RSF 37	32 - 37	M 8 & M 10	20	800 N
RSF 45	40 - 45	M 8 & M 10	20	1000 N
RSF 52	46 - 52	M 8 & M 10	18	1000 N
RSF 54	48 - 54	M 8 & M 10	20	1000 N
RSF 61	55 - 61	M 8 & M 10	20	1000 N
RSF 67	63 - 67	M 8 & M 10	20	1000 N
RSF 73	68 - 73	M 8 & M 10	20	1800 N
RSF 80	72 - 80	M 8 & M 10	20	1800 N
RSF 86	80 - 86	M 8 & M 10	20	1800 N
RSF 92	87 - 92	M 8 & M 10	20	1800 N
RSF 103	95 - 103	M 8 & M 10	20	1800 N
RSF 116	108 - 116	M 8 & M 10	20	1800 N
RSF 129	120 - 129	M 8 & M 10	25	1500 N
RSF 137	130 - 137	M 8 & M 10	25	1500 N
RSF 145	138 - 145	M 8 & M 10	25	1500 N
RSF 155	146 - 155	M 8 & M 10	25	1500 N
RSF 163	156 - 163	M 8 & M 10	25	1500 N
RSF 172	164 - 172	M 8 & M 10	25	1500 N

* Threaded socket with two usable fastening threads

Bolts and threaded bars for pipe clamps

Hanger bolt

Type	Type	Thread	For dowel Ø
zinc-pl. steel	AISI 304		
KK STS 8	KK STS 8 ES	M 8	10 mm
KK STS 10	KK STS 10 ES	M 10	12 mm

Threaded bar, 1000 mm long

Type	Type	Thread
zinc-pl. steel	AISI 304	
GWS 8	GWS 8 ES	M 8
GWS 10	GWS 10 ES	M 10

Connection sockets for threaded bars

Type	Thread	Length
zinc-pl. steel		
GWS 8 VM	M 8	30 mm
GWS 10 VM	M 10	30 mm



Beam clamps for pipe clamps M 8/M 10

Suitable: Assembly of pipes, sprinkler systems, aeration channels on T-beams, U and elbow profiles


- ✓ **Advantages:**
- Beam clamps for easy mounting of pipe clamps without drilling and welding
 - VdS approval

Type malleable cast iron galv.	Thread female	Clamping range	Statically tested max. load
Beam clamp made of malleable cast iron galvanised			
TK M8	M 8	1-23 mm	2500 N
TK M10	M 10	1-20 mm	2500 N
Safety strap made of zinc-plated steel*			
TK SL	Safety strap suitable for beam clamps M 8 and M 10		

* VdS regulation for sprinkler systems as of tube diameter DN 65



! Order accessories at the same time!



All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.