


T pieces with reduced outlet

EN 10253 type A (DIN 2615)

Type AISI 316Ti*	Type AISI 321	Type P235GH-TC1 steel black	Connection D1 x S1	Connection D2 x S2	a	b	Version
T26,923/21A6	T26,923/21A4	T26,923/21ST	26.9 x 2.3	21.3 x 2.0	29	29	Seamless
T26,932/21A6	---	---	26.9 x 3.2	21.3 x 3.2	29	29	Seamless
T33,720/26GA6	T33,720/26GA4	---	33.7 x 2.0	26.9 x 1.6	38	38	Welded
T33,720/21GA6	T33,720/21GA4	---	---	21.3 x 1.6	38	38	Welded
T33,726/26A6	T33,726/26A4	T33,726/26ST	33.7 x 2.6	26.9 x 2.3	38	38	Seamless
T33,726/21A6	T33,726/21A4	T33,726/21ST	---	21.3 x 2.0	38	38	Seamless
---	---	T33,732/26ST	33.7 x 3.2	26.9 x 3.2	38	38	Seamless
T33,736/21A6	T33,736/21A4	---	33.7 x 3.6	21.3 x 2.9	38	38	Seamless
T42,420/33GA6	T42,420/33GA4	---	42.4 x 2.0	33.7 x 2.0	48	48	Welded
T42,420/26GA6	T42,420/26GA4	---	---	26.9 x 1.6	48	48	Welded
T42,426/33A6	T42,426/33A4	T42,426/33ST	42.4 x 2.6	33.7 x 2.6	48	48	Seamless
T42,426/26A6	T42,426/26A4	T42,426/26ST	---	26.9 x 2.3	48	48	Seamless
---	T42,436/26A4	T42,436/26ST	42.4 x 3.6	26.9 x 3.2	48	48	Seamless
T48,320/42GA6	T48,320/42GA4	---	48.3 x 2.0	42.4 x 2.0	57	57	Welded
T48,320/33GA6	T48,320/33GA4	---	---	33.7 x 2.0	57	57	Welded
T48,320/26GA6	T48,320/26GA4	---	---	26.9 x 2.0	57	57	Welded
T48,326/42A6	T48,326/42A4	T48,326/42ST	48.3 x 2.6	42.4 x 2.6	57	57	Seamless
T48,326/33A6	T48,326/33A4	T48,326/33ST	---	33.7 x 2.6	57	57	Seamless
T48,326/26A6	T48,326/26A4	T48,326/26ST	---	26.9 x 2.3	57	57	Seamless
T60,320/48GA6	T60,320/48GA4	---	60.3 x 2.0	48.3 x 2.0	64	60	Welded
T60,320/42GA6	T60,320/42GA4	---	---	42.4 x 2.0	64	57	Welded
T60,320/33GA6	T60,320/33GA4	---	---	33.7 x 2.0	64	51	Welded
T60,320/26GA6	T60,320/26GA4	---	---	26.9 x 2.0	64	44	Welded
T60,329/48A6	T60,329/48A4	T60,329/48ST	60.3 x 2.9	48.3 x 2.6	64	60	Seamless
T60,329/42A6	T60,329/42A4	T60,329/42ST	---	42.4 x 2.6	64	57	Seamless
T60,329/33A6	---	T60,329/33ST	---	33.7 x 2.6	64	51	Seamless
T60,329/26A6	T60,329/26A4	T60,329/26ST	---	26.9 x 2.3	64	44	Seamless
T60,340/48A6	---	T60,340/48ST	60.3 x 4.0	48.3 x 4.0	64	60	Seamless
T60,340/42A6	T60,340/42A4	T60,340/42ST	---	42.4 x 3.6	64	57	Seamless
T60,340/33A6	---	T60,340/33ST	---	33.7 x 3.2	64	51	Seamless
T76,123/60GA6	T76,123/60GA4	---	76.1 x 2.3	60.3 x 2.0	76	70	Welded
T76,123/48GA6	T76,123/48GA4	---	---	48.3 x 2.0	76	67	Welded
T76,129/60A6	T76,129/60A4	T76,129/60ST	76.1 x 2.9	60.3 x 2.9	76	70	Seamless
T76,129/48A6	T76,129/48A4	T76,129/48ST	---	48.3 x 2.6	76	67	Seamless
T76,129/42A6	T76,129/42A4	T76,129/42ST	---	42.4 x 2.6	76	64	Seamless
T88,923/76GA6	T88,923/76GA4	---	88.9 x 2.3	76.1 x 2.3	86	83	Welded
T88,923/60GA6	T88,923/60GA4	---	---	60.3 x 2.0	86	76	Welded
T88,923/48GA6	T88,923/48GA4	---	---	48.3 x 2.0	86	73	Welded
T88,932/76A6	T88,932/76A4	T88,932/76ST	88.9 x 3.2	76.1 x 2.9	86	83	Seamless
T88,932/60A6	T88,932/60A4	T88,932/60ST	---	60.3 x 2.9	86	76	Seamless
T88,932/48A6	T88,932/48A4	T88,932/48ST	---	48.3 x 2.6	86	73	Seamless
T88,956/60A6	T88,956/60A4	---	88.9 x 5.6	60.3 x 4.5	86	76	Seamless
T114,326/88GA6	T114,326/88GA4	---	114.3 x 2.6	88.9 x 2.3	105	98	Welded
T114,326/76GA6	T114,326/76GA4	---	---	76.1 x 2.3	105	95	Welded
T114,326/60GA6	T114,326/60GA4	---	---	60.3 x 2.0	105	89	Welded
T114,336/88A6	T114,336/88A4	T114,336/88ST	114.3 x 3.6	88.9 x 3.2	105	98	Seamless
T114,336/76A6	T114,336/76A4	T114,336/76ST	---	76.1 x 2.9	105	95	Seamless
T114,336/60A6	T114,336/60A4	T114,336/60ST	---	60.3 x 2.9	105	89	Seamless
T139,726/114GA6	T139,726/114GA4	---	139.7 x 2.6	114.3 x 2.6	124	117	Welded
T139,726/88GA6	T139,726/88GA4	---	---	88.9 x 2.3	124	111	Welded
T139,729/114GA6	T139,729/114GA4	---	139.7 x 2.9	114.3 x 2.6	124	117	Welded
T139,729/88GA6	---	---	---	88.9 x 2.3	124	111	Welded
T168,326/114GA6	T168,326/114GA4	---	168.3 x 2.6	114.3 x 2.6	143	130	Welded
T168,326/88GA6	T168,326/88GA4	---	---	88.9 x 2.3	143	124	Welded
T168,329/114GA6	T168,329/114GA4	---	168.3 x 2.9	114.3 x 2.6	143	130	Welded
T168,329/88GA6	T168,329/88GA4	---	---	88.9 x 2.3	143	124	Welded
T168,345/114A6	T168,345/114A4	T168,345/114ST	168.3 x 4.5	114.3 x 3.6	143	130	Seamless
T168,345/88A6	T168,345/88A4	T168,345/88ST	---	88.9 x 3.2	143	124	Seamless
T219,129/168GA6	T219,129/168GA4	---	219.1 x 2.9	168.3 x 2.6	178	168	Welded
T219,129/139GA6	T219,129/139GA4	---	---	139.7 x 2.6	178	162	Welded
T219,129/114GA6	T219,129/114GA4	---	---	114.3 x 2.6	178	156	Welded

* standard delivery program



Clamp brackets complete with shells and nuts

Supply volume: Round steel U-bolt clamps are delivered complete with shells and nuts.

Type zinc-plated steel	Max. tube Ø	Type zinc-plated steel	Max. tube Ø
RSBK 28	28	RSBK 50	50
RSBK 32	32	RSBK 52	52
RSBK 36	36	RSBK 54	54
RSBK 38	38	RSBK 58	58
RSBK 40	40	RSBK 60	60
RSBK 42	42	RSBK 65	65
RSBK 45	45	RSBK 70	70
RSBK 48	48	RSBK 75	75



All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.