


PVC tubes and PVC adhesives



When ordering, please state shipping length!

Packaging service: max. 2 m
Overnight express: max. 3 m
Freight: arbitrary



Tubes PVC-U

EN 1452-2 (DIN 8062) - PN 16

Materials: PVC-U
Colour: RAL 7011 - dark grey
Tube lengths: 5 m (with smooth ends)



Warning: Not suitable for compressed air or other gases under pressure!

Type	External Ø D	Wall thickness S
PVCHR 16x1.5	16	1.5
PVCHR 20x1.5	20	1.5
PVCHR 25x1.9	25	1.9
PVCHR 32x2.4	32	2.4
PVCHR 40x3.0	40	3.0
PVCHR 50x3.7	50	3.7
PVCHR 63x4.7	63	4.7
PVCHR 75x5.6	75	5.6
PVCHR 90x6.7	90	6.7
PVCHR 110x8.1	110	8.1

up to Ø 160 in PN16 and up to Ø 315 in PN10 upon request

Tube clamps with mounting holes

Materials: Body: PE (black, UV-stabilised) or PP (grey), bar: PVC-U
Temperature range: PE: -20°C to max. +50°C, PP: -10°C to max. +80°C

Type PE (black)	Type PP (grey)	Tube Ø external	Ø Mounting hole	Packing unit
KK 16 PE	KK 16 PP	16	5.0	5
KK 20 PE	KK 20 PP	20	5.0	5
KK 25 PE	KK 25 PP	25	5.5	5
KK 32 PE	KK 32 PP	32	5.5	5
KK 40 PE	KK 40 PP	40	7.0	10
KK 50 PE	KK 50 PP	50	7.0	10
KK 63 PE	KK 63 PP	63	9.0	10
KK 75 PE	KK 75 PP	75	9.0	10
KK 90 PE	KK 90 PP	90	9.0	10
KK 110 PE	KK 110 PP	110	9.0	10



Ø 16 - 32



mounting
hole

Adhesives and cleaners for PVC fittings

Cleaner: The surfaces to be bonded to each other must be clean and free of grease. If this is not guaranteed, the surface must be cleaned with PVC cleaner.

Adhesive: The adhesive can be used with or without the application of cleaning agents. The surface characteristics determine the quality of the bond.

Adhesives for PVC fittings

✓ Advantages TANGIT EXPRESS: • Ideal for fast repairs
• Quick load-bearing capacity after only 15 minutes (= 1 bar)

Type TANGIT	Type TANGIT EXPRESS	Contents
TANGIT KLEB 25	---	250 g
TANGIT KLEB 50	TANGIT KLEB 50 EXP	500 g
TANGIT KLEB 100	---	1000 g



Cleaners for PVC fittings

Type TANGIT	Contents
TANGIT REINIGER	1 l

Flat brushes for PVC adhesives

Type	Suitable for tubes Ø	Brush width
PINSEL 10	16 - 32	10 mm
PINSEL 22	40 - 63	22 mm
PINSEL 50	75 - 200	50 mm



All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.