



PVC adhesive fittings





7901

8001



7000



1002

Adhesive flange adaptors for loose flanges PVC-U

PN 16



Warning: Not suitable for compressed air or other gases under pressure!

Type	Internal Ø d	External Ø D	DN	Flange Ø D ₁	Install. length L	Flange width L ₁	Z
PVCBB 20	20	27	15	34	19	6	3
PVCBB 25	25	33	20	41	22	7	3
PVCBB 32	32	41	25	50	25	7	3
PVCBB 40	40	50	32	61	29	8	3
PVCBB 50	50	61	40	73	34	8	3
PVCBB 63	63	76	50	90	41	9	3
PVCBB 75	75	90	65	106	47	10	3
PVCBB 90	90	108	80	125	56	11	5
PVCBB 110	110	131	100	150	66	12	5

Loose flanges PVC-U

PN 16/10



Warning: Not suitable for compressed air or other gases under pressure!

Type	Nom. Ø d	External Ø D	DN	Hole circle Ø D ₁	Internal Ø D ₂	Hole Ø D ₃	Height H
PVCLF 20	20	95	15	65	28	14	12
PVCLF 25	25	105	20	75	34	14	13
PVCLF 32	32	115	25	85	42	14	15
PVCLF 40	40	140	32	100	51	18	16
PVCLF 50	50	150	40	110	62	18	17
PVCLF 63	63	165	50	125	78	18	18
PVCLF 75	75	185	65	145	92	18	22
PVCLF 90	90	200	80	160	110	18	23
PVCLF 110	110	220	100	180	133	18	24

Flat seals for PVC-U loose flanges

Type	Type	Nominal Ø	External Ø		Internal Ø	Height
EPDM	FKM	d	D	DN	D ₁	H
PVCDR 20 EPDM	PVCDR 20 FKM	20	29	15	20	2
PVCDR 25 EPDM	PVCDR 25 FKM	25	35	20	24	2
PVCDR 32 EPDM	PVCDR 32 FKM	32	44	25	29	2
PVCDR 40 EPDM	PVCDR 40 FKM	40	58	32	40	2
PVCDR 50 EPDM	PVCDR 50 FKM	50	70	40	50	2
PVCDR 63 EPDM	PVCDR 63 FKM	63	88	50	63	2
PVCDR 75 EPDM	PVCDR 75 FKM	75	103	65	74	2
PVCDR 90 EPDM	PVCDR 90 FKM	90	123	80	90	2.5*
PVCDR 110 EPDM	PVCDR 110 FKM	110	140	100	110	2.5*

* FKM: 3 mm

Adhesive threaded angles 90° PVC-U

PN 16/10

Note: • Reinforcement ring rust free (V2A)
• Connection for plastic or metal screw threads
• Do not use PVC-U damaging thread sealing paste!



Warning: Not suitable for compressed air or other gases under pressure!

Type	Internal Ø d	Thread female G	External Ø D	Length L	Z
PVCWG 2012	20	Rp 1/2"	28	25	11
PVCWG 2534	25	Rp 3/4"	34	30	14
PVCWG 3210	32	Rp 1"	43	36	17
PVCWG 40114	40	Rp 1 1/4"	54	41	21
PVCWG 50112	50	Rp 1 1/2"	63	46	26
PVCWG 6320	63	Rp 2"	78	57	33
PVCWG 75212	75	Rp 2 1/2"	89	84	40
PVCWG 9030*	90	Rp 3"	106	99	48
PVCWG 11040*	110	Rp 4"	129	119	58


* without external reinforcement, connection only for plastic thread PN 10




Ball valves
from page 280



Strainers made of
stainless steel
on page 359



Fine and backwash
filter for drinking water
on page 361



Industrial hoses
from page 213

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.