

<sup>1)</sup> as soon as the inlet pressure falls below the minimum input pressure, the drain valve opens automatically. The semi-automatic drain valve can be prevented from opening by screwing on the drain plug tightly.

## Filters Futura model series

**Version:** Filtering using the centrifugal principal and sintered filter  
**Materials:** Body: Grivory® (PA 66), seals: NBR, condensate container: Polycarbonate  
**Temperature range:** -10°C to max. +50°C  
**Input pressure:** 1.5 - 16 bar (model series 0: 1.5 - 12 bar)  
**Condensate draining:** Semi-automatic<sup>1)</sup>  
**Pore width in the filter:** 5 µm  
**Media:** Compressed air, neutral gases

✓ **Advantages:** • Simple assembly of single components using coupling kits within a model series.

### Filters Futura model series 0 1000 l/min

**Max. condensate amount:** 16 cm<sup>3</sup>  
**Optional:** Version with metal container and without inspection tube -M, automatic drain -AM, automatic drain closed when not pressurised (0 - 12 bar) -AMNC

Type	Thread	Mounting bracket	Coupling kit
F 014 F	G 1/4"	W 0 F	KP 0 F or KPW 0 F

Order example: F 014 F \*\*

Standard type

**Designation for the options:**  
 With metal container, without inspection tube .....-M  
 With automatic drain .....-AM  
 With automatic drain, closed when depressurised (0 to 12 bar) ...-AMNC

### Filters Futura model series 1 2200 l/min

**Max. condensate amount:** 28 cm<sup>3</sup>  
**ATEX:** Operating material without its own potential source of ignition in accordance with Directive 2014/34/EU  
**Optional:** Version with metal container and inspection tube -M, automatic drain -AM, automatic drain closed without pressure (0 - 16 bar) -AMNC

Type	Thread	Mounting bracket	Coupling kit
F 14 F	G 1/4"	W 1 F	KP 1 F or KPW 1 F
F 38 F	G 3/8"	W 1 F	KP 1 F or KPW 1 F

Order example: F 14 F \*\*

Standard type

**Designation for the options:**  
 With metal container and inspection tube .....-M  
 With automatic drain .....-AM  
 With automatic drain, closed when depressurised (0 to 16 bar) ...-AMNC

### Filters Futura model series 2 3500 l/min

**Max. condensate amount:** 49 cm<sup>3</sup>  
**ATEX:** Operating material without its own potential source of ignition in accordance with Directive 2014/34/EU  
**Optional:** Version with metal container and inspection tube -M, automatic drain -AM, automatic drain closed without pressure (0 - 16 bar) -AMNC

Type	Thread	Mounting bracket	Coupling kit
F 382 F	G 3/8"	W 2 F	KP 2 F or KPW 2 F
F 12 F	G 1/2"	W 2 F	KP 2 F or KPW 2 F

Order example: F 382 F \*\*

Standard type

**Designation for the options:**  
 With metal container and inspection tube .....-M  
 With automatic drain .....-AM  
 With automatic drain, closed when depressurised (0 to 16 bar) ...-AMNC

### Filters Futura model series 4 8000 l/min

**Max. condensate amount:** 87 cm<sup>3</sup>  
**ATEX:** Operating material without its own potential source of ignition in accordance with Directive 2014/34/EU  
**Optional:** Version with metal container and inspection tube -M, automatic drain -AM, automatic drain closed without pressure (0 - 16 bar) -AMNC

Type	Thread	Mounting bracket	Coupling kit
F 34 F	G 3/4"	W 4 F	KP 4 F or KPW 4 F
F 10 F	G 1"	W 4 F	KP 4 F or KPW 4 F

Order example: F 34 F \*\*

Standard type

**Designation for the options:**  
 With metal container and inspection tube .....-M  
 With automatic drain .....-AM  
 With automatic drain, closed when depressurised (0 to 16 bar) ...-AMNC