

IQS push in connections - ES

INOX

F

Dimensions can be found in the item details in our Online Shop!

IQS push in connections made of stainless steel

ES

Materials: Body and sleeve: AISI 316L, seals: FKM (cylindrical thread with captive FKM O-ring, FDA approved), (only silicone-free seals and lubricants are used during assembly)
Temperature range: -20°C to max. +150°C (Ø 16mm: -15°C to max. +120°C)
Operating pressure: -0.95 to 15 bar (Ø 16mm: max. 10 bar)
Media: Compressed air, harmless gases and liquids

Push in fittings

ES




Type	R	D
IQSG 184 ES	R 1/8"	4
IQSG 186 ES	R 1/8"	6
IQSG 188 ES	R 1/8"	8
IQSG 144 ES	R 1/4"	4
IQSG 146 ES	R 1/4"	6
IQSG 148 ES	R 1/4"	8

* exterior hexagon only

Type	R	D
IQSG 1410 ES	R 1/4"	10
IQSG 388 ES	R 3/8"	8
IQSG 3810 ES	R 3/8"	10
IQSG 3812 ES	R 3/8"	12
IQSG 1212 ES	R 1/2"	12
IQSG 1216 ES	R 1/2"	16

Push in fittings, cylindrical threads

ES




Type	G	D
IQSG M54 ES*	M 5	4
IQSG 184 G ES	G 1/8"	4
IQSG 186 G ES	G 1/8"	6
IQSG 188 G ES	G 1/8"	8
IQSG 144 G ES	G 1/4"	4
IQSG 146 G ES	G 1/4"	6

* exterior hexagon only

Type	G	D
IQSG 148 G ES	G 1/4"	8
IQSG 1410 G ES	G 1/4"	10
IQSG 3810 G ES	G 3/8"	10
IQSG 3812 G ES	G 3/8"	12
IQSG 1212 G ES	G 1/2"	12

Push in fittings with NPT thread

ES



Type	R	D
IQSG 184 ES NPT	NPT 1/8"	4
IQSG 186 ES NPT	NPT 1/8"	6
IQSG 188 ES NPT	NPT 1/8"	8
IQSG 146 ES NPT	NPT 1/4"	6
IQSG 148 ES NPT	NPT 1/4"	8

Type	R	D
IQSG 1410 ES NPT	NPT 1/4"	10
IQSG 1412 ES NPT	NPT 1/4"	12
IQSG 3810 ES NPT	NPT 3/8"	10
IQSG 3812 ES NPT	NPT 3/8"	12
IQSG 1212 ES NPT	NPT 1/2"	12

Outstanding value!

L push in fittings (fixed)

ES



Type	R	D
IQSL 184 ES B	R 1/8"	4
IQSL 186 ES B	R 1/8"	6
IQSL 188 ES B	R 1/8"	8

Type	R	D
IQSL 146 ES B	R 1/4"	6
IQSL 148 ES B	R 1/4"	8
IQSL 1410 ES B	R 1/4"	10

L push in fittings (positionable)

ES



Type	R	D
IQSL 184 ES	R 1/8"	4
IQSL 186 ES	R 1/8"	6
IQSL 188 ES	R 1/8"	8
IQSL 144 ES	R 1/4"	4
IQSL 146 ES	R 1/4"	6
IQSL 148 ES	R 1/4"	8

Type	R	D
IQSL 1410 ES	R 1/4"	10
IQSL 3810 ES	R 3/8"	10
IQSL 3812 ES	R 3/8"	12
IQSL 1212 ES	R 1/2"	12
IQSL 1216 ES	R 1/2"	16

L push in fittings, cylindrical thread (positionable)

ES



Type	G	D
IQSL M54 ES	M 5	4
IQSL M56 ES	M 5	6
IQSL 184 G ES	G 1/8"	4
IQSL 186 G ES	G 1/8"	6
IQSL 188 G ES	G 1/8"	8
IQSL 144 G ES	G 1/4"	4
IQSL 146 G ES	G 1/4"	6

Type	G	D
IQSL 148 G ES	G 1/4"	8
IQSL 1410 G ES	G 1/4"	10
IQSL 3810 G ES	G 3/8"	10
IQSL 3812 G ES	G 3/8"	12
IQSL 1210 G ES	G 1/2"	10
IQSL 1212 G ES	G 1/2"	12

L push in fittings with NPT thread (positionable)

ES



Type	R	D
IQSL 184 ES NPT	NPT 1/8"	4
IQSL 186 ES NPT	NPT 1/8"	6
IQSL 188 ES NPT	NPT 1/8"	8
IQSL 146 ES NPT	NPT 1/4"	6
IQSL 148 ES NPT	NPT 1/4"	8

Type	R	D
IQSL 1410 ES NPT	NPT 1/4"	10
IQSL 1412 ES NPT	NPT 1/4"	12
IQSL 3810 ES NPT	NPT 3/8"	10
IQSL 3812 ES NPT	NPT 3/8"	12
IQSL 1212 ES NPT	NPT 1/2"	12

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.