





M5 & M7



G 1/8" - G 1"



Silencers made of sintered bronze with sintered threads and slots

Type	Thread	D	L
SD 50*	M 5	8.5	15
SD 70*	M 7	10.0	15
SD 18	G 1/8"	11.0	16
SD 14	G 1/4"	14.0	19
SD 38	G 3/8"	18.0	25
SD 12	G 1/2"	24.0	32
SD 34	G 3/4"	29.5	52
SD 10	G 1"	35.5	60

* copper-plated thread, body without a slot

Silencers made of sintered bronze with brass threads

Type	Thread	SW	L
SD 18 MS	G 1/8"	13	18
SD 14 MS	G 1/4"	16	25
SD 38 MS	G 3/8"	19	33
SD 12 MS	G 1/2"	24	39
SD 34 MS	G 3/4"	30	47
SD 10 MS	G 1"	36	57

Silencers made of sintered bronze with hexagons

Type	Thread	SW	L
SDS 18	G 1/8"	13	22
SDS 14	G 1/4"	17	25
SDS 38	G 3/8"	22	26
SDS 12	G 1/2"	27	32
SDS 34	G 3/4"	32	40
SDS 10	G 1"	41	50
SDS 20	G 2"	70	59

Silencers made of stainless steel

Materials: Body: AISI 303, filter: AISI 304

Optional: NPT thread -NPT (only for types SD 18 ES to SD 12 ES)

Type	Thread	SW	L
SD 50 ES	M 5	8	16
SD 18 ES*	G 1/8"	13	20
SD 14 ES*	G 1/4"	16	31
SD 38 ES*	G 3/8"	19	33
SD 12 ES*	G 1/2"	24	39
SD 34 ES	G 3/4"	30	46
SD 10 ES	G 1"	36	54

* optional NPT thread

Order example: SD 18 ES **

Standard type

Designation for the options:
NPT thread*-NPT

Silencers made of plastic (porous low pressure polyethylene)

Operating pressure: Max. 10 bar

Type	Thread	Ø D	L
U 50	M 5	6.5	18
U 70*	M 7	9.8	24
U 18	G 1/8"	12.5	29
U 14	G 1/4"	15.5	36
U 38	G 3/8"	18.5	57
U 12	G 1/2"	23.3	67
U 34	G 3/4"	38.5	115
U 10	G 1"	49.0	141

* special model

Silencers made of plastic with granular fillings

Operating pressure: Max. 6 bar

Type	Thread	Ø D	L
KU 18	G 1/8"	16.0	26
KU 14	G 1/4"	20.0	35
KU 38	G 3/8"	24.0	47
KU 12	G 1/2"	24.0	47
KU 34	G 3/4"	SW50	97
KU 10	G 1"	SW50	97