

Small cylinders ISO 6432/CETOP RP 52 P - accessories

Cylinder head fastening nuts

for small cylinders ISO 6432

Type zinc-plated steel	Type V4A (stainless steel)	Thread	SW	For cylinder Ø
GM 12/25 ST	GM 12/25 ES	M 12 x 1.25	19	8 and 10
GM 16/15 ST	GM 16/15 ES	M 16 x 1.5	24	12 and 16
GM 22/15 ST	GM 22/15 ES	M 22 x 1.5	32	20 and 25



Piston rod nuts

for small cylinders ISO 6432

Type zinc-plated steel	Type V4A (stainless steel)	Thread	SW	For cylinder Ø
GM 4 ST	GM 4 ES	M 4	7	8 and 10
GM 6 ST	GM 6 ES	M 6	10	12 and 16
GM 8 ST	GM 8 ES	M 8	13	20
GM 10/25 ST	GM 10/25 ES	M 10 x 1.25	17	25




Yokes with bolts

for small cylinders ISO 6432

Optional: Material AISI 316Ti - ES 4A

Type zinc-plated steel	Type AISI 303*	A	B	C	D	E	F	G	H	For cylinder Ø
GAK 8/10	GAK 8/10 ES	M 4	8	16	11	4	21	8	4	8 and 10
GAK 12/16	GAK 12/16 ES	M 6	12	24	16	6	31	12	6	12 and 16
GAK 20	GAK 20 ES	M 8	16	32	23	8	42	16	8	20
GAK 25/32	GAK 25/32 ES	M 10 x 1.25	20	40	27	10	52	20	10	25

* type stainless steel can optically differ from the drawing




Swivel heads

for small cylinders ISO 6432

Materials: Type zinc-plated steel: Housing: Zinc-plated steel, bearing: Brass/PTFE, inside ring: 100Cr6
Type stainless steel: Housing: AISI 304, bearing: AISI 304/PTFE, inside ring: AISI 420

Type zinc-plated steel	Type stainless steel	A	B	C	D	D2	H	L	For cylinder Ø
SGS 8/10	SGS 8/10 ES	M 4	8	6.0	5	18	27	10	8 and 10
SGS 12/16	SGS 12/16 ES	M 6	9	6.75	6	20	30	12	12 and 16
SGS 20	SGS 20 ES	M 8	12	9.0	8	24	36	16	20
SGS 25/32	SGS 25/32 ES	M 10 x 1.25	14	10.5	10	28	43	20	25



Swivel heads made of plastic


for small cylinders ISO 6432

Materials: High performance polymer, self lubricating

Temperature range: -40°C to max. +80°C

Operating range: Wet environments, weak acids and alkalis, water, extreme dirt

Type	A	B	C	D	D2	H	For cylinder Ø
SGS 12/16 KU	M 6	9	7.0	6	20	30	12 and 16
SGS 20 KU	M 8	12	9.0	8	24	36	20
SGS 25/32 KU	M 10 x 1.25	14	10.5	10	30	43	25




Swivel heads 90°

for small cylinders ISO 6432

Materials: Body: Die-cast aluminium, spigot and ball: Zinc-plated steel

Type	d1	d2	d3	L	l	L1	l1	L2	l2	D1	D2	For cylinder Ø
SGS 12/16-90	M 6	10	20	40.5	36.0	30	11	14	26	10.0	13	12 and 16
SGS 20-90	M 8	12	24	49.0	43.5	36	12	17	31	12.5	16	20
SGS 25/32-90	M 10 x 1.25	14	30	58	51.5	43	15	21	37	15.0	19	25



FESTO
Festo cylinders can be found in our Online Shop



Manual tools can be found in Online Shop



Blow guns from page 524



tesa
tesa®-adhesive technology from page 585

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.