


Small cylinders ISO 6432/CETOP RP 52 P - accessories




Flexo couplings

for small cylinders ISO 6432

Type zinc-plated steel	Type AISI 303/304	A	B*	D*	SW 1*	SW 2	Radial play*	For cylinder Ø
FK 8/10	FK 8/10 ES	M 4	8	33.0	12	12	0.5	8 and 10
FK 12/16	FK 12/16 ES	M 6	10	35.0	7	15	2.0	12 and 16
FK 20	FK 20 ES	M 8	20	57.0	11	19	2.0	20
FK 25/32	FK 25/32 ES	M 10 x 1.25	20	71.5	19	30	2.0	25


* dimensions for stainless steel may vary



Flexo couplings

for screw-in cylinders


Type zinc-plated steel	A	B	D	SW 1	SW 2	Radial play*
FK M 5	M 5	12	39	7	13	0.5



Bearing blocks with bolts

for small cylinders ISO 6432


Type zinc-plated steel	Type AISI 304	B	B1	C	H	L	N	O	R	S	M	For cylinder Ø
BG 8/10	BG 8/10 ES	4.5	4	12.5	20	24	8.1	17	5	2.5	11.25	8 and 10
BG 12/16	BG 12/16 ES	5.5	6	15	25	27	12.1	23	7	3	13	12 and 16
BG 20/25	BG 20/25 ES	6.6	8	20	32	30	16.1	29.5	10	4	16	20 and 25



Foot fastenings

for small cylinders ISO 6432

Type zinc-plated steel	Type AISI 304	A	B	C	D	G	H	J	R	S	For cylinder Ø
BF 8/10	BF 8/10 ES	12	4.5	35	25	11	16	16	10	3	8 and 10
BF 12/16	BF 12/16 ES	16	5.5	42	32	14	20	20	12.5	4	12 and 16
BF 20/25	BF 20/25 ES	22	6.6	54	40	17	25	25	20	5	20 and 25



Flange fastenings

for small cylinders ISO 6432

Type zinc-plated steel	Type AISI 304	A	B	C	R	S	For cylinder Ø
BFL 8/10	BFL 8/10 ES	12	3	30	11	4.5	8 and 10
BFL 12/16	BFL 12/16 ES	16	4	40	15	5.5	12 and 16
BFL 20/25	BFL 20/25 ES	22	5	50	20	6.6	20 and 25



M 8 - Socket

Connection lines

M 8 (3 pin)

Description: Pre-fabricated connection lines with 3-pin M8 socket (M8 x1 female thread acc. to DIN EN 61076-2-104) on one side and 3 loose cable ends on the other side.

Temperature range: -25°C to max. +90°C

Voltage: max. 60V AC/DC, max. 4 A

Protection class: IP 67

Cable: PUR cable, 3 x 0,34 mm²

Cable layout: PIN 1 - brown, PIN 3 - blue, PIN 4 - black

Suitable: These cables are used preferentially for the connection of cylinder switches, inductive proximity switches or solenoid valves. Warning! They are not compatible with the (e.g. used frequently for light barriers) 4-pin M8 cable connectors.

Type straight	Type angled	Cable length
KAB M8 1 G	KAB M8 1 W	1 mtr.
KAB M8 3 G	KAB M8 3 W	3 mtr.
KAB M8 5 G	KAB M8 5 W	5 mtr.
KAB M8 10 G	KAB M8 10 W	10 mtr.

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.