


# Cylinders ISO 15552 - accessories

## Flexo couplings

## for cylinder ISO 15552

Type zinc-plated steel	Type <b>AISI 303/304</b>	A	B*	D*	SW 1*	SW 2*	Radial play*	For cylinder Ø
FK 25/32	FK 25/32 ES	M 10 x 1.25	20	71.5	19	30	2	32
FK 40	FK 40 ES	M 12 x 1.25	24	75.0	19	32	2	40
FK 50/63	FK 50/63 ES	M 16 x 1.5	32	104.0	27	41	2	50 and 63
FK 80/100	FK 80/100 ES	M 20 x 1.5	40	119.0	27	41	2	80 and 100
FK 125	FK 125 ES	M 27 x 2	54	147.0	54	65	2	125
FK 160/200	FK 160/200 ES	M 36 x 2	72	190.0	54	70	2	160 and 200


\* dimensions for stainless steel may vary



## Flexo couplings with mounting plates

## for cylinder ISO 15552

Type zinc-plated steel	Type <b>AISI 304</b>	A	D1	D2	H1	H2	M1	M2	N1	N2	SW	T	For cylinder Ø
FKB 25/32	FKB 25/32 ES	M 10 x 1.25	20	6.6	24	15	60	37	36	23	17	7	32
FKB 40	FKB 40 ES	M 12 x 1.25	25	9.0	30	20	60	56	42	38	19	9	40
FKB 50/63	FKB 50/63 ES	M 16 x 1.5	30	11.0	32	20	80	80	58	58	24	11	50 and 63
FKB 80/100	FKB 80/100 ES	M 20 x 1.5	40	14.0	35	20	90	90	65	65	36	13	80 and 100
FKB 125	FKB 125 ES	M 27 x 2	40	14.0	35	20	90	90	65	65	36	13	125
FKB 160/200	FKB 160/200 ES	M 36 x 2	60	18.0	55	30	125	125	90	90	50	17	160 and 200




## Foot fastenings

## for cylinder ISO 15552

Supply volume: 1 mounting bracket, incl. 2 fastening screws

Type zinc-plated steel	Type <b>AISI 316</b>	AA	D	FA	G	HH	L3	L5	M	N	Q	For cylinder Ø
TA 32	TA 32 ES	32	7	32	4	35	142	166	45	32.5	11	32
TA 40	TA 40 ES	36	9	36	4	36	161	187	52	38.0	8	40
TA 50	TA 50 ES	45	9	45	5	47	170	207	65	46.5	15	50
TA 63	TA 63 ES	50	9	50	5	45	185	222	75	56.5	13	63
TA 80	TA 80 ES	63	12	63	6	55	210	255	95	72.0	14	80
TA 100	TA 100 ES	75	14	71	6	57	220	270	115	89.0	16	100
TA 125	---	90	16	90	8	70	250	324	140	110.0	25	125
TA 160	---	115	18	115	9	75	300	392	180	140.0	15	160
TA 200	---	135	22	135	12	100	320	417	220	175.0	30	200
TA 250	---	165	26	165	14	100	350	464	270	220.0	25	250




## Flange fastenings at the front or rear

## for cylinder ISO 15552

Supply volume: 1 flange plate, incl. 4 fastening screws

Type zinc-plated steel	Type <b>AISI 316</b>	Ø B	D	L	M	N	T	TM	U	For cylinder Ø
TB 32	TB 32 ES	7	10	130	45	32.5	64	32	80	32
TB 40	TB 40 ES	9	10	145	52	38.0	72	36	90	40
TB 50	TB 50 ES	9	12	155	65	46.5	90	45	110	50
TB 63	TB 63 ES	9	12	170	75	56.5	100	50	120	63
TB 80	TB 80 ES	12	16	190	95	72.0	126	63	150	80
TB 100	TB 100 ES	14	16	205	115	89.0	150	75	170	100
TB 125	---	16	20	245	140	110.0	180	90	205	125
TB 160	---	18	20	280	180	140.0	230	115	260	160
TB 200	---	22	25	300	220	175.0	270	135	300	200
TB 250	---	26	25	330	285	220.0	330	165	400	250



All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.