# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878



# **HP CLEAN**

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** : HP CI FAN

Registration number REACH : Not applicable (mixture)

Product type REACH : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1 Relevant identified uses

Detergent according to Regulation (EC) No 648/2004

#### 1.2.2 Uses advised against

No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

#### Supplier of the safety data sheet

TEC7\*

Industrielaan 5B

B-2250 Olen

**3** +32 14 85 97 37

**4** +32 14 85 97 38

info@tec7.be

\*TEC7 is a registered trademark of Novatech International N.V.

#### Manufacturer of the product

Novatech International N.V.

Industrielaan 5B

B-2250 Olen

**2** +32 14 85 97 37

**4** +32 14 85 97 38

info@novatech.he

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):

+32 14 58 45 45 (BIG)

## SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) NO 1272/2008			
Class	Category	Hazard statements	
Eve Irrit.	category 2	H319: Causes serious eve irritation.	

#### 2.2. Label elements



Signal word Warning

**H-statements** H319

Causes serious eye irritation.

P-statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

Wear eye protection. P280

P264 Wash hands thoroughly after handling.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. P305 + P351 + P338

Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

#### 2.3. Other hazards

Caution! Substance is absorbed through the skin

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

http://www.big.be

© BIG vzw

Reason for revision: 3; 8; 11; 12; 15

Publication date: 2021-04-30 Date of revision: 2025-05-09

1/15

Revision number: 0100 (supersedes revision 0001 of 2022-10-16) BIG number: 67010

# SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
2-(2-butoxyethoxy)ethanol 01-2119475104-44	112-34-5 203-961-6	C<5%	Eye Irrit. 2; H319	(1)(2)(10)	Constituent	
alcohols, C9-11, ethoxylated	68439-46-3	C<5%	Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Irrit. 2; H315	(1)(10)	Constituent	
propan-2-ol 01-2119457558-25	67-63-0 200-661-7	C<5%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Constituent	

<sup>(1)</sup> For H- and EUH-statements in full: see section 16

# SECTION 4: First aid measures

#### 4.1. Description of first aid measures

#### General

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

#### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

#### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

#### After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

## 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

#### After inhalation:

No effects known.

#### After skin contact:

No effects known.

#### After eye contact:

Irritation of the eye tissue.

#### After ingestion:

AFTER INGESTION OF HIGH QUANTITIES: Vomiting. Abdominal pain. Diarrhoea. Dizziness. Headache.

#### 4.2.2 Delayed symptoms

No effects known.

## 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting class B foam extinguisher, Quick-acting CO2 extinguisher.

Major fire: Class B foam (alcohol-resistant), Water spray if puddle cannot expand.

#### 5.1.2 Unsuitable extinguishing media:

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion.

Major fire: Water; risk of puddle expansion.

#### 5.2. Special hazards arising from the substance or mixture

In case of fire: possible release of toxic/corrosive gases/vapours.

Reason for revision: 3; 8; 11; 12; 15 Publication date: 2021-04-30 Date of revision: 2025-05-09

Revision number: 0100 BIG number: 67010 2/15

<sup>(2)</sup> Substance with a Community workplace exposure limit

<sup>(10)</sup> Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

#### 5.3. Advice for firefighters

#### 5.3.1 Instructions:

No specific fire-fighting instructions required.

#### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Safety glasses (EN 166). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

No naked flames. Exposure to fire/heat: keep upwind. Exposure to fire/heat: have neighbourhood close doors and windows.

#### 6.1.1 Protective equipment for non-emergency personnel

See section 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Safety glasses (EN 166). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

#### 6.2. Environmental precautions

Contain released product, collect/pump into suitable containers. Plug the leak, cut off the supply.

#### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into inert absorbent material. Scoop absorbed substance into closing containers. Clean contaminated surfaces with an excess of water. Wash clothing and equipment after handling.

#### 6.4. Reference to other sections

See section 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 7.1. Precautions for safe handling

Keep away from naked flames/heat. In finely divided state: use spark-/explosionproof appliances. Finely divided: keep away from ignition sources/sparks. Observe normal hygiene standards. Keep container tightly closed.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Meet the legal requirements. Keep container in a well-ventilated place. Protect against frost. Keep out of direct sunlight.

#### 7.2.2 Keep away from:

Heat sources.

#### 7.2.3 Suitable packaging material:

Synthetic material.

#### 7.2.4 Non suitable packaging material:

Metal.

#### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

#### 8.1.1 Occupational exposure

#### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

### EU

2-(2-Butoxyethoxy)ethanol	Time-weighted average exposure limit 8 h (Indicative occupational	10 ppm
	exposure limit value)	
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	67.5 mg/m <sup>3</sup>
		15 ppm
	Short time value (Indicative occupational exposure limit value)	101.2 mg/m³

Reason for revision: 3; 8; 11; 12; 15 Publication date: 2021-04-30

Date of revision: 2025-05-09

Revision number: 0100 BIG number: 67010 3 / 15

Belgium 2-(2-Butoxyéthoxy)éthanol	Time weighted average time to 1	10 000
z- <sub>(</sub> z-putoxyetnoxy)etnanoi	Time-weighted average exposure limit 8 h	10 ppm 67.5 mg/m <sup>3</sup>
	Time-weighted average exposure limit 8 h	<u>.</u>
	Short time value	15 ppm
	Short time value	101.2 mg/m³
Alcool isopropylique	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	500 mg/m <sup>3</sup>
	Short time value	400 ppm
	Short time value	1000 mg/m <sup>3</sup>
The Netherlands		
2-(2-Butoxyethoxy)ethanol	Time-weighted average exposure limit 8 h (Public occupational exposure	0.7.4.nnm
2-(2-butoxyethoxy)ethanor	limit value)	е/.4 рріп
	Time-weighted average exposure limit 8 h (Public occupational exposure	e 50 mg/m³
	limit value)	J
	Short time value (Public occupational exposure limit value)	14.8 ppm
	Short time value (Public occupational exposure limit value)	100 mg/m <sup>3</sup>
		1
rance		
2-(2-butoxyethoxy)éthanol	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire	10 ppm
	indicative)	67.5 / 2
	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire	67.5 mg/m <sup>3</sup>
	indicative)  Short time value (VRI) Valour réglementaire indicative)	15 nnm
	Short time value (VRI: Valeur réglementaire indicative)	15 ppm
Name I to a granultano	Short time value (VRI: Valeur réglementaire indicative)	101.2 mg/m³
Alcool isopropylique	Short time value (VL: Valeur non réglementaire indicative)	400 ppm
	Short time value (VL: Valeur non réglementaire indicative)	980 mg/m <sup>3</sup>
Germany		
2-(2-Butoxyethoxy)ethanol	Time-weighted average exposure limit 8 h (TRGS 900)	10 ppm <b>(1)</b>
2 Butoxyethoxyjethunor	Time-weighted average exposure limit 8 h (TRGS 900)	67 mg/m <sup>3</sup> (1)
	Summe aus Dampf und Aerosolen.	07 mg/m (1)
Dronan 2 ol	***	200 nnm (2)
1) UF: 1,5 (I)	Time-weighted average exposure limit 8 h (TRGS 900) Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm <b>(2)</b> 500 mg/m <sup>3</sup> <b>(2</b>
1) UF: 1,5 (I) 2) UF: 2 (II)	Time-weighted average exposure limit 8 h (TRGS 900)	
1) UF: 1,5 (I) 2) UF: 2 (II) <b>Austria</b>	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm (2) 500 mg/m <sup>3</sup> (2
1) UF: 1,5 (I) 2) UF: 2 (II) <b>Austria</b>	Time-weighted average exposure limit 8 h (TRGS 900) Time-weighted average exposure limit 8 h (TRGS 900)	500 mg/m³ <b>(2</b>
1) UF: 1,5 (I) 2) UF: 2 (II) <b>Austria</b>	Time-weighted average exposure limit 8 h (TRGS 900) Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK)	500 mg/m³ <b>(2</b>
1) UF: 1,5 (I) 2) UF: 2 (II) <b>Austria</b>	Time-weighted average exposure limit 8 h (TRGS 900) Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK) Tagesmittelwert (MAK)	500 mg/m³ (2 200 ppm 500 mg/m³
1) UF: 1,5 (I) 2) UF: 2 (II) Austria 2-Propanol	Time-weighted average exposure limit 8 h (TRGS 900) Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK)	200 ppm 500 mg/m³ (2 200 ppm 500 mg/m³ 800 ppm
1) UF: 1,5 (I) 2) UF: 2 (II) Austria 2-Propanol	Time-weighted average exposure limit 8 h (TRGS 900) Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Tagesmittelwert (MAK)	200 ppm 500 mg/m³ 800 ppm 2000 mg/m³
1) UF: 1,5 (I) 2) UF: 2 (II) Austria 2-Propanol	Time-weighted average exposure limit 8 h (TRGS 900) Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK)	200 ppm 500 mg/m³ 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³
1) UF: 1,5 (I) 2) UF: 2 (II) Austria 2-Propanol	Time-weighted average exposure limit 8 h (TRGS 900) Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Tagesmittelwert (MAK) Tagesmittelwert (MAK) Tagesmittelwert (MAK)	200 ppm 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm
1) UF: 1,5 (I) 2) UF: 2 (II)  Austria 2-Propanol  Butyldiglykol	Time-weighted average exposure limit 8 h (TRGS 900) Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Tagesmittelwert (MAK) Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK)	200 ppm 500 mg/m³ (2 200 ppm 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³ 15 ppm
1) UF: 1,5 (I) 2) UF: 2 (II)  Austria 2-Propanol  Butyldiglykol	Time-weighted average exposure limit 8 h (TRGS 900) Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Tagesmittelwert (MAK) Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK)	200 ppm 500 mg/m³ 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³ 15 ppm 101.2 mg/m³
1) UF: 1,5 (I) 2) UF: 2 (II)  Austria 2-Propanol  Butyldiglykol	Time-weighted average exposure limit 8 h (TRGS 900) Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Tagesmittelwert (MAK) Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK)	200 ppm 500 mg/m³ (2 200 ppm 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³ 15 ppm
1) UF: 1,5 (I) 2) UF: 2 (II)  Austria 2-Propanol  Butyldiglykol	Time-weighted average exposure limit 8 h (TRGS 900) Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Tagesmittelwert (MAK) Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Time-weighted average exposure limit 8 h (Workplace exposure limit	200 ppm 500 mg/m³ 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³ 15 ppm 101.2 mg/m³
1) UF: 1,5 (I) 2) UF: 2 (II)  Austria 2-Propanol  Butyldiglykol	Time-weighted average exposure limit 8 h (TRGS 900)  Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	200 ppm 500 mg/m³ (2 200 ppm 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³ 10 ppm 101.2 mg/m³
1) UF: 1,5 (I) 2) UF: 2 (II)  Austria 2-Propanol  Butyldiglykol	Time-weighted average exposure limit 8 h (TRGS 900)  Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit	200 ppm 500 mg/m³ (2  200 ppm 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³ 15 ppm 101.2 mg/m³  10 ppm
1) UF: 1,5 (I) 2) UF: 2 (II)  Austria 2-Propanol  Butyldiglykol	Time-weighted average exposure limit 8 h (TRGS 900)  Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	200 ppm 500 mg/m³ (2 200 ppm 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³ 10 ppm 101.2 mg/m³
Propan-2-ol  (1) UF: 1,5 (I) (2) UF: 2 (II)  Austria  2-Propanol  Butyldiglykol  UK  2-(2-Butoxyethoxy)ethanol	Time-weighted average exposure limit 8 h (TRGS 900)  Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Short time value (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	200 ppm 500 mg/m³ (2  200 ppm 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³ 15 ppm 101.2 mg/m³  10 ppm
(1) UF: 1,5 (I) (2) UF: 2 (II)  Austria 2-Propanol  Butyldiglykol  UK 2-(2-Butoxyethoxy)ethanol	Time-weighted average exposure limit 8 h (TRGS 900)  Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Short time value (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	200 ppm 500 mg/m³ (2  200 ppm 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³ 15 ppm 101.2 mg/m³ 15 ppm 101.2 mg/m³
1) UF: 1,5 (I) 2) UF: 2 (II)  Austria 2-Propanol  Butyldiglykol  UK 2-(2-Butoxyethoxy)ethanol	Time-weighted average exposure limit 8 h (TRGS 900)  Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Short time value (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	200 ppm 500 mg/m³ (2  200 ppm 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³ 15 ppm 101.2 mg/m³ 15 ppm 101.2 mg/m³
1) UF: 1,5 (I) 2) UF: 2 (II)  Austria 2-Propanol  Butyldiglykol  UK 2-(2-Butoxyethoxy)ethanol	Time-weighted average exposure limit 8 h (TRGS 900)  Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Short time value (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	200 ppm 200 mg/m³ (2 200 ppm 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³ 15 ppm 101.2 mg/m³ 400 ppm 999 mg/m³
1) UF: 1,5 (I) 2) UF: 2 (II)  Austria 2-Propanol  Butyldiglykol  UK 2-(2-Butoxyethoxy)ethanol	Time-weighted average exposure limit 8 h (TRGS 900)  Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Short time value (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Short time value (Workplace exposure limit 8 h (Workplace exposure limit (EH40/2005))	200 ppm 200 mg/m³ (2 200 ppm 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³ 15 ppm 101.2 mg/m³ 15 ppm 101.2 mg/m³ 400 ppm 999 mg/m³ 500 ppm
1) UF: 1,5 (I) 2) UF: 2 (III)  Austria 2-Propanol  Butyldiglykol  JK 2-(2-Butoxyethoxy)ethanol	Time-weighted average exposure limit 8 h (TRGS 900)  Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Tagesmittelwert (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Kurzzeitwert 15(Miw) 4x (MAK)  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Short time value (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	200 ppm 200 mg/m³ (2 200 ppm 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³ 15 ppm 101.2 mg/m³ 400 ppm 999 mg/m³
1) UF: 1,5 (I) 2) UF: 2 (II)  Austria 2-Propanol  Butyldiglykol  JK 2-(2-Butoxyethoxy)ethanol  Propan-2-ol	Time-weighted average exposure limit 8 h (TRGS 900)  Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Tagesmittelwert (MAK) Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK)  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Short time value (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Short time value (Workplace exposure limit (EH40/2005))  Short time value (Workplace exposure limit (EH40/2005))  Short time value (Workplace exposure limit (EH40/2005))	200 ppm 500 mg/m³ (2  200 ppm 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³ 15 ppm 101.2 mg/m³ 15 ppm 101.2 mg/m³ 500 ppm 999 mg/m³ 500 ppm 1250 mg/m³
1) UF: 1,5 (I) 2) UF: 2 (II)  Austria 2-Propanol  Butyldiglykol  JK 2-(2-Butoxyethoxy)ethanol  Propan-2-ol	Time-weighted average exposure limit 8 h (TRGS 900)  Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Tagesmittelwert (MAK) Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK)  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) Short time value (Workplace exposure limit (EH40/2005)) Short time value (Workplace exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) Short time value (Workplace exposure limit (EH40/2005)) Short time value (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit (EH40/2005))  Time-weighted average exposure limit (EH40/2005))	200 ppm 2000 mg/m³ (2 200 ppm 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³ 15 ppm 101.2 mg/m³ 400 ppm 999 mg/m³ 500 ppm 1250 mg/m³
1) UF: 1,5 (I) 2) UF: 2 (II)  Austria 2-Propanol  Butyldiglykol  UK 2-(2-Butoxyethoxy)ethanol	Time-weighted average exposure limit 8 h (TRGS 900)  Time-weighted average exposure limit 8 h (TRGS 900)  Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Tagesmittelwert (MAK) Tagesmittelwert (MAK) Tagesmittelwert (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK) Kurzzeitwert 15(Miw) 4x (MAK)  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Short time value (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))  Short time value (Workplace exposure limit (EH40/2005))  Short time value (Workplace exposure limit (EH40/2005))  Short time value (Workplace exposure limit (EH40/2005))	200 ppm 500 mg/m³ (2  200 ppm 500 mg/m³ 800 ppm 2000 mg/m³ 10 ppm 67.5 mg/m³ 15 ppm 101.2 mg/m³ 15 ppm 101.2 mg/m³ 500 ppm 999 mg/m³ 500 ppm 1250 mg/m³

Reason for revision: 3; 8; 11; 12; 15

Publication date: 2021-04-30

Date of revision: 2025-05-09

Revision number: 0100 BIG number: 67010 4 / 15

#### Germany

Propan-2-ol (Aceton)		25 mg/l	
Propan-2-ol (Aceton)	Vollblut: expositionsende, bzw. schichtende	25 mg/l	

#### USA (BEI-ACGIH)

2-Propanol (Acetone)	Urine: end of shift at end of workweek	40 mg/L	Background, Nonspecific
----------------------	--	---------	-------------------------

#### 8.1.2 Sampling methods

Product name	Test	Number	
Butyl Carbitol	OSHA	2095	
Isopropanol (Volatile Organic compounds)	NIOSH	2549	
Isopropyl Alcohol (Alcohols I)	NIOSH	1400	
Isopropyl Alcohol	NIOSH	3900	
Isopropyl Alcohol	OSHA	5001	

#### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

#### 8.1.4 Threshold values

#### **DNEL/DMEL - Workers**

2-(2-butoxyethoxy)ethanol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term local effects inhalation	67.5 mg/m³	
	Acute local effects inhalation	101.2 mg/m³	

#### propan-2-ol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	500 mg/m³	
	Acute systemic effects inhalation	1000 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	888 mg/kg bw/day	

#### **DNEL/DMEL - General population**

#### 2-(2-butoxyethoxy)ethanol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects oral	6.25 mg/kg bw/day	
propan-2-ol			

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	89 mg/m³	
	Acute systemic effects inhalation	178 mg/m³	
	Long-term systemic effects dermal	319 mg/kg bw/day	
	Long-term systemic effects oral	26 mg/kg bw/day	
	Acute systemic effects oral	51 mg/kg bw/day	

#### 8.1.5 Control banding

If applicable and available it will be listed below.

### 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. In finely divided state: use spark-/explosionproof appliances. Finely divided: keep away from ignition sources/sparks. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

## 8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

#### a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

#### b) Hand protection:

Protective gloves against chemicals (EN 374).

## c) Eye protection:

Safety glasses (EN 166).

#### d) Skin protection:

Protective clothing (EN 14605 or EN 13034).

#### 8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

· /	
Physical form	Liquid
Colour	Green
Odour	Characteristic odour
Odour threshold	No data available in the literature
Melting point	0 °C
Boiling point	76 °C - 360 °C
Flammability	Not classified as flammable

Reason for revision: 3; 8; 11; 12; 15

Publication date: 2021-04-30

Date of revision: 2025-05-09

Revision number: 0100 BIG number: 67010 5 / 15

Explosion limits	0.85 - 24.6 vol %
Flash point	No data available in the literature
Auto-ignition temperature	200 °C
Decomposition temperature	No data available in the literature
рН	9.1
Kinematic viscosity	1 mm²/s ; 20 °C
Dynamic viscosity	1 mPa.s ; 20 °C
Solubility	Water ; soluble
Log Kow	Not applicable (mixture)
Vapour pressure	No data available in the literature
Absolute density	1018 kg/m³ ; 20 °C
Relative density	1.02 ; 20 °C
Relative vapour density	No data available in the literature
Particle size	Not applicable (liquid)

#### 9.2. Other information

Evaporation rate	1.3 ; Butyl acetate
------------------	---------------------

# SECTION 10: Stability and reactivity

### 10.1. Reactivity

Heating increases the fire hazard. Basic reaction.

#### 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

No data available.

#### 10.4. Conditions to avoid

#### **Precautionary measures**

Keep away from naked flames/heat. In finely divided state: use spark-/explosionproof appliances. Finely divided: keep away from ignition sources/sparks.

#### 10.5. Incompatible materials

No data available.

## 10.6. Hazardous decomposition products

No data available.

# SECTION 11: Toxicological information

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## 11.1.1 Test results

#### Acute toxicity

#### HP CLEAN

No (test)data on the mixture available

Judgement is based on the relevant ingredients

#### 2-(2-butoxyethoxy)ethanol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD 401	2410 mg/kg bw - 5530 mg/kg bw		Mouse (male)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	2764 mg/kg bw	24 h	Rabbit (male)	Experimental value	
Inhalation (aerosol)	IRT (inhalation risk test)	BASF test	> 29 ppm	2 h	Rat	Experimental value	

## alcohols, C9-11, ethoxylated

Route of exposure	Parameter	Method	Value	Exposure time	 Value determination	Remark
Oral			category 4		Literature study	

Reason for revision: 3; 8; 11; 12; 15

Publication date: 2021-04-30

Date of revision: 2025-05-09

Revision number: 0100 BIG number: 67010 6 / 15

propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD 401	5840 mg/kg bw		Rat	Experimental value	
Dermal	LD50	Equivalent to OECD 402	13120 mg/kg bw/day	24 h	Rabbit	Experimental value	Converted value
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 10000 ppm		Rat (male / female)	Experimental value	

#### Conclusion

Not classified for acute toxicity

### Corrosion/irritation

#### **HP CLEAN**

No (test)data on the mixture available

Classification is based on the relevant ingredients  $\underline{\text{2-}(2\text{-butoxyethoxy})\text{ethanol}}$ 

							_
Route of exposure	Result	Method	Exposure time	Time point	Species	Value	Remark
						determination	
Eye	Highly irritating	OECD 405	72 h	24; 48; 72 hours	Rabbit	Experimental	Single treatment
						value	with rinsing
Skin	Slightly irritating	OECD 404	1 h	24; 48; 72 hours	Rabbit	Experimental	
						value	

alcohols, C9-11, ethoxylated

Route of exposure	Result	Method	Exposure time	Time point	 Value determination	Remark
Eye	Serious eye damage; category 1				Literature study	
Skin	Irritating; category 2				Literature study	

propan-2-ol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value	Remark
						determination	
Eye		Equivalent to OECD 405		1; 2; 3; 4; 7; 10; 14 days	Rabbit	'	Single treatment without rinsing
Skin	Not irritating		4 h	4; 24; 48; 72 hours	Rabbit	Experimental value	

#### Conclusion

Causes serious eye irritation.

Not classified as irritating to the skin

Not classified as irritating to the respiratory system

#### Respiratory or skin sensitisation

### HP CLEAN

No (test)data on the mixture available

Judgement is based on the relevant ingredients

2-(2-butoxyethoxy)ethanol

Route of exposure	Result	Method	•	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD			Guinea pig (male	Experimental value	
		406			/ female)		

propan-2-ol

Route of expos	re Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

## **Conclusion**

Not classified as sensitizing for skin Not classified as sensitizing for inhalation

#### Specific target organ toxicity

#### **HP CLEAN**

No (test)data on the mixture available Judgement is based on the relevant ingredients

Reason for revision: 3; 8; 11; 12; 15 Publication date: 2021-04-30 Date of revision: 2025-05-09

Revision number: 0100 BIG number: 67010 7 / 15

2-(2-butoxyethoxy)ethanol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time		Value determination	Remark
Oral (drinking water)	NOAEL	OECD 408	250 mg/kg bw/day	No effect	· · / ·	Rat (male / female)	Experimental value	
Dermal	NOAEL local effects	EPA TSCA consent order	< 200 mg/kg bw/day	Skin (no effect)	13 weeks (daily, 5 days / week)	Rat (male / female)	Experimental value	
Dermal	NOAEL systemic effects	EPA OTS 798.6050	2000 mg/kg bw/day	No adverse systemic effects	13 weeks (daily, 5 days / week)	Rat (male / female)	Experimental value	
Inhalation	NOAEL	OECD 413	94 mg/m³ air	Lungs (no effect)	90 days (6h / day)	Rat (male / female)	Experimental value	

propan-2-ol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time		Value determination	Remark
Oral							Data waiving	
Inhalation (vapours)	NOAEC	OECD 451	5000 ppm	No adverse systemic effects	` '	Rat (male / female)	Experimental value	
Inhalation (vapours)	Dose level	Equivalent to OECD 403	5000 ppm	Central nervous system (drowsiness, dizziness)		Rat (male / female)	Experimental value	

#### Conclusion

Not classified for subchronic toxicity

### Mutagenicity (in vitro)

#### HP CLEAN

No (test)data on the mixture available

Judgement is based on the relevant ingredients

2-(2-butoxyethoxy)ethanol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic	Equivalent to OECD 476	Chinese hamster ovary		Experimental value	
activation, negative		(CHO)			
without metabolic					
activation					
Negative with metabolic	OECD 471	Bacteria (S. typhimurium		Experimental value	
activation, negative		and E. coli)			
without metabolic					
activation					

propan-2-ol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)	No effect	Experimental value	

## Mutagenicity (in vivo)

## HP CLEAN

No (test)data on the mixture available

Judgement is based on the relevant ingredients

2-(2-butoxyethoxy)ethanol

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Oral (stomach	Equivalent to OECD 475		Mouse (male /	No effect	Experimental value	Single treatment
tube))			female)			
nronan-2-ol	•	-	•	•	-	

propan-2-ol

<del></del>						
Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Intraperitoneal)	Equivalent to OECD 474		Mouse (male /	No effect	Experimental value	Single
			female)			intraperitoneal
						injection

## Conclusion

Not classified for mutagenic or genotoxic toxicity

#### Carcinogenicity

Reason for revision: 3; 8; 11; 12; 15 Publication date: 2021-04-30

Date of revision: 2025-05-09

Revision number: 0100 BIG number: 67010 8 / 15

## HP CLEAN

No (test)data on the mixture available

Judgement is based on the relevant ingredients

#### propan-2-ol

Route of	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
exposure								
Inhalation	NOEL	OECD 451	5000 ppm	No carcinogenic	104 weeks (6h /	Rat (male /	Experimental value	
(vapours)				effect	day, 5 days /	female)		
					week)			

#### Conclusion

Not classified for carcinogenicity

#### Reproductive toxicity

#### **HP CLEAN**

No (test)data on the mixture available

Judgement is based on the relevant ingredients <u>2-(2-butoxyethoxy)ethanol</u>

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Oral (diet))	Dose level	Equivalent to OECD 414	633 mg/kg bw/day	21 days (gestation, daily)	Rat	No effect	Experimental value	
Maternal toxicity (Oral (diet))	Dose level	Equivalent to OECD 414	633 mg/kg bw/day	21 days (gestation, daily)	Rat	No effect	Experimental value	
Effects on fertility (Oral (drinking water))	NOAEL (P)	NTP continuous breeding protocol	720 mg/kg bw/day	14 week(s)	Mouse (male / female)	No effect	Experimental value	

#### propan-2-ol

Category	Parameter	Method	Value	Exposure time	Species		Value determination	Remark
Developmental toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	Foetus (no effect)	Experimental value	
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect	Experimental value	
Effects on fertility (Oral (stomach tube))	NOAEL	Equivalent to OECD 416	> 1000 mg/kg bw/day		Rat (male / female)	No effect	Experimental value	

#### Conclusion

Not classified for reprotoxic or developmental toxicity

#### Aspiration hazard

## HP CLEAN

Judgement is based on the relevant ingredients

Not classified for aspiration toxicity

## **Toxicity other effects**

No (test)data on the mixture available

#### Chronic effects from short and long-term exposure

#### HP CLEAN

No effects known.

#### 11.2. Information on other hazards

No evidence of endocrine disrupting properties

# SECTION 12: Ecological information

## 12.1. Toxicity

Revision number: 0100

#### **HP CLEAN**

No (test)data on the mixture available

Judgement of the mixture is based on the relevant ingredients

Reason for revision: 3; 8; 11; 12; 15 Publication date: 2021-04-30 Date of revision: 2025-05-09

BIG number: 67010 9/15

2-(2-butoxyethoxy)ethanol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	1300 mg/l	96 h	Lepomis macrochirus	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	EU Method C.2	> 100 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Long-term toxicity fish	ChV	ECOSAR	370 mg/l	30 day(s)	Pisces		Fresh water	QSAR
Long-term toxicity aquatic crustacea	ChV	ECOSAR	139 mg/l		Invertebrata			QSAR
Toxicity aquatic micro- organisms	EC10	Equivalent to OECD 209	> 1995 mg/l	30 minutes	Activated sludge	Static system	Fresh water	Experimental value; Respiration

propan-2-ol Value Parameter Method Duration Test design Fresh/salt Value determination Species water LC50 9640 mg/l -96 h Acute toxicity fishes Equivalent to **Pimephales** Flow-Fresh water Experimental value; **OECD 203** 10000 mg/l promelas through Lethal system Acute toxicity crustacea LC50 Equivalent to > 10000 mg/l 24 h Daphnia magna Static Fresh water Experimental value; **OECD 202** system Locomotor effect Toxicity algae and other 1800 mg/l 7 day(s) Toxicity Scenedesmus Static Experimental value; Fresh water threshold quadricauda aquatic plants system Toxicity test Long-term toxicity fish NOELR Petrotox > 1000 mg/l 28 day(s) Brachydanio Estimated value computer rerio model Long-term toxicity aquatic NOEC 141 mg/l 16 day(s) Daphnia magna Fresh water Experimental value; crustacea Growth 1050 mg/l Toxicity aquatic micro-Toxicity 16 h Pseudomonas Static Experimental value; Equivalent to Fresh water organisms threshold DIN 38412/8 putida system Toxicity test EC50 ISO 8192 41676 mg/l 30 minutes Activated sludge Experimental value

#### Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

### 12.2. Persistence and degradability

2-(2-butoxyethoxy)ethanol

**Biodegradation water** 

Method	Value	Duration	Value determination
OECD 301C	85 %; Oxygen consumption	28 day(s)	Experimental value

alcohols, C9-11, ethoxylated

**Biodegradation water** 

Method \	Value	Duration	Value determination
	72 %	28 day(s)	Weight of evidence

propan-2-ol

**Biodegradation water** 

Method	Value	Duration	Value determination
EU Method C.5	53 %; Oxygen consumption	5 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	18 h	1.5E6 /cm³	Calculated value

#### Conclusion

Water

The surfactant(s) is/are biodegradable according to Regulation (EC) No 648/2004

## 12.3. Bioaccumulative potential

**HP CLEAN** 

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

#### 2-(2-butoxyethoxy)ethanol

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		1	20 °C	Experimental value

Reason for revision: 3; 8; 11; 12; 15

Publication date: 2021-04-30

Date of revision: 2025-05-09

Revision number: 0100 BIG number: 67010 10 / 15

#### alcohols, C9-11, ethoxylated

#### **BCF** fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		12.7 l/kg - 237 l/kg	72 h	Pimephales promelas	Read-across

#### Log Kow

Method	Remark	Value	Temperature	Value determination
KOWWIN		3.3 - 3.73		QSAR

#### propan-2-ol

#### Log Kow

Method	Remark	Value	Temperature	Value determination
			25 °C	Weight of evidence approach

#### Conclusion

Does not contain bioaccumulative component(s)

#### 12.4. Mobility in soil

## 2-(2-butoxyethoxy)ethanol

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc		0.64 - 1.0	Calculated value

#### Percent distribution

Method	Fraction air		Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level I	0.01 %	0 %	0.01 %	0.3 %	99.7 %	QSAR

#### alcohols, C9-11, ethoxylated

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	1.399 - 1.656	Calculated value

#### propan-2-ol

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc		0.19 - 0.54	Calculated value

#### Conclusion

Contains component(s) with potential for mobility in the soil

#### 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

#### 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

#### 12.7. Other adverse effects

#### HP CLEAN

#### Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

#### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

#### Water ecotoxicity pH

pH shift

#### 2-(2-butoxyethoxy)ethanol

#### Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

#### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

#### Groundwater

Groundwater pollutant

#### alcohols, C9-11, ethoxylated

#### Groundwater

Groundwater pollutant

## propan-2-ol

#### Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

#### Groundwater

Groundwater pollutant

Reason for revision: 3; 8; 11; 12; 15

Publication date: 2021-04-30

Date of revision: 2025-05-09

Revision number: 0100 BIG number: 67010 11 / 15

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

#### **European Union**

Can be considered as non hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

20 01 30 (separately collected fractions (except 15 01): detergents other than those mentioned in 20 01 29). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

#### 13.1.3 Packaging/Container

#### **European Union**

Waste material code packaging (Directive 2008/98/EC).

15 01 02 (plastic packaging).

## SECTION 14: Transport information

#### Road (ADR), Rail (RID), Inland waterways (ADN), Sea (IMDG/IMSBC), Air (ICAO-TI/IATA-DGR)

14.	1. UN number or ID number					
	Transport	Not subject				
14.	1.2. UN proper shipping name					
14.	4.3. Transport hazard class(es)					
	Hazard identification number					
	Class					
	Classification code					
14.	4. Packing group					
	Packing group					
	Labels					
14.	5. Environmental hazards					
	Environmentally hazardous substance mark	no				
14.	6. Special precautions for user					
	Special provisions					
	Limited quantities					
14.	7. Maritime transport in bulk according to IMO instruments					
	Annex II of MARPOL 73/78	Not applicable, based on available data				

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture <a href="European legislation"><u>European legislation:</u></a>

VOC content Directive 2010/75/EU

VOC content	Remark
1.78 %	
18.12 g/l	

#### Directive 2012/18/EU (Seveso III)

Not subject to registration according to Directive 2012/18/EU (Seveso III)

Ingredients according to Regulation (EC) No 648/2004 and amendments

 $<\!5\%\ phosphates, <\!5\%\ non\text{-ionic surfactants},\ perfumes$ 

#### **REACH Candidate list**

Does not contain component(s) included in candidate list of substances of very high concern (SVHC) for authorisation (Article 59 of Regulation (EC) No 1907/2006)

#### **REACH Annex XIV - Authorisation**

Does not contain component(s) included in Annex XIV of Regulation (EC) No 1907/2006: list of substances subject to authorisation

#### REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	) - · · · · · · · · · · · · · · · · · ·		
	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction	
	Substances of of the mixture		
· 2-(2-butoxyethoxy)ethanol	Liquid substances or mixtures fulfilling the	1. Shall not be used in:	
· alcohols, C9-11, ethoxylated	criteria for any of the following hazard classes	<ul> <li>ornamental articles intended to produce light or colour effects by means of different</li> </ul>	
· propan-2-ol	or categories set out in Annex I to Regulation	phases, for example in ornamental lamps and ashtrays,	
	(EC) No 1272/2008:	— tricks and jokes,	

Reason for revision: 3; 8; 11; 12; 15

Publication date: 2021-04-30

Date of revision: 2025-05-09

Revision number: 0100 BIG number: 67010 12 / 15

		(a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	— games for one or more participants, or any article intended to be used as such, even with ornamental aspects,  2. Articles not complying with paragraph 1 shall not be placed on the market.  3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:  — can be used as fuel in decorative oil lamps for supply to the general public, and,  — present an aspiration hazard and are labelled with H304,  4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).  5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:  a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage";  b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";  c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
	propan-2-ol	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:  — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs.  2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:  "For professional users only".  3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.  4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
	2-(2-butoxyethoxy)ethanol	2-(2-butoxyethoxy)ethanol (DEGBE)	1. Shall not be placed on the market for the first time after 27 June 2010, for supply to the general public, as a constituent of spray paints or spray cleaners in aerosol dispensers in concentrations equal to or greater than 3 % by weight.  2. Spray paints and spray cleaners in aerosol dispensers containing DEGBE and not conforming to paragraph 1 shall not be placed on the market for supply to the general public after 27 December 2010.  3. Without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that paints other than spray paints containing DEGBE in concentrations equal to or greater than 3 % by weight of that are placed on the market for supply to the general public are visibly, legibly and indelibly marked by 27 December 2010 as follows: "Do not use in paint spraying equipment".
	2-(2-butoxyethoxy)ethanol propan-2-ol	Substances falling within one or more of the following points:  (a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008:  — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation  — reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation  — reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation  — skin sensitiser category 1, 1A or 1B  — skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2  — serious eye damage category 1 or eye irritant category 2  (b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council  (c) substances listed in Annex IV to Regulation is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex.  The ancillary requirements in paragraphs 7	Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081
Pos	son for revision: 3: 8: 11: 12: 15	<u> </u>	Publication date: 2021-04-30

Reason for revision: 3; 8; 11; 12; 15

Publication date: 2021-04-30

Date of revision: 2025-05-09

Revision number: 0100 BIG number: 67010 13 / 15

and 8 of column 2 of this entry apply to all	
mixtures for use for tattooing purposes,	
whether or not they contain a substance	
falling within points (a) to (d) of this column of	
this entry	

# National legislation Belgium HP CLEAN

No data available

propan-2-ol

Agents cancérigènes,	alcool isopropylique; VI.2.2.; Liste des procédés au cours desquels une substance ou un mélange se dégage; Procédé à
mutagènes et reprotoxiques et	l'acide fort dans la fabrication d'alcool isopropylique.
aux agents possédant des	
propriétés perturbant le	
système endocrinien (Code du	
bien-être au travail, Livre VI,	
titre 2)	

### **National legislation The Netherlands**

	Waterbezwaarlijkheid	B (5); Algemene Beoordelingsmethodiek (ABM)
<u>2</u> -	-butoxyethoxy)ethanol	
	Huidopname (wettelijk)	2-(2-Butoxyethoxy)ethanol; H

# National legislation France HP CLEAN

No data available

# National legislation Germany HP CLEAN

	Lagerklasse (TRGS510)	10: Brennbare Flüssigkeiten die keiner der vorgenannten LGK zuzuordnen sind	
	WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017	
2-	2-(2-butoxyethoxy)ethanol		
	TA-Luft	5.2.5	
	TRGS900 - Risiko der	2-(2-Butoxyethoxy)ethanol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des	
	Fruchtschädigung	biologischen Grenzwertes nicht befürchtet zu werden	
<u>al</u>	alcohols, C9-11, ethoxylated		
	TA-Luft	5.2.5/I	
pi	propan-2-ol		
	TA-Luft	5.2.5	
	TRGS900 - Risiko der	Propan-2-ol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen	
	Fruchtschädigung	Grenzwertes nicht befürchtet zu werden	

#### **National legislation Austria**

HP CLEAN

No data available

#### **National legislation United Kingdom**

**HP CLEAN** 

No data available

# Other relevant data HP CLEAN

No data available

propan-2-ol

TLV - Carcinogen	2-propanol; A4
IARC - classification	3; Isopropanol

## 15.2. Chemical safety assessment

No chemical safety assessment is required for a mixture.

# SECTION 16: Other information

## Full text of any H- and EUH-statements referred to under section 3:

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

INTERNAL CLASSIFICATION BY BIG

(\*) ADI Acceptable daily intake

AOEL Acceptable operator exposure level

ATE **Acute Toxicity Estimate** BCF **Bioconcentration Factor** 

Reason for revision: 3; 8; 11; 12; 15 Publication date: 2021-04-30

Date of revision: 2025-05-09

Revision number: 0100 BIG number: 67010 14 / 15

BEI Biological Exposure Indices

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

DMEL Derived Minimal Effect Level
DNEL Derived No Effect Level
EC10 Effect Concentration 10 %
EC50 Effect Concentration 50 %

ErC50 EC50 in terms of reduction of growth rate

GLP Good Laboratory Practice
LCO Lethal Concentration 0 %
LC50 Lethal Concentration 50 %
LD50 Lethal Dose 50 %

LOAEC/LOAEL Lowest Observed Adverse Effect Concentration/Lowest Observed Adverse Effect Level

NOAEC/NOAEL No Observed Adverse Effect Concentration/No Observed Adverse Effect Level

NOEC/NOEL No Observed Effect Concentration/No Observed Effect Level
OECD Organisation for Economic Co-operation and Development

PBT Persistent, Bioaccumulative & Toxic
PNEC Predicted No Effect Concentration
STP Sludge Treatment Process

vPvB very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3; 8; 11; 12; 15 Publication date: 2021-04-30

Date of revision: 2025-05-09

Revision number: 0100 BIG number: 67010 15 / 15