


Water guns



Hose sprayers with hose connections

Type	Size	Nozzle Ø	DN	Hose Ø internal	Length L approx.
GSK SPR 13	1/2"	5.3	9	13 (1/2")	90
GSK SPR 19	3/4"	6.4	16	19 (3/4")	110
GSK SPR 25	1"	7.2	21	25 (1")	135



Hose sprayers for garden hose quick couplings

40 mm

Type	Size	Nozzle Ø	DN	Length L approx.	Seal NBR
GSK SPR 12	1/2"	5.3	9	84	GKOR
GSK SPR 34	3/4"	6.4	14	95	GKOR
GSK SPR 10	1"	7.0	20	112	GKOR

Plastic water sprinklers

8 bar

Materials: PA 66 (FDA 177.1500), valve: Stainless steel, seal: EPDM (KTW approval and FDA 177.2600)

Temperature range: Max. +60°C

Operating pressure: Max. 8 bar

Operating range: Ergonomic hand shower for the food processing industry

- ✓ **Advantages:**
- Ergonomically shaped
 - Low weight

Type	Connection
BRAUSE 12 PA	G 1/2" (FT)

Water conserving guns

24 bar

Materials: Stainless steel/brass combination rubber jacketing (type stainless steel: stainless steel complete, rubber jacketed), rubber jacketing: EPDM

Temperature range: Max. +95°C

Operating pressure: Max. 24 bar

Flow: Max. 80 l/min.

☞ **Optional:** Insulated stainless steel safety bracket -S

- ✓ **Advantages:**
- Variable regulation of the water jet from a fine spray mist to a concentrated jet.
 - Optimum protection against heat, cold and impact by the thick rubber jacketing.
 - Mounting clamp for continuous operation.

Type stainless steel/brass	Type complete stainless steel	Connection
WSP 12	WSP 12 ES	G 1/2" (FT)
Replace. parts blue	Replace. parts white	
WSP 12 GRIFF	WSP 12 GRIFF WS	Grip sleeve
WSP 12 SCHUTZ	WSP 12 SCHUTZ WS	Protective sleeve
Hot water swivel joint		
WSP 12 DREH	WSP 12 DREH ES	G 1/2" (FT/MT)



Safety washing guns

40 bar

Materials: Body: Aluminium, lever: Brass, grip plates: Polyamide, safety bar: Zinc-plated steel

Temperature range: Max. +90°C

Operating pressure: Max. 40 bar

Flow: Nozzles Ø 2 mm (Standard): At 6 bar - 5 l/min., at 16 bar - 8 l/min., at 40 bar - 13 l/min.
Nozzles Ø 4 mm (optional): At 6 bar - 20 l/min., at 16 bar - 32 l/min., at 40 bar - 50 l/min.

- ✓ **Advantages:**
- Variable regulation of the water jet from a fine spray mist to a concentrated jet.
 - Operating pressure up to 40 bar.
 - Actuating lever secured by safety bar.

☞ **Optional:** Nozzle 4 mm Ø -4

Type	Connection
WSPH 13	13 mm hose connection
WSPH 19	19 mm hose connection
Replacement nozzles	
WSPH DUSE 2	Nozzles Ø 2 mm
WSPH DUSE 4	Nozzles Ø 4 mm

☞ **Order example:** WSPH 13 **

Standard type

Designation for the options:
Nozzles Ø 4mm-4



Garden hose couplings from page 178



Hose clamps from page 234



Water hoses - Goldschlange® on page 212



GARDENA Hose sprayers from page 181

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.