

Hand tyre inflators (pressure gauges Ø 63)

for tyre valves VG 8 (7.7 mm)

Type	Pressure gauge display	Plug	Filling hose connection	Connection	Replacement pressure gauge
Hobby version					
HRFB	0 - 12 bar	Moment	G 1/4", rigid	Coupling plug NW 7.2*	---
Industrial version					
HRF	0 - 10 bar	Lever	G 1/4", rotatable	6 mm nozzle	HRF MANO
HRF KS	0 - 10 bar	Lever	G 1/4", rotatable	Coupling plug NW 7.2*	HRF MANO
HRFS	0 - 12 bar	Moment	G 1/4", rigid	Coupling plug NW 7.2*	HRFS MANO

* standard coupling



Hand tyre inflators (pressure gauges Ø 80)

for tyre valves VG 8 (7.7 mm)

Connection: Coupling plugs, NW 7.2 (standard coupling)

Type	Pressure gauge display	Plug	Filling hose connection	Version	Replacement pressure gauge*
HRFG	0 - 12 bar	Lever	G 1/4", rotatable	Calibrated	HRFG MANO
HRFG B	0 - 12 bar	Lever	G 1/4", rotatable	Not calibrated	HRFG MANO
HRFG TS	0 - 12 bar	Petrol sta.	G 1/4", rotatable	Calibrated	HRFG MANO
HRFG 25	0 - 25 bar	Lever	G 1/4", rotatable	Not calibrated	HRFG MANO 25
HRFGS	0 - 12 bar	Moment	G 1/4", rigid	Calibrated	HRFGS MANO

* replacing the pressure gauge invalidates the HRFG's calibration seal. A new calibration is needed after the pressure gauge is changed.



Hand tyre inflator accessories

for tyre valves VG 8 (7.7 mm)

Type	Connection	Description	Replacement seals
LEVER PLUG	6 mm nozzle	Lever plug	HEBELSTECKER MEM
CLIP CONNECTOR	6 mm nozzle	Clip connector	---
QUICKSTECKER 6	6 mm nozzle	Profi-plug with double	---
QUICKSTECKER 8	8 mm nozzle	Claw holder	---
PETROL STATION PLUG	Valve plug VG 8 (7.7 mm)	Petrol station plug	TANKSTELLENST MEM
TANKSTELLENSTECKER S	6 mm nozzle	Petrol station plug	TANKSTELLENST MEM
PRUFVENTIL 18	G 1/8" (MT)	Check valve with VG 8 tyre valve and dust cover	---
HRFG SCHLAUCH	G 1/4"/M 20x1 (MT)	500 mm filling hose, with lever plug	HEBELSTECKER MEM
HRFG SCHLAUCH MS	G 1/4"/M 20x1 (MT), rotatable	500 mm filling hose, with clip connector	---
HRFG SCHLAUCH TS	G 1/4"/M 20x1 (MT), rotatable	500 mm filling hose, with petrol station plug	TANKSTELLENST MEM



Hose nozzles for lorry tyre inflation bottles

✓ **Advantages:** • This hose nozzle fits the majority of vehicles with compressed air brakes, e.g. trucks, Unimog, etc.

Type	Thread	Connection
ST LKW	M 16 x 1.5	6 mm nozzle




PU hose sets with coupling & plug on page 208



Coil tubes assembled with couplings from page 200



Ball valves with venting from page 287



All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise in writing.