



Screwdriver holders

- ✓ **Advantages:**
- Keeps the tool always close at hand
 - Protects the tool from external influences
 - Ensures increased safety due to a clear working area

Rugged industrial rubber protects your compressed air tool and holds it securely in its position. This quiver is fastened to the wall and offers your tool the best protection. Thanks to its conical shape, the quiver can take almost any tool size.

Type	Diameter	Height	Mounting hole
SCHRAUBERKÖCHER	70 mm/110 mm	145/170	M 6



type 4114



type 818



type 413WP

Power socket sets for impact screwdrivers

Type	Version	SW	For actuator
Power socket sets			
3113	13-pc. set in plastic magazine	7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18 and 19 3/8" (9.5 mm)	
4114	14-pc. set in plastic magazine	10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 26 and 27 1/2" (12.7 mm)	
618	8-pc. set in plastic magazine	26, 27, 29, 30, 32, 35, 36 and 38	3/4" (19.0 mm)
818	8-pc. set in plastic magazine	27, 30, 32, 33, 35, 36, 38 and 41	1" (25.4 mm)
Lorry power socket sets			
814D	4-pc. shock resistant	27, 32, 33 and 36	1" (25.4 mm)
Power socket sets, long, with PVC coating for fitting aluminium wheels			
413WP	3-pc. set in plastic magazine	17, 19 and 21	1/2" (12.7 mm)

Long power sockets for impact screwdrivers

Version: Long, thin walled, blistered

Type	SW	For actuator
842017	17	1/2" (12.7 mm)
842019	19	1/2" (12.7 mm)
842021	21	1/2" (12.7 mm)
842024	24	1/2" (12.7 mm)

Ratchet screwdrivers

Type	Weight kg	Air consumption l/min.	Torque Nm	Speed min. ⁻¹	Operating pressure	Square drive	Sound level db (A)	Air connection
3607	1.25	460	90	170	6 bar	1/2" (12.7 mm)	89	Rp 1/4"
3700	1.6	830	130*	320	6 bar	1/2" (12.7 mm)	92	Rp 1/4"

* max. hand torque 250 Nm



type 3607



type 3700



type 4100

type 4105



type 4500



type 4550



type 4650



type 4784



type 4780-1

Drills with quick action chucks

Type	Weight kg	Air consumption l/min.	Output watts	Speed min. ⁻¹	Operating pressure	Drill Ø mm	Sound level dB (A)	Air connection
Gun drilling machine								
4100	1.0	470	500	2200	6 bar	1 - 10	87	Rp 1/4"
4105*	0.6	440	180	3000	6 bar	1 - 6.5	71	Rp 1/4"
4500	1.2	620	500	2000	6 bar	1 - 10	93	Rp 1/4"
4550	1.4	585	500	800	6 bar	1.5 - 13	92	Rp 1/4"
Angle drilling machine								
4650*	1.1	450	500	1500	6 bar	1 - 10	90	Rp 1/4"

* with crown gear chuck, right-left running

Power wrenches

Type	Weight kg	Air consumption l/min.	Torque Nm	Speed min. ⁻¹	Operating pressure	Actuator-hexagon socket	Sound level db (A)	Air connection
4784	0.9	595	1 - 6	1770	6 bar	1/4" (6.3 mm)	80	Rp 1/4"
4780-1	1.5	395	5 - 25	1200	6 bar	1/4" (6.3 mm)	87	Rp 1/4"

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.