

## Rust converter primers

Type	Packing	Function
ROSTUMWANDLER	400 ml Spray can	Rust converting elastic single part primer for particularly resilient repainting. For iron, aluminium and zinc coated, as well as corrugated iron, concrete and asbestos cement. Can be painted and sprayed over, extremely weather, heat, sea water, oil and petrol resistant.

## Protective wax sprays

Type	Packing	Function
PROTECTSPRAY	400 ml Spray can	Protective wax for all metals and unpainted parts against rust, water, dirt, road salt, etc. The ideal protective film to preserve tools and precision parts. Long-term protection during oversea shipping. Easy to remove using INDUSTRIAL CLEANER.

## PTFE sprays

Type	Packing	Function
PTFESPRAY	400 ml Spray can	Universally used as non-greasy sliding, lubricating and separating agents, e.g. on chutes in the plastics industry. Adheres to all materials, such as glass, rubber, wood, plastics and metal. Temperature stability from -60°C to a max. +260°C. Is water resistant and corrosion-protective at the same time. Ideal for the prevention of creaking and squeaking noises in various material composites. Reduces friction and wear, prevents dust formation. Especially suitable in demoulding processes caused by anti-bonding behaviour, for the coating of seals and O-rings, for lubricating purposes and as anti-bonding material.

## Lubricant spray - transparent with high lubricating ability

Type	Packing	Function
HAFTSCHMIERSPRAY	400 ml Spray can	High pressure adhesive lubricant can be exposed to great loads and reduces wear. Adhesive, non-dripping for quick cycle. High creep and penetrating ability in chain joints, bolts, cable braids, bearing, etc. Reduces the required drive energy by reducing friction value. Corrosion protecting in aggressive environment. Transparent, colourless lubricating technology. Very economical because of high functional safety and secure long-term lubrication.

## Refrigerant sprays

Type	Packing	Function
KALTESPRAY	400 ml Spray can	Quick acting agent for freezing and shrinking metals. To find errors like thermal breaks. Helps prevent heat damage when soldering.

## Compressed air sprays

Type	Packing	Function
DRUCKLUFTSPRAY	400 ml Spray can	Easily removes dust and loose dirt even in areas that are not easily accessible. Sensitive surfaces can be cleaned without any contact.

## Drilling and cutting oil sprays

Type	Packing	Function
SCHNEIDOLSPRAY	400 ml Spray can	Synthetic oil mixture with best corrosion behaviour. Excellent lubrication action with oxidation protection For all drilling and cutting tools and machines operated pneumatically and with compressed-air and tools operated at low temperature ranges. Extraordinary lubricating ability, even with clamped parts. Enables higher tool service life and reduces risk of breakage.

## Silicone spray

Type	Packing	Function
SILIKONSPRAY	400 ml Spray can	Universal lubricating, separating, gliding and impregnating agent for the permanent care and protection of metal, rubber, and plastics. Eliminates squeaks and running noise, is waterproof, weather resistant, anti-static and dust-repellent.

## Welding protection sprays, silicone-free

Type	Packing	Function
SCHWEISSSPRAY	400 ml Spray can	The silicone free separating agent prevents the adhesion of welding spatter, protects nozzles and parts from sticking of weld spatters, and does not affect subsequent painting. Increases the torch service life.



All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.