

## WD-40 multi-purpose oil

Suitable: Silicone- and resin-free multi-purpose oil with 5-fold function. It can be used as a rust remove, lubricant (also in machining), contact spray, corrosion protection and part cleaner.

The number 1 problem solver - proven thousands of times over!

| Туре       | Content Packing                            |
|------------|--|
| WD40-300   | 300 ml Smart-Straw-spray can               |
| WD40-400   | 400 ml Classic spray can                   |
| WD40-500   | 500 ml Smart-Straw-spray can               |
| WD40-5000  | 5 litre Canister (DIN 40)                  |
| WD40-SPRAY | 600 ml Atomizer (empty) for canister goods |



smart-Straw spray can 500 ml

canister

atomizer

## WD-40 specialists

| WD-40 specialisis                    |                  |                        |   |
|--------------------------------------|------------------|------------------------|---|
| Туре                                 | Packing          | Spray can              | Description   |
| Drilling and cutting oil             | 0                | . ,                    | '   |
| WD40 SCHNEIDOL-400                   | 400 ml           | Smart-Straw            | Improves machining processes for all metals, reduces heat generation and reduces wear, extends the service life of cutting tools and drills.  |
| Brake cleaner                        |                  |                        |   |
| WD40 BREMSEN-500                     | 500 ml           | Classic                | Brake cleaner, residue free, works immediately, powerful spray, can be sprayed upside down.   |
| Contact spray                        |                  |                        |   |
| WD40 KONTAKT-100                     | 100 ml           | Classic                | Fast-acting contact spray, removes oil, dirt, flux and oxida-   |
| WD40 KONTAKT-400                     | 400 ml           | Smart-Straw            | tion residue, dries quickly without leaving behind any residue, NSF K2.   |
| White lithium grease spro            | ау               |                        |   |
| WD40 LITHIUM-400                     | 400 ml           | Smart-Straw            | Long-lasting lubrication without dripping or running, reduces friction from metal parts and thus keeps connections open, even under high pressure or at high temperatures, NSF H2. Temperature range: -18°C to max. +145°C  |
| PTFE lubricant spray                 |                  |                        |   |
| WD40 PTFE-400                        | 400 ml           | Smart-Straw            | For use on metal, glass, vinyl, rubber and plastic, extends<br>the service life of tools and devices, reduces friction and<br>wear, long-lasting formula with excellent lubricating proper-<br>ties, NSF H2.<br>Temperature range: -20°C to max. +100°C   |
| PTFE dry lubricant spray             |                  |                        |   |
| WD40 PTFE T-400                      | 400 ml           | Smart-Straw            | Anti-friction PTFE dry lubricating spray, improved lubricating properties at high temperatures and under high pressure, does not attract dust, dirt or oil, is an excellent lubricating and separating agent, NSF H2.  Temperature range: -45°C to max. +260°C  |
| Rust remover                         |                  |                        |   |
| WD40 ROSTLO-100<br>WD40 ROSTLO-400   | 100 ml<br>400 ml | Classic<br>Smart-Straw | Powerful and fast acting, penetrates and separates stuck parts, highly water-repellent, NSF H2.  Temperature range: -20°C to max. +90°C   |
| Lock cylinder spray                  |                  |                        |   |
| WD40 SCHLZYL-100                     | 100 ml           | Classic                | Specifically for servicing all types of lock cylinders. The silicone-free and grease-free formula, as well as the high capillary action, allow the product to seep into the cylinder mechanism and clear blockages without gumming up. It leaves behind a thin lubricating film, which additionally provides protection against corrosion.  Temperature range: -70°C to max. +150°C |
| Silicone spray                       | 100 !            | Cl :                   | F. H. alle e  |
| WD40 SILIKON-100<br>WD40 SILIKON-400 | 100 ml<br>400 ml | Classic<br>Smart-Straw | Excellent lubricating properties, water-repellent, protects against moisture; suited for metals, wood, plastics and rubber, NSF H2.   |
|                                      |                  |                        | Temperature range: -35°C to max. +200°C   |
| Universal cleaner                    | F00 1            | C                      | For one of the first of the   |
| WD40 REINIGER-500                    | 500 ml           | Smart-Straw            | Fast acting, removes grease, oil, dirt and rust, without leav-<br>ing any residues, especially suited to metals, extractor hoods<br>and floor coverings, NSF K1.  |



spray 400 ml





lithium grease spray 400 ml

PTFE lubricant spray 400 ml



lubricant spray 400 ml

rust remover



Oil binding agents & oil binding cloths from page 581



tesa -adhesive technology from page 585





Castors and wheels





lock cylinder

cleaner spray
500 ml 100 ml
All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.

575