

Pneumatic suction devices for liquids

Working pressure: 6 to 8 bar

Application: By actuating the suction device a vacuum is generated in the container. As a result non-inflammable, non-toxic liquids are sucked into the container through the suction hose supplied. It is recommended that the container of the liquid be emptied on reaching its mean level of filling as this would prevent the liquid from flowing out with the vacuum-generating air jet.

Recommendation: The device is ideal for an oil change in the gears, motors and compressors. The oil can easily be sucked out through the oil filler necks. Use petrol or other combustible liquids without dilution!

Type	Container content	Temperature range	Connection
SAUGPB	0.6 l	0°C to max. +50°C	Coupling plug NW 7.2*

* standard coupling



PE canister

Material: HD-PE

Media: Water, many acids, bases, salt solutions and oils. Partially suitable for solvents.

Type	Content	Dimensions (L x W x H)	Shutter/filling opening	HAZMAT licence (UN)
BEH KANISTER 1	1 l	70 x 89 x 214	DIN 25 with a spout	No
BEH KANISTER 2	2 l	109 x 145 x 181	DIN 45	Yes
BEH KANISTER 5	5 l	194 x 168 x 228	DIN 51	Yes
BEH KANISTER 10	10 l	233 x 204 x 324	DIN 51	Yes
BEH KANISTER 20	20 l	290 x 260 x 381	DIN 61	Yes



Drain cocks for plastic canisters

Materials: Body: PE, lever: PP, seal EPE (PE foam)

Type	Thread female	For canister threads male Ø	Thread pitch
KHA DIN45	DIN 45 (Ø internal: 41.0 mm)	44.6	4
KHA DIN51	DIN 51 (Ø internal: 50.2 mm)	54.8	5
KHA DIN61	DIN 61 (Ø internal: 55.6 mm)	60.5	6



Measuring cans and measuring cups

Type	Content
Measuring can (PE, white), with flexible discharge hose, cover, end cap and scale.	
BEH MKANNE 1 PE	1 l
BEH MKANNE 2 PE	2 l
BEH MKANNE 5 PE	5 l
Measuring cup (PP, transparent), scaled, food-safe	
BEH MBECHER 1 PP	1 l
BEH MBECHER 2 PP	2 l
BEH MBECHER 5 PP	5 l



Funnel, polyethylene


Type	Description
TRICHTER 50-120 SET	Set of funnels in Ø 50/75/100/120 mm with retaining tab, fixed discharge
TRICHTER 50-160 SET	Set of funnels in Ø 50/75/100/120/150/160 mm with retaining tab, fixed discharge (Ø 160 mm with removable brass screen)
TRICHTER 160 FLEX	Ø 160 mm funnel, with flexible discharge (330 mm), removable brass screen



Work gloves on page 589



PE canisters + buckets from page 642



Industrial hoses from page 213

Industrial oiler

Description: Industrial oiler with brass double-pump, gravity actuated suction lance and aluminium spray pipe.

Type	Type	Spray pipe length	Content
PE container	metal container		
MSOL 200	MSOL 200 HD	135	200 ml
MSOL 300	MSOL 300 HD	165	300 ml
MSOL 500	MSOL 500 HD	165	500 ml



All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.