



Industrial fabric adhesive tape - tesa®

tesa 🖊

Suitable: Fabric band for bundling, repairing, mounting, strengthening, labelling and much more. Highly weatherproof, water resistant for interior and external use. Tear resistant but can be torn by hand. Easily to label and smooth. The universal tape in the industry with natural rubber adhesive.

Туре	Туре	
19 mm wide	50 mm wide	Colour
25 m Roll length		
TESA G4651 19x25S	TESA G4651 50x25S	Black ●
TESA G4651 19x25W	TESA G4651 50x25W	White 🔘
TESA G4651 19x25B		Blue 🔵
TESA G4651 19x25G	TESA G4651 50x25G	Yellow 🥚
TESA G4651 19x25R		Red ●
50 m Roll length		
TESA G4651 19x50S	TESA G4651 50x50S	Black ●
TESA G4651 19x50W	TESA G4651 50x50W	White 🔘
TESA G4651 19x50B	TESA G4651 50x50B	Blue •
TESA G4651 19x50G	TESA G4651 50x50G	Yellow 🕒
TESA G4651 19x50R	TESA G4651 50x50R	Red ●



Tape band (extra strong)

LOCTITE.

Adhesive tape for repairing, reinforcing, mounting and sealing. Suitable for all applications in plumbing and heading systems as well as automotive and industrial applications.



Advantages: • Can be torn by hand


- Temperature range from -10°C to max. +70°C 100% water resistant
- Pressure resistant up to 4 bar

Type Locite	Type alternative*	Roll length
5080/25		25 m
5080/50	KLBG 50/50 SIL	50 m





Double-sided	adhesive tapes - tesafix®/NOPI tesa					
Туре	Application					
Universal use, roller width: 50 mm, roll length: 25 m						
NOPI FI 5617	Used universally, double-sided adhesive PP glazing tape. For carpets with smooth backs, for universal fixing, decoration and crafting. Adheres to all firm and hard substrates, except PVC, marble, artificial stone. Favourable brand adhesive tape.					
TESA FI 4934	Used universally, double-sided adhesive tape made of a fabric carrier with a high adhesive mass wadding. For carpets, for universal fixing, decoration and crafting. Especially suitable for rough and fibrous substrates.					
Compensating unevenness by foam backing, roller width: 19 mm, roll length: 25 m						
TESA FI 4957	Double-sided adhesive tape consisting of a soft, highly smooth PE foam backing (white) and an acrylic-based adhesive. Ideal for raw subsurfaces. Compensates differential expansions. For adhesion of strips, cable ducts, window bars, bottom rails, plastic hooks etc.					



10

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.