

One-way batteries - coin cells

Type	Description	Dimensions (Ø x height)	Capacity mAh
Silver oxide (voltage: 1.55 Volt)			
BAT 364 AGO	SR 60	6.8 x 2.15	18
BAT 377 AGO	SR 66	6.8 x 2.6	25
BAT 392 AGO	SR 41	7.9 x 3.6	42
BAT 395 AGO	SR 57	9.5 x 2.70	55
BAT 389 AGO	SR 54	11.6 x 3.05	70
BAT 357 AGO	SR 44	11.6 x 5.4	165
Alkaline (voltage: 1.5 Volt)			
BAT 189 AL	LR 54	11.6 x 3.05	44
BAT 186 AL	LR 43	11.6 x 4.2	70
BAT A76 AL	LR 44	11.6 x 5.4	110
BAT 625A AL	LR 9	15.6 x 5.95	190
Lithium (voltage: 3 Volt)			
BAT CR1220 Li	CR1220	12.5 x 2.0	35
BAT CR1616 Li	CR1616	16 x 1.6	42
BAT CR2016 Li	CR2016	20 x 1.6	72
BAT CR2025 Li	CR2025	20 x 2.5	160
BAT CR2032 Li	CR2032	20 x 3.2	220
BAT CR2430 Li	CR2430	24.5 x 3	270

GP Batteries



Charging device for NiMH rechargeable batteries (Micro and Mignon)

Supply volume: Charger for 2 or 4 NiMH rechargeable batteries

Version: Dual LED Load indicator, 2 charging channels for NiMH-batteries

Type	Description	Voltage
BAT LADER 1*	Quick charger for 2 or 4 NiMH rechargeable batteries (AAA/AA)	100-240V AC
BAT LADER 2	Table charger for 2 or 4 NiMH (AAA/AA/C/D/9V)	100-240V AC

* incl. 4 Mignon NiMH batteries (AA)



quick charger

GP Batteries



table charger

Rechargeable torch



- Advantages:**
- Cutting-edge SMD-LED technology
 - Wireless
 - High brightness
 - Charging status display
 - Sturdy, splash resistant housing
 - Holding magnets on back of housing and on bottom of handle

Supply volume: torch incl. USB-A cable

Type	Lumen	Protection class
HANDLAMPE 325	325	IP 54

