

# Castors and wheels



## Transport device castors

50 - 450 kg

**Properties:** Durable solid rubber tyres for light to medium loading. Silent running, protects cargo. Steel sheet housing, zinc-plated, double ball ring and seal in the yoke. Wheels with solid black rubber tyres on steel sheet rims.

**Bearing type:** Roller bearing with thread guard.

Type swivel castors	Type swivel castors w/ total lock	Type fixed castors								
RO 80 TG L	RO 80 TG LF	RO 80 TG B	80	25	105	104x80	72x52	9	34**	50
RO 100 TG L	RO 100 TG LF	RO 100 TG B	100	30	128	104x80	72x52 80x60	9	34**	70
RO 125 TG L	RO 125 TG LF	RO 125 TG B	125	37	155	104x80	72x52 80x60	9	36**	100
RO 140 TG L	RO 140 TG LF	RO 140 TG B	140	37	173	105x80	80x60	9	36**	115
RO 160 TG L	RO 160 TG LF	RO 160 TG B	160	40	195	135x110	105x75 105x80	11	48**	135
RO 180 TG L	RO 180 TG LF	RO 180 TG B	180	45	218	135x110	105x75 105x80	11	48**	170
RO 200 TG L	RO 200 TG LF	RO 200 TG B	200	50	235	135x110	105x75 105x80	11	55**	205
RO 225 TG L*	RO 225 TG LF*	RO 225 TG B*	225	55	257	135x110	105x75 105x80	11	61**	250
RO 250 TG L*	RO 250 TG LF*	RO 250 TG B*	250	60	290	135x110	105x75 105x80	11	66**	295
RO 280 TG L*	RO 280 TG LF*	RO 280 TG B*	280	70	325	186x170	140x105	14.5	80**	385
RO 400 TG L*	RO 400 TG LF*	RO 400 TG B*	400	75	458	150x150	125x125	11	82**	450

\* no thread guard \*\* does not apply to type fixed castor \*\*\* 175x140 for type fixed castor

## Transport device castors - wheels

50 - 475 kg

**Properties:** Durable solid rubber tyres on rims of zinc-plated steel sheet, for light to medium loading. Silent running, protects cargo.

**Bearing type:** Roller bearing

Type					
RO 80 TG	80	25	12	40	50
RO 100 TG	100	30	12	40	70
RO 125 TG	125	37	15	50	100
RO 140 TG	140	37	15	50	115
RO 160 TG	160	40	20	60	135
RO 180 TG	180	45	20	59	170
RO 181 TG	180	80	20	75	200
RO 200 TG	200	50	20	60	205
RO 225 TG	225	55	20	60	250
RO 250 TG	250	60	25	75	295
RO 260 TG*	260	85	20	75	200
RO 280 TG	280	70	30	75	385
RO 380 TG*	380	80	25	75	350
RO 400 TG	400	75	25	75	475

\* convex running surface

## Elastic solid rubber castors

100 - 350 kg

**Properties:** High elasticity, great driving comfort, firm tyre seating and low roll resistance characterises these rollers. Steel sheet housing, zinc-plated, double ball ring in yoke, wheels with blue elastic solid rubber tyre, free of grooves, plastic wheel body, up to Ø 125 a thread guard is included in the delivery.

**Bearing type:** Roller bearing

Type swivel castors	Type swivel castors w/ total lock	Type fixed castors								
RO 80 VG L	RO 80 VG LF	RO 80 VG B	80	35	105	104x80	80x60	9	34*	100
RO 100 VG L	RO 100 VG LF	RO 100 VG B	100	36	128	104x80	80x60	9	34*	130
RO 125 VG L	RO 125 VG LF	RO 125 VG B	125	36	155	104x80	80x60	9	36*	160
RO 160 VG L	RO 160 VG LF	RO 160 VG B	160	50	195	135x110	105x75 105x80	11	48*	300
RO 200 VG L	RO 200 VG LF	RO 200 VG B	200	50	235	135x110	105x75 105x80	11	55*	350

\* does not apply to type fixed castor

## Elastic solid rubber castors - wheels

100 - 350 kg

**Properties:** Elastic-solid rubber tyres, blue, no tracks, on a plastic wheel body, lower roll resistance.

**Bearing type:** Roller bearing

Type					
RO 80 VG	80	35	12	40	100
RO 100 VG	100	36	12	40	130
RO 125 VG	125	36	15	50	160
RO 160 VG	160	50	20	60	300
RO 200 VG	200	50	20	60	350

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.