




Button head tapping screws with cross recesses

DIN 7981 C/ISO 7049



Ordering example of other diameters and lengths: 7981C-**x***



Type steel hardened & zinc-plated	Type stainless steel A2 ^{INOX}	d	l
d=2.9; dk=5.6; k(max)=2.2; cross recess=1 (PH 1)			
7981C-2,9x6,5	7981C-2,9x6,5 ES	2.9	6.5
7981C-2,9x9,5	7981C-2,9x9,5 ES	2.9	9.5
7981C-2,9x13	7981C-2,9x13 ES	2.9	13
7981C-2,9x16	7981C-2,9x16 ES	2.9	16
7981C-2,9x19	7981C-2,9x19 ES	2.9	19
7981C-2,9x22	7981C-2,9x22 ES	2.9	22
7981C-2,9x25	7981C-2,9x25 ES	2.9	25
d=3.5; dk=6.9; k(max)=2.6; cross recess=2 (PH 2)			
7981C-3,5x6,5	7981C-3,5x6,5 ES	3.5	6.5
7981C-3,5x9,5	7981C-3,5x9,5 ES	3.5	9.5
7981C-3,5x13	7981C-3,5x13 ES	3.5	13
7981C-3,5x16	7981C-3,5x16 ES	3.5	16
7981C-3,5x19	7981C-3,5x19 ES	3.5	19
7981C-3,5x22	7981C-3,5x22 ES	3.5	22
7981C-3,5x25	7981C-3,5x25 ES	3.5	25
7981C-3,5x32	7981C-3,5x32 ES	3.5	32
7981C-3,5x38	---	3.5	38
d=3.9; dk=7.5; k(max)=2.8; cross recess=2 (PH 2)			
7981C-3,9x9,5	7981C-3,9x9,5 ES	3.9	9.5
7981C-3,9x13	7981C-3,9x13 ES	3.9	13
7981C-3,9x16	7981C-3,9x16 ES	3.9	16
7981C-3,9x19	7981C-3,9x19 ES	3.9	19
7981C-3,9x22	7981C-3,9x22 ES	3.9	22
7981C-3,9x25	7981C-3,9x25 ES	3.9	25
7981C-3,9x32	7981C-3,9x32 ES	3.9	32
7981C-3,9x38	7981C-3,9x38 ES	3.9	38
7981C-3,9x45	7981C-3,9x45 ES	3.9	45
7981C-3,9x50	7981C-3,9x50 ES	3.9	50
d=4.2; dk=8.2; k(max)=3.05; cross recess=2 (PH 2)			
7981C-4,2x9,5	7981C-4,2x9,5 ES	4.2	9.5
7981C-4,2x13	7981C-4,2x13 ES	4.2	13
7981C-4,2x16	7981C-4,2x16 ES	4.2	16
7981C-4,2x19	7981C-4,2x19 ES	4.2	19
7981C-4,2x22	7981C-4,2x22 ES	4.2	22
7981C-4,2x25	7981C-4,2x25 ES	4.2	25
7981C-4,2x32	7981C-4,2x32 ES	4.2	32
7981C-4,2x38	7981C-4,2x38 ES	4.2	38
7981C-4,2x45	7981C-4,2x45 ES	4.2	45
7981C-4,2x50	7981C-4,2x50 ES	4.2	50
7981C-4,2x60	7981C-4,2x60 ES	4.2	60
7981C-4,2x70	7981C-4,2x70 ES	4.2	70

Type steel hardened & zinc-plated	Type stainless steel A2 ^{INOX}	d	l
d=4.8; dk=9.5; k(max)=3.55; cross recess=2 (PH 2)			
7981C-4,8x9,5	7981C-4,8x9,5 ES	4.8	9.5
7981C-4,8x13	7981C-4,8x13 ES	4.8	13
7981C-4,8x16	7981C-4,8x16 ES	4.8	16
7981C-4,8x19	7981C-4,8x19 ES	4.8	19
7981C-4,8x22	7981C-4,8x22 ES	4.8	22
7981C-4,8x25	7981C-4,8x25 ES	4.8	25
7981C-4,8x32	7981C-4,8x32 ES	4.8	32
7981C-4,8x38	7981C-4,8x38 ES	4.8	38
7981C-4,8x45	7981C-4,8x45 ES	4.8	45
7981C-4,8x50	7981C-4,8x50 ES	4.8	50
7981C-4,8x60	7981C-4,8x60 ES	4.8	60
7981C-4,8x70	7981C-4,8x70 ES	4.8	70
7981C-4,8x80	7981C-4,8x80 ES	4.8	80
d=5.5; dk=10.8; k(max)=3.95; cross recess=3 (PH 3)			
7981C-5,5x13	7981C-5,5x13 ES	5.5	13
7981C-5,5x16	7981C-5,5x16 ES	5.5	16
7981C-5,5x19	7981C-5,5x19 ES	5.5	19
7981C-5,5x22	7981C-5,5x22 ES	5.5	22
7981C-5,5x25	7981C-5,5x25 ES	5.5	25
7981C-5,5x32	7981C-5,5x32 ES	5.5	32
7981C-5,5x38	7981C-5,5x38 ES	5.5	38
7981C-5,5x45	7981C-5,5x45 ES	5.5	45
7981C-5,5x50	7981C-5,5x50 ES	5.5	50
7981C-5,5x60	7981C-5,5x60 ES	5.5	60
7981C-5,5x70	7981C-5,5x70 ES	5.5	70
7981C-5,5x80	7981C-5,5x80 ES	5.5	80
d=6.3; dk=12.5; k(max)=4.55; cross recess=3 (PH 3)			
7981C-6,3x13	7981C-6,3x13 ES	6.3	13
7981C-6,3x16	7981C-6,3x16 ES	6.3	16
7981C-6,3x19	7981C-6,3x19 ES	6.3	19
7981C-6,3x22	7981C-6,3x22 ES	6.3	22
7981C-6,3x25	7981C-6,3x25 ES	6.3	25
7981C-6,3x32	7981C-6,3x32 ES	6.3	32
7981C-6,3x38	7981C-6,3x38 ES	6.3	38
7981C-6,3x45	7981C-6,3x45 ES	6.3	45
7981C-6,3x50	7981C-6,3x50 ES	6.3	50
7981C-6,3x60	7981C-6,3x60 ES	6.3	60
7981C-6,3x70	7981C-6,3x70 ES	6.3	70

Multibox button head tapping screws DIN 7981C

Description: This multi-box contains 1450 button head tapping screws, 2.9 to 4.8 mm, in zinc-plated steel.

Advantages: For ease of transport and clear arrangement, up to 4 of these multi-boxes can be stowed in the practical multi-box container type MULTIBOX P 1 C.

Info: Tapping screws can be found on page 626

Type	Content
MULTIBOX 7981C	100 screws DIN 7981C 2.9 mm (9.5 mm)
	300 screws DIN 7981C 3.5 mm (13 - 16 - 19 mm)
	350 screws DIN 7981C 3.9 mm (9.5 - 13 - 16 - 19 mm)
	400 screws DIN 7981C 4.2 mm (9.5 - 13 - 16 - 19 - 25 mm)
	300 screws DIN 7981C 4.8 mm (13 - 16 - 19 - 22 - 32 mm)

Multibox button head drilling screws DIN 7504M

Description: This multi-box contains 900 button head drilling screws, 3.5 to 4.8 mm, in zinc-plated steel.

Advantages: For ease of transport and clear arrangement, up to 4 of these multi-boxes can be stowed in the practical multi-box container type MULTIBOX P 1 C.

Info: Drilling screws can be found on page 629

Type	Content
MULTIBOX 7504M	200 screws DIN 7504M 3.5 mm (9.5 - 13 - 16 - 19 mm)
	200 screws DIN 7504M 3.9 mm (13 - 16 - 19 - 25 mm)
	250 screws DIN 7504M 4.2 mm (13 - 16 - 19 - 22 - 25 mm)
	250 screws DIN 7504M 4.8 mm (13 - 16 - 19 - 22 - 25 mm)

