

Hose connector

1



Hose connection tubes made of plastic

PN 8

Temperature range: POM*: 0°C to max. +80°C, PVDF: -40°C to max. +140°C

Type POM*	Type PVDF	Previous item no.	Hose Ø internal	Type POM* reducing	Previous item no.	D1	D2
SVR 3 K	---	---	3	SVR 4/3 K	---	4	3
SVR 4 K	SVR 4 PVDF	---	4	SVR 6/4 K	---	6	4
SVR 5 K	---	---	5	SVR 8/4 K	SVR 9/4 K	8	4
SVR 6 K	SVR 6 PVDF	---	6	SVR 8/6 K	SVR 9/6 K	8	6
SVR 8 K	---	SVR 9 K	8	SVR 9/4 K	---	9	4
SVR 9 K	SVR 9 PVDF	---	9	SVR 9/6 K	---	9	6
SVR 10 K	SVR 10 PVDF	---	10	SVR 10/6 K	---	10	6
SVR 12 K	---	SVR 13 K	12	SVR 10/8 K	SVR 10/9 K	10	8
SVR 13 K	SVR 13 PVDF	---	13	SVR 10/9 K	---	10	9
SVR 16 K	---	---	16	SVR 12/8 K	SVR 13/9 K	12	8
SVR 19 K	---	---	19	SVR 13/9 K	---	13	9
SVR 25 K	---	---	25	SVR 12/10 K	SVR 13/10 K	12	10
				SVR 13/10 K	---	13	10

* resistance against hydrocarbons, petrol, diesel, oils, fats, chlorinated hydrocarbons, alkalis and salt solutions (neutral).
Not resistant to acids, oxidisers, phenols, glycerine and glycol.



Universal hose connection tubes made of plastic

PN 8

Temperature range: 0°C to max. +80°C



Type polypropylene	Hose Ø internal	Type polypropylene reducing	Hose 1 Ø internal	Hose 2 Ø internal
SVR 35 PP	3 to 5	SVR 81048 PP	8 to 10	4 to 8
SVR 57 PP	5 to 7	SVR 121648 PP	12 to 16	4 to 8
SVR 710 PP	7 to 10	SVR 1216812 PP	12 to 16	8 to 12
SVR 912 PP	9 to 12			
SVR 1114 PP	11 to 14			
SVR 1315 PP	13 to 15			



Angle hose connectors made of plastic

PN 8

Temperature range: POM*: 0°C to max. +80°C, PVDF: -40°C to max. +140°C

Type POM*	Type PVDF	Previous item no.	Hose Ø internal	Type POM*	Type PVDF	Previous item no.	Hose Ø internal
W 3 K	---	---	3	W 10 K	W 10 PVDF	---	10
W 4 K	W 4 PVDF	---	4	W 12 K	---	W 13 K	12
W 5 K	---	---	5	W 13 K	W 13 PVDF	---	13
W 6 K	W 6 PVDF	---	6	W 16 K	---	---	16
W 8 K	---	W 9 K	8	W 19 K	---	---	19
W 9 K	W 9 PVDF	---	9	W 25 K	---	---	25

* resistance against hydrocarbons, petrol, diesel, oils, fats, chlorinated hydrocarbons, alkalis and salt solutions (neutral).
Not resistant to acids, oxidisers, phenols, glycerine and glycol.



T-hose connectors made of plastic

PN 8

Temperature range: POM*: 0°C to max. +80°C, PVDF: -40°C to max. +140°C

Type POM*	Type PVDF	Previous item no.	Hose Ø internal	Type POM*	Type PVDF	Previous item no.	Hose Ø internal
T 3 K	---	---	3	T 10 K	T 10 PVDF	---	10
T 4 K	T 4 PVDF	---	4	T 12 K	---	T 13 K	12
T 5 K	---	---	5	T 13 K	T 13 PVDF	---	13
T 6 K	T 6 PVDF	---	6	T 16 K	---	---	16
T 8 K	---	T 9 K	8	T 19 K	---	---	19
T 9 K	T 9 PVDF	---	9	T 25 K	---	---	25

* resistance against hydrocarbons, petrol, diesel, oils, fats, chlorinated hydrocarbons, alkalis and salt solutions (neutral).
Not resistant to acids, oxidisers, phenols, glycerine and glycol.



T-hose connectors made of brass

PN 16

Type	Hose Ø internal	Type	Hose Ø internal
T 5 MS	5	T 13 MS	13
T 6 MS	6	T 16 MS	16
T 8 MS	8	T 19 MS	19
T 9 MS	9	T 25 MS	25

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.