


Particle board half-round head screws (pan head) with TORX drives **fischer**



Type zinc-plated steel, white	d	l
d=3; TORX size=T 10(ISZ 10)		
SPAN 3x12 HR TX	3	12
SPAN 3x16 HR TX	3	16
SPAN 3x20 HR TX	3	20
SPAN 3x25 HR TX	3	25
SPAN 3x30 HR TX	3	30
d=3.5; TORX size=T 15(ISZ 15)		
SPAN 3.5x12 HR TX	3.5	12
SPAN 3.5x16 HR TX	3.5	16
SPAN 3.5x20 HR TX	3.5	20
SPAN 3.5x25 HR TX	3.5	25
SPAN 3.5x30 HR TX	3.5	30
SPAN 3.5x35 HR TX	3.5	35
d=4; TORX size=T 20(ISZ 20)		
SPAN 4x16 HR TX	4	16
SPAN 4x20 HR TX	4	20
SPAN 4x25 HR TX	4	25
SPAN 4x30 HR TX	4	30
SPAN 4x35 HR TX	4	35
SPAN 4x40 HR TX	4	40
SPAN 4x45 HR TX	4	45
SPAN 4x50 HR TX	4	50

Type zinc-plated steel, white	d	l
d=4.5; TORX size=T 20(ISZ 20)		
SPAN 4.5x16 HR TX	4.5	16
SPAN 4.5x20 HR TX	4.5	20
SPAN 4.5x25 HR TX	4.5	25
SPAN 4.5x30 HR TX	4.5	30
SPAN 4.5x35 HR TX	4.5	35
SPAN 4.5x40 HR TX	4.5	40
SPAN 4.5x45 HR TX	4.5	45
SPAN 4.5x50 HR TX	4.5	50
d=5; TORX size=T 20(ISZ 20)		
SPAN 5x20 HR TX	5	20
SPAN 5x25 HR TX	5	25
SPAN 5x30 HR TX	5	30
SPAN 5x35 HR TX	5	35
SPAN 5x40 HR TX	5	40
SPAN 5x50 HR TX	5	50
SPAN 5x60 HR TX	5	60
SPAN 5x70 HR TX	5	70
SPAN 5x80 HR TX	5	80



Nails/wire pins with countersunk head shape B

DIN EN 10230-1 (DIN 1151)

Description: Steel wire nails for general use in the construction industry (grade level 2). Not suited for mechanical nailing.
Supply volume: 1 piece corresponds to one carton with the specified fill weight

Type plain steel	Type steel hot-dip galvanised	Ø D	L	Fill weight *
1151-1.8x35	1151-1.8x35 V	1.8	35	2.5 kg (approx. 3289 pcs.)
1151-2.0x40	1151-2.0x40 V	2.0	40	2.5 kg (approx. 2500 pcs.)
1151-2.2x45	---	2.2	45	2.5 kg (approx. 1923 pcs.)
1151-2.2x50	1151-2.2x50 V	2.2	50	2.5 kg (approx. 1563 pcs.)
1151-2.5x55	---	2.5	55	2.5 kg (approx. 1087 pcs.)
1151-2.5x60	1151-2.5x60 V	2.5	60	2.5 kg (approx. 1000 pcs.)
1151-2.8x65	1151-2.8x65 V	2.8	65	2.5 kg (approx. 781 pcs.)
1151-3.1x65	---	3.1	65	2.5 kg (approx. 625 pcs.)
1151-3.1x70	1151-3.1x70 V	3.1	70	2.5 kg (approx. 581 pcs.)
1151-3.1x80	1151-3.1x80 V	3.1	80	2.5 kg (approx. 510 pcs.)
1151-3.4x80	---	3.4	80	2.5 kg (approx. 431 pcs.)
1151-3.4x90	1151-3.4x90 V	3.4	90	5.0 kg (approx. 746 pcs.)
1151-3.8x100	1151-3.8x100 V	3.8	100	5.0 kg (approx. 531 pcs.)
1151-4.2x100	---	4.2	100	5.0 kg (approx. 443 pcs.)
1151-4.2x110	---	4.2	110	5.0 kg (approx. 403 pcs.)
1151-4.2x120	1151-4.2x120 V	4.2	120	5.0 kg (approx. 370 pcs.)
1151-4.6x130	1151-4.6x130 V	4.6	130	5.0 kg (approx. 282 pcs.)
1151-5.5x140	---	5.5	140	5.0 kg (approx. 186 pc.)
1151-5.5x145	1151-5.5x145 V	5.5	145	5.0 kg (approx. 184 pcs.)
1151-5.5x160	1151-5.5x160 V	5.5	160	5.0 kg (approx. 137 pcs.)
1151-6.0x180	1151-6.0x180 V	6.0	180	5.0 kg (approx. 117 pcs.)
1151-7.0x210	1151-7.0x210 V	7.0	210	5.0 kg (approx. 74 pcs.)
1151-7.6x230	1151-7.6x230 V	7.6	230	5.0 kg (approx. 58 pcs.)
1151-7.6x260	1151-7.6x260 V	7.6	260	5.0 kg (approx. 51 pcs.)
1151-8.8x260	1151-8.8x260 V	8.8	260	5.0 kg (approx. 38 pcs.)
1151-8.8x290	1151-8.8x290 V	8.8	290	5.0 kg (approx. 33 pcs.)
1151-9.4x310	---	9.4	310	5.0 kg (approx. 29 pcs.)



* details in brackets apply to type plain steel. The quantities are slightly lower for the type steel hot-dip galvanised.



type plain steel



type steel, hot-dip galvanised



Diagonal cutters/combiner pliers can be found in the Online Shop



Manual tools can be found in the Online Shop



Knives on page 595



Blast guns and blasting abrasives on page 535

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.