

Dowel assortments

fischer

Type	Dowel types	Content
DUBEL SORTI SX	SX and UX dowels	60 pcs. SX 6x30 – 50 pcs. SX 8x40 – 20 pcs. SX 10x50 – 60 pcs. UX 5x30 R – 40 pcs. UX 6x50 R – 50 pcs. UX 8x50 R – 10 pcs. UX 10x60 R
DUBEL SORTI S6	S dowel	100 pcs. S 6 – 100 pcs. S 8 – 25 pcs. S 10

MADE
IN
GERMANY



type DUBEL SORTI SX

type DUBEL SORTI S6

FIXtainer boxes (assortment and empty boxes)

fischer

Description: Fixtainer boxes are equipped with carrier handles, transparent covers and removable dividers. FIXtainers can be securely attached to and stacked on top of one another using the click system. They are compatible with the Sortimo L-Boxx system.

Type	Description
FISCHER FIX BOX	Empty box without contents: can be used as a storage box for packed lunches, collection box for small parts, utensils, tools, toys, etc.
FISCHER FIX SX	"SX dowel box": 120 pcs. dowel SX 6x30 – 60 pcs. dowel SX 8x40 – 30 pcs. dowel SX 10x50
FISCHER FIX SXS	"SX dowel and screw box": 60 pcs. dowels SX 6x30 and countersunk head screws 4.5x40 – 30 pcs. dowels SX 8x40 and countersunk head screws 5x60 – 15 pcs. dowels SX 10x50 and countersunk head screws 6x85
FISCHER FIX UNI 1	"All-in-one box": 50 SX 6x30 dowels and 4.5x40 countersunk head screws - 50 UX 6x35 R universal dowels 4.5x60 countersunk head screws - 25 GK plasterboard dowels incl. screw-in tool - 15 GKM metal plasterboard dowels

MADE
IN
GERMANY



type FISCHER
FIX BOX

type FISCHER
FIX SX

type FISCHER
FIX SXS

type FISCHER
FIX UNI 1


Liquid fixing - the problem solver

fischer

Application: Solvent free polyurethane based injection compound. It is injected into a hole, expands there into the defined volume and cures at room temperature in around 2 to 5 minutes. It is suitable for anchoring fixing elements, to fill and repair broken boreholes or as a repair compound for wood based materials. You can screw screws and eyelets etc. of diameters between 2 to 6 mm into and out of the hardened compound, just as you can with wood. Temperature resistant from -10°C to max. +40°C. Ideal for renovation work and wood repairs, compatible with all building materials (new and old).

Type	Description
DUBEL FILLFIX	Complete set sufficient for min. 4 boreholes Ø 10 mm and 50 mm deep consisting of: 1 x resealable cartridge (25 ml injection compound) 2 x mix nozzles 2 x extension tube (for filling small and deep holes) 4 x injection anchor sleeves (for perforated or board materials)

MADE
IN
GERMANY



FMD dowel metal expansion bolts

fischer

Application: Concrete and solid brick wall materials, honeycomb brick, aerated concrete. Meets the technical regulation for gas pipes. Dowels must be placed flush into the carrying underground.

Screws that can be used: Wood or chipboard screws

Type	Drill Ø ¹⁾	Min. hole depth	Screws Ø	Amount
DUBEL FMD6x32	6-7	38	5-6	100 packs
DUBEL FMD8x38	10	46	6-8	100 packs
DUBEL FMD8x60	10-12	68	6-8	50 packs

¹⁾ the drill Ø must be matched to the building material burst strength. The higher the burst strength, the bigger the drill Ø

