

Shipping packages/buckets/padlocks

Bubble wrap

■ Scaled Air

Advantage: The only bubble wrap with a special long-term sealing of the bubbles. A barrier layer of polyamide minimizes air loss from the bubbles, so that even after long-term storage, optimum product protection is still

| Туре | Format | Packing unit | | | | | | |
|--|--------------------------|--------------|--|--|--|--|--|--|
| Roller goods AirCap® (barrier layer bubble wrap) | | | | | | | | |
| LUPO 50x100 | 50 cm x 100 m | 3 pcs | | | | | | |
| LUPO 75x100 | 75 cm x 100 m | 2 pcs | | | | | | |
| LUPO 100x100 | 100 cm x 100 m | 1 pcs | | | | | | |
| Dispenser box BUBBLE PAK® | | | | | | | | |
| LUPO BOX | 30 cm x 50 m | 1 pcs | | | | | | |
| | (perforated every 50 cm) | | | | | | | |



Bucket

| Туре | Volume | Version |
|-----------------|--------|--|
| BEH EIMER 12 PE | 12 | Made of high-quality PE recycled material, zinc-plated metal bracket and |
| BEH EIMER 20 PE | 20 | litre scale, TÜV/GS tested |
| BEH EIMER 12 ST | 12 l | Made of zinc-plated steel sheet, zinc-plated bracket |



Cylinder padlocks

Materials: Housing: Brass, bracket: Steel (hardened), internal parts: Steel

Supply volume: Cylinder padlock with 2 keys

Optional: Simultaneous locking* with closure A -GSA, simultaneous locking* with closure B -GSB

| | • | | | - | | | - | _ | | |
|---|------------------|----|----|--------------|----|----|----|----|---------------------|-----|
| | Type standard | | | Туре | 10 | | | | | |
| | standard | В | C | high bracket | 1 | В | C | S | Bracket thickness Ø | i A |
| | VHS 20 | 12 | 7 | VHS 20 H | | 24 | 20 | 20 | 3.5 | 10 |
| ľ | VHS 30 | 17 | 10 | VHS 30 H | | 40 | 32 | 30 | 5.0 | 16 |
| ľ | VHS 40 | 24 | 15 | VHS 40 H | | 63 | 53 | 40 | 6.0 | 23 |
| ľ | VHS 50 | 30 | 18 | | | | | 50 | 8.0 | 29 |
| ľ | VHS 60 | 36 | 20 | | | | | 60 | 10.0 | 36 |

* every lock with the same item number can be opened with the same key.

Order example: VHS 20- ** Standard type

Designation for the options: Simultaneous locking with closure A . .-GSA Simultaneous locking with closure B . .-GSB















Funnel and measuring cans on page 576

All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refers, if not otherwise indicated, to liquids of Group II at +20°C

10