

Threaded nozzles with conical threads

up to 16 bar

Type 16 bar brass nickel-plated	Type 16 bar AISI 316	Type 8 bar plastic PA 6	Thread	Hose Ø internal	SW ⁽¹⁾
---	---	GT 53 K	M 5	3	---
---	---	GT 184 K	R 1/8"	4	---
GT 186 K MSV	---	GT 186 K	R 1/8"	6	12
GT 188 K MSV	---	---	R 1/8"	8	12
GT 189 K MSV	---	GT 189 K	R 1/8"	9	12
GT 1810 K MSV	---	---	R 1/8"	10	12
---	---	GT 144 K	R 1/4"	4	---
GT 145 K MSV	---	GT 145 K	R 1/4"	5	14
GT 146 K MSV	---	GT 146 K	R 1/4"	6	14
GT 148 K MSV	---	---	R 1/4"	8	14
GT 149 K MSV	GT 149 K ES*	GT 149 K	R 1/4"	9	14
GT 1410 K MSV	---	GT 1410 K	R 1/4"	10	14
GT 1412 K MSV	---	---	R 1/4"	12	14
---	---	GT 386 K	R 3/8"	6	---
GT 389 K MSV	GT 389 K ES*	GT 389 K	R 3/8"	9	17
GT 3810 K MSV	---	GT 3810 K	R 3/8"	10	17
GT 3812 K MSV	---	---	R 3/8"	12	17
GT 3813 K MSV	GT 3813 K ES*	GT 3813 K	R 3/8"	13	17
GT 3816 K MSV	---	---	R 3/8"	16	17
GT 129 K MSV	---	GT 129 K	R 1/2"	9	22
GT 1210 K MSV	---	---	R 1/2"	10	22
GT 1212 K MSV	---	---	R 1/2"	12	22
GT 1213 K MSV	GT 1213 K ES*	GT 1213 K	R 1/2"	13	22
GT 1216 K MSV	---	GT 1216 K	R 1/2"	16	22
GT 1219 K MSV	GT 1219 K ES*	---	R 1/2"	19	22
---	---	GT 3416 K	R 3/4"	16	---
---	GT 3419 K ES*	GT 3419 K	R 3/4"	19	---
---	GT 1025 K ES*	GT 1025 K	R 1"	25	---
---	GT 11432 K ES*	---	R 1 1/4"	32	---
---	GT 11238 K ES*	---	R 1 1/2"	38	---
---	GT 2050 K ES*	---	R 2"	50	---
---	GT 21260 K ES	---	R 2 1/2"	60	---
---	GT 3075 K ES	---	R 3"	75	---

⁽¹⁾ Details apply for the brass type. For all other types, please ask. * optional: NPT thread -NPT

Order example: GT 149 K ES **

Standard type

Designation for the options:

NPT thread-NPT




Dairy fittings are found in the Online Shop

Compressed air and water hoses from page 208

LOCTITE Liquid seals, gaskets & tapes from page 549

Threaded nozzles PVC-U (for plastic threads only)

PN 10



Warning: Not suitable for compressed air or other gases under pressure!

Type	Thread	Hose Ø internal	Installation length
GT 1412 PVC	Rp 1/4"	12	52
GT 3816 PVC	Rp 3/8"	16	54
GT 1220 PVC	Rp 1/2"	20	60
GT 3425 PVC	Rp 3/4"	25	67
GT 1032 PVC	Rp 1"	32	80
GT 11440 PVC	Rp 1 1/4"	40	84
GT 11240 PVC	Rp 1 1/2"	40	89
GT 11250 PVC	Rp 1 1/2"	50	99
GT 2060 PVC	Rp 2"	60	100



Threaded nozzles with cylindrical left-hand threads - internal cone

PN 16

Type brass	Thread	Hose Ø internal	SW
GT 146 MS LH	G 1/4" LH	6	17
GT 386 MS LH	G 3/8" LH	6	19
GT 389 MS LH	G 3/8" LH	9	19



Threaded nozzles with metric threads

PN 16

Type brass	Thread	Hose Ø internal	SW
GT M86 MS	M 8 x 0.75	6	11
GT M89 MS	M 8 x 0.75	9	11
GT M109 MS	M 10 x 1	9	11
GT M1213 MS	M 12 x 1.5	13	15
GT M1413 MS	M 14 x 1.5	13	15
GT M1613 MS	M 16 x 1.5	13	17
GT M2419 MS	M 24 x 1.5	19	27



All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.