


Steel & stainless steel cutting ring fittings ISO 8434-1

T-screw connections with reduced outlet


Type zinc-plated steel	Type AISI 316Ti	Tube Ø 1 external	Tube Ø 2 external	Tube Ø 3 external
Light model series				
---	TR 6/10/6 LES	6 L	10 L	6 L
TR 8/6/8 L	TR 8/6/8 L ES	8 L	6 L	8 L
TR 8/8/6 L	---	8 L	8 L	6 L
TR 8/10/8 L	TR 8/10/8 L ES	8 L	10 L	8 L
TR 10/6/10 L	TR 10/6/10 L ES	10 L	6 L	10 L
TR 10/8/10 L	TR 10/8/10 L ES	10 L	8 L	10 L
---	TR 10/10/8 L ES	10 L	10 L	8 L
TR 12/8/12 L	TR 12/8/12 L ES	12 L	8 L	12 L
TR 12/10/10 L	TR 12/10/10 L ES	12 L	10 L	10 L
TR 12/10/12 L	TR 12/10/12 L ES	12 L	10 L	12 L
---	TR 12/12/10 L ES	12 L	12 L	10 L
TR 12/18/12 L	TR 12/18/12 L ES	12 L	18 L	12 L
TR 15/8/15 L	TR 15/8/15 L ES	15 L	8 L	15 L
TR 15/10/15 L	TR 15/10/15 L ES	15 L	10 L	15 L
TR 15/12/15 L	TR 15/12/15 L ES	15 L	12 L	15 L
TR 18/15/18 L	TR 18/15/18 L ES	18 L	15 L	18 L
TR 22/10/22 L	TR 22/10/22 L ES	22 L	10 L	22 L
TR 22/12/22 L	TR 22/12/22 L ES	22 L	12 L	22 L
TR 22/15/22 L	TR 22/15/22 L ES	22 L	15 L	22 L
TR 22/18/22 L	TR 22/18/22 L ES	22 L	18 L	22 L
TR 28/12/28 L	TR 28/12/28 L ES	28 L	12 L	28 L
TR 28/15/28 L	TR 28/15/28 L ES	28 L	15 L	28 L
TR 28/22/28 L	TR 28/22/28 L ES	28 L	22 L	28 L
Heavy model series				
TR 12/10/12 S	TR 12/10/12 S ES	12 S	10 S	12 S
TR 16/12/16 S	TR 16/12/16 S ES	16 S	12 S	16 S
TR 25/16/25 S	TR 25/16/25 S ES	25 S	16 S	25 S
TR 25/20/25 S	TR 25/20/25 S ES	25 S	20 S	25 S



TIP More reducers on request!

Adjustable 45° L-screwed connections with sealing cone and O-ring


Type zinc-plated steel	Type AISI 316Ti	Type compr. ring AISI 316Ti (NC)	Tube Ø external	Union nut thread
Light model series				
EL 6 L	EL 6 L ES	EL 6 L NC	6 L	M 12 x 1.5
EL 8 L	EL 8 L ES	EL 8 L NC	8 L	M 14 x 1.5
EL 10 L	EL 10 L ES	EL 10 L NC	10 L	M 16 x 1.5
EL 12 L	EL 12 L ES	EL 12 L NC	12 L	M 18 x 1.5
EL 15 L	EL 15 L ES	EL 15 L NC	15 L	M 22 x 1.5
EL 18 L	EL 18 L ES	EL 18 L NC	18 L	M 26 x 1.5
EL 22 L	EL 22 L ES	EL 22 L NC	22 L	M 30 x 2
EL 28 L	EL 28 L ES	---	28 L	M 36 x 2
EL 35 L	EL 35 L ES	---	35 L	M 45 x 2
EL 42 L	EL 42 L ES	---	42 L	M 52 x 2
Heavy model series				
EL 6 S	EL 6 S ES	EL 6 S NC	6 S	M 14 x 1.5
EL 8 S	EL 8 S ES	EL 8 S NC	8 S	M 16 x 1.5
EL 10 S	EL 10 S ES	EL 10 S NC	10 S	M 18 x 1.5
EL 12 S	EL 12 S ES	EL 12 S NC	12 S	M 20 x 1.5
EL 14 S	EL 14 S ES	EL 14 S NC	14 S	M 22 x 1.5
EL 16 S	EL 16 S ES	EL 16 S NC	16 S	M 24 x 1.5
EL 20 S	EL 20 S ES	EL 20 S NC	20 S	M 30 x 2
EL 25 S	EL 25 S ES	EL 25 S NC	25 S	M 36 x 2
EL 30 S	EL 30 S ES	---	30 S	M 42 x 2
EL 38 S	EL 38 S ES	---	38 S	M 52 x 2



O-rings for sealing cone screw connections and welding nipple

Temperature range: NBR: -20°C to max. +80°C, FKM: -20°C to max. +200°C

Type NBR	Type FKM	For pipe screw connection	Type NBR	Type FKM	For pipe screw connection
ORING 6 P	ORING 6 V	6 L / 6 S	ORING 20 P	ORING 20 V	20 S
ORING 8 P	ORING 8 V	8 L / 8 S	ORING 22 P	ORING 22 V	22 L
ORING 10 P	ORING 10 V	10 L / 10 S	ORING 25 P	ORING 25 V	25 S
ORING 12 P	ORING 12 V	12 L / 12 S	ORING 28 P	ORING 28 V	28 L
ORING 14 P	ORING 14 V	14 S	ORING 30 P	ORING 30 V	30 S
ORING 15 P	ORING 15 V	15 L	ORING 35 P	ORING 35 V	35 L
ORING 16 P	ORING 16 V	16 S	ORING 38 P	ORING 38 V	38 S
ORING 18 P	ORING 18 V	18 L	ORING 42 P	ORING 42 V	42 L



All data are considered to be unbinding reference values. We accept no liability for data selection that is not confirmed in writing. Pressure data refer, if not otherwise indicated, to liquids of Group II at +20°C.