


What is Depth Filtration?



Successfully used in a variety of applications, depth filtration utilises a thick layer of media to effectively trap and retain various particulate. Commonly specified as the first stage of a filtration cascade, more advanced manufacturing techniques have now developed depth cartridges suited to improving downstream filtration.

Cross-Section of a Depth Cartridge



How do Depth Filters Work?

As liquid from the inlet is sent twisting and turning on a tortuous path through the filter cartridge, particles become caught in the densely packed fibres of a depth filter - this sieving or interception is known as mechanical retention. With the introduction of graded-depth filtration, a broad range of particulate can be captured across the entirety of the depth media.

From outside to in, the media fibres become densely packed with larger particulate captured first, allowing smaller particles to be progressively intercepted. As well as the physical interception, fibres also naturally attract particles via Van de Waals force. This adhesion process is known as adsorptive retention.

Typical Applications

Depth filtration offers a myriad of solutions to suit many applications:

- Incoming water
- Pre-RO
- General pre-filtration
- Particulate removal
- High temperatures
- Aggressive solvents
- Food grade compatibility
- High viscosity liquids
- Adhesives
- Paints and inks



SPECTRUM



Wound Polypropylene

0.5-150 micron

The most popular wound cartridge media by far, the SPECTRUM wound polypropylene offers broad chemical compatibility and good temperature resistance at low cost. With over 50 years proven experience and in a variety of micron sizes, across standard and large

diameters, the SWP provides a basic filtration solution perfectly suited for first-stage and general particulate reduction. Whilst newer spun technologies offer higher efficiency and longer life cartridges, wounds still exceed filtration standards in many applications.

Key Features

- Tried and tested with over 50 years of experience
- Broad chemical compatibility
- Constructed using FDA compliant materials

Typical Applications

- General particulate filtration
- Sand, silt and rust removal
- Batch process



Specification

Efficiency

65%

Max. Operating Temperature

65°C

Max. Operating Pressure Differential

2 bar at 21°C



Materials of Construction

Filter Media

Polypropylene

Core

Polypropylene



Compliance

FDA Compliant Material
Regulation (EC) 1935/2004
Regulation (EU) No10/2011



Configurations

Micron (µm)


0.5	1	5	10	25	50	75
100	150					

Length (")


4 7/8	10	20	30	40
-------	----	----	----	----

Diameter

Standard	Large = BB
----------	------------



Dimensions & Packaging



Length (")	Dimension (mm)		
	A	B	C
4 7/8	28	124	63
10	28	254	63
20	28	508	63
30	28	762	63
40	28	1016	63
10BB	30	254	115
20BB	30	508	115

Packaging	
Box Qty	Box Weight (kg)
48	5
24	6
24	12
9	7
9	9
4	3.5
4	7

Part Number

Code	Micron	Length
SWP	0.5, 1, 5, 10, 25, 50, 75, 100, 150	4 7/8, 10, 20, 30, 40
	1, 5, 10, 25, 50, 75, 100	10BB, 20BB


e.g. SWP-25-10

Industry Terms Explained

The filtration industry and its associated technical terms can sometimes be misleading or confusing, with different manufacturers using various testing parameters and terminology to promote certain elements of their products performance. Filerder have compiled a list of technical jargon typically used within the industry to help explain filter performance, benefits and key features.


Classification

This process, sometimes referred to as 'sharp-cut off', removes the targeted contaminants whilst retaining smaller desirable or acceptable particles such as colour, flavour and odour, which are critical to the final product.




Micron Rating Creep

As a filter cartridge is used, the pores within the filter matrix become partially or completely blocked by the retained particulate. This means that particulate smaller than the micron rating of the cartridge can sometimes be filtered from the incoming fluid. Specialised cartridges, such as the CP2, are designed with an advanced fibre matrix to reduce the effects of micron rating creep.



Void Volume & Void Volume

Maximising the available internal space for retained particulate, whilst maintaining cartridge strength and efficiency, is the key to producing an effective filter cartridge. Modern manufacturing techniques use extremely fine fibres resulting in lightweight construction to optimise the void volume of the cartridge, increasing its dirt holding capacity and therefore effectively increasing its service life.



Beta Ratio Explained


The table below shows the relationship between beta ratio and filter efficiency:

Upstream Contaminant Concentration (mg/l)	Downstream Contaminant Concentration (mg/l)	Beta Ratio	Filter Removal Efficiency (%)
10000	1000	10	90
	500	20	95
	100	100	99
	10	1000	99.9
	2	5000	99.98

e.g. upstream ÷ downstream = beta ratio
 10000 ÷ 10 = 1000

Beta Ratio

Bringing a standardised method to determine filter efficiency, beta ratio testing, typically used for high efficiency cartridges, measures controlled contaminant such as AC fine test dust at a specific micron size both upstream and downstream of a filter element. The beta ratio is calculated by dividing the number of particulate recorded on the upstream side of the filter by the number of particulate recorded downstream. The higher the beta ratio, the more efficient the cartridge at that micron rating.



Nominal Efficiency Rating

Nominal rating describes the ability of a filter to remove particulate at the stated micron size and above e.g. 80% at 10 micron. For improved classification and particle reduction **high efficiency** cartridges remove at least 95% of contaminate. There is no standardised method to determine the nominal rating of a filter, therefore some manufacturers will not state their products efficiency or will use larger particulate to increase the value. **To make product comparison and selection as simple as possible, Filder list the particle removal efficiency of each filter at its given micron rating.**



Absolute Efficiency Rating

The absolute rating of a filter describes the diameter of the largest particle that would pass through the filter under laboratory conditions. In the filtration industry it is typically used to describe a filter with an efficiency of 99.9% or above at a specific micron size, e.g. 99.9% at 1 micron. Absolute rated filters are recommended for use in more critical applications and processes where known filtrate quality is essential.