

# Hose Reels

## Air Hose Reel

- Reinforced PU hose
- Tough impact resistant polypropylene construction
- 180° swivel
- Self-layering hose guide for perfectly even hose rewinding
- Speed-controlled return spring
- Auto-locking mechanism allows easy use of hose at any length
- Lightweight



Maximum Working Pressure:  
12 bar



### 9 Metre Hose Length

Part Number	Length mtrs	I.D.	Thread - Inlet	Thread - Outlet
ZA02-9	9	5/16"	1/4" BSPT	1/4" BSPT

## Air & Water Hose Reels

- Reinforced PVC hose
- Tough Impact resistant polypropylene construction
- 180° swivel
- Self-layering hose guide for perfectly even hose rewinding
- Speed-controlled return spring
- Auto-locking mechanism allows easy use of hose at any length
- Carry handle
- Lightweight



Maximum Working Pressure:  
Air: 17 bar



### 10 Metre Hose Length

Part Number	Length mtrs	I.D.	Thread - Inlet	Thread - Outlet
ZA04-10B	10	3/8"	1/4" BSPT	1/4" BSPT



Maximum Working Pressure:  
Air: 17 bar



### 15 Metre Hose Length

Part Number	Length mtrs	I.D.	Thread - Inlet	Thread - Outlet
ZA05-15	15	3/8"	1/4" BSPT	1/4" BSPT
ZA05-15-38	15	3/8"	3/8" BSPT	3/8" BSPT



Maximum Working Pressure:  
Air: 17 bar



### 20 Metre Hose Length

Part Number	Length mtrs	I.D.	Thread - Inlet	Thread - Outlet
ZA05-20B	20	1/2"	3/8" BSPT	3/8" BSPT
ZA05-20B-12	20	1/2"	1/2" BSPT	1/2" BSPT

The connection termination on all CONAH hose reels can be adapted to suit specific requirements.  
For further details, contact our Business Development Team.